


NFA2X 3x70RMAL+95RMAA+25RMAL mm²
0.6/1 (1.2) Kv
HD 626 S1: Part 6 – Section D*



*illustrative only

	<i>Construction</i>	<i>Material</i>	<i>Size</i>	<i>Diameter** (mm)</i>
<i>I</i>	<i>Phase Conductors, 1-2-3</i>	Al	7wires , RMC	9.7
	<i>Neutral Conductor, N</i>	AlMgSi	7wires , RMC	11.4
	<i>PSL Conductor</i>	Al	7wires , RMC	5.9
<i>II</i>	<i>Phase Insulation, TIX-2</i>	XLPE, Bk	Nom.th.: 1.5 mm	12.7
	<i>Neutral Insulation, TIX-2</i>		Nom.th: 1.7 mm	14.8
	<i>Public street lighting conductor, TIX-2</i>		Nom.th: 1.3 mm	8.5

III	Assembly of cores		Hand of lay: Right (Z) Max pitch : 1170 mm	33.2
IV	Core identification			
	Core no. 1		1 longitudinal rib (embossing)	
	Core no. 2		2 longitudinal ribs (embossing)	
	Core no. 3		3 longitudinal ribs (embossing)	
	Core N	Producer name	NFA2X 3x70RM +1x95RM + 1x25RM 0.6/1 kV [year] 0001M	
	Core PSL		4 longitudinal ribs (embossing)	
V	Way of marking,		Ink jet,	
	Core no. N		1 x text marking / 1m of cable	

- *Partial applied; ** informative only!*

Type	Max. current carrying capacity, at conductor temperature 90 °C, in air at 25 °C, direct sunlight, wind velocity 0.6 m/s and maximum solar radiation 1000 W/m ²		Mass of complete cable Approx. [kg/km]
	Max. short circuit temperature, (≤5s) [°C]	Max. continuous load [A]	
NFA2X 3x70+95+25	250	240	1130

** *Max. continuous load for public street lighting conductor: 130 [A]

Applications:

Overhead distribution and service, fixed installations

Electrical characteristics:

Max. electrical DC resistance of phase conductor, @ 20 °C: 0.443 Ω/km

Max. electrical DC resistance of neutral conductor, @ 20 °C: 0.363 Ω/km

Max. electrical DC resistance of public street lighting conductor, @ 20 °C: 1.20 Ω/km



KABLO ELEKTRİK AYD. İNŞ. SAN. ve TİC. A.Ş.

Installation conditions:

Operation temperature: - 25 °C to +40 °C

Min. installation temperature: - 20 °C

(below 0°C special precaution shall be taken)

Min. breaking load of messenger: 27.9 kN

Min. installation bending radius: 640 mm



Fabrika Merkez : Şabanoğlu OSB Mah. Organize San. Bulvarı No.40/1 Tekkeköy - Samsun

Tel:+90 362 26659 25 **Faks:** +90 362 266 61 94 - 26

Fabrika 1 Şube : Kerimbey OSB Mah. Vali M. Erdoğan Cebeci Bulvarı No.54 Tekkeköy - Samsun

İstanbul Şube : Barbaros Mah. Mor Sümbül Sok.No.9 WBC Kat.8 Pk.34746 Batı Ataşehir-İstanbul **Tel:** +90 216 766 25 88

Mersis no : 0-1800- 4427-3100011

Tic Sicil no: 1528 / Tekkeköy

19 Mayıs VD.180 044 2731

www.borsan.com.tr • info@borsan.com.tr • <https://facebook.com/borsangrup> • <https://twitter.com/borsangrup>