



= L-MAX9 =

Size	LI/SI	PR	Depth (mm)	Rim	S/W (mm)	O/W (mm)	Load (kg)	Index (Lbs)	Max Pressure (Kpa/Psi)	UTQG	Sidewall		.O.:	((-1)
185R14C BSW	102/100R	8	9	5 1/2]	188	650	850/800	1875/1765	450/65	-	BSW	С	Е	72
185R14C WSW	102/100R	8	9	5 1/2]	188	650	850/800	1875/1765	450/65	-	WSW	C	E	72
195R14C BSW	106/104R	8	9	5 1/2]	198	666	950/900	2094/1984	450/65	-	BSW	C	Е	72
195R14C WSW	106/104R	8	9	5 1/21	198	666	950/900	2094/1984	450/65	-	WSW	C	E	72
205R14C BSW	109/107R	8	8.5	61	208	686	1030/975	2271/2150	450/65	-	BSW	С	Ε	72
215R14C BSW	112/110R	8	9	61	218	700	1120/1060	2469/2337	450/65	-	BSW	C	E	72
195R15C WSW	89/87R	8	9	5 1/21	170	693	950/900	2094/1984	375/54	-	WSW	C	Е	72
195R15C BSW	90/88R	8	9	5 1/21	177	693	950/900	2094/1984	375/54	-	BSW	C	E	72
165/70R14C BSW	106/104R	6	8.5	51	196	588	580/545	1279/1202	450/65	-	BSW	C	Е	72
175/65R14C BSW	106/104R	6	8.5	51	196	584	600/560	1323/1235	450/65	-	BSW	C	E	72
195/70R15C BSW	104/102R	8	9	61	201	655	900/850	1984/1874	450/65	-	BSW	C	Е	72
215/70R15C BSW	104/101R	8	9	6 1/21	221	683	900/825	1984/1819	450/65	-	BSW	C	E	72
175/75R16C BSW	101/99R	8	9	51	177	668	825/775	1819/1705	475/69	-	BSW	C	Е	72
195/75R16C BSW	107/105R	8	9	5 1/21	196	698	975/925	2149/2039	475/69	-	BSW	C	E	72
205/65R16C BSW	107/105R	8	9	61	209	672	975/925	2149/2039	475/69	-	BSW	С	E	72
215/65R16C BSW	109/107R	8	9	6 1/21	221	686	1030/975	2271/2150	475/69	-	BSW	C	Е	72
225/65R16C BSW	112/110R	8	9	6 1/2	228	698	1120/1060	2469/2337	475/69	-	BSW	С	E	72
235/65R16C BSW	115/113R	8	9	71	240	712	1215/1150	2679/2535	475/69	-	BSW	C	E	72



^{*} New Developing Sizes / The Labeling Information Is Subject To Change Without Notice.