

ÖZTİRYAKİLER

Cumhuriyet Mah.Hadımköy Yolu Cad.No:8 Büyükçekmece-İstanbul-TURKEY e-mail: export@oztiryakiler.com.tr

web: www.oztiryakiler.com.tr

code:

COLD UNITS

model: GN 600.00 NTV

79E4.06NTV.00

SINGLE SOLID DOOR GN SIZE VERTICAL TYPE REFRIGERATOR











REFRIGERATORS MAIN FEATURES

- * Digital control with cabinet temperature display and setting and manual activation of defrost cycle. Fully compliant HACCP digital controls include visible alarms, open door, hi-lo temp,condenser temp etc.
- * Large storage area suitable to contain 2/1 GN containers or shelves on anti-tilt pressed runners.
- * Optimized back to front forced air flow provide even temperature distribution and fast cooling in any conditions.
- * Automatic defrost.
- Performance guaranteed at ambient temperatures of +43°C
- * Cabinet fitted with up to 60 mm thickness of polyurethane insulation for best insulating performance with 100% environmental protection.
- * Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption.
- * Cleaning-free condenser: the structure of the wire frame condenser prevents dust and grease accumulation thus avoiding periodical cleaning operations and reducing energy consumption.
- Automatic evaporation of the defrosting water by hot gas on the top for energy saving.

CONSTRUCTION

- Interior cabinet constructed from the highest quality AISI 304 stainless steel, exterior is from AISI 430.
- * External back, bottom and top in galvanized steel.
- * $\,$ Interior base with corners, pressed from a single sheet.
- * Easy access to the main components for maintenance.
- * Mounted on adjustable Stainless steel feet.
- * High density (40-42 kg/m³) polyurethane CFC and HCFC-free insulation.
- * Door switch stops the fan when door is opened to avoid cold air exiting the cell, thus saving energy.
- Doors are self-closing and can be fully opened up to 180.
- * Right hinged door as factory setup, door assembly ready for interchangeable to the left side opening .

*

OPTIONS

- * Wheels
- * Stainless steel shelf
- * Interior led lighting.
- Lockable door

ACCESSORIES

* Plastic coated shelf 3 Pcs.

STANDARDS

* EN 60335-1 European Standard relating to safety of household and similar electrical appliances

* EN 60335-2-89 European Standard relating to particular requirements for commercial refrigerating

appliances with an incorporated or remote refrigerant unit or compressor





ÖZTİRYAKİLER

Cumhuriyet Mah.Hadimköy Yolu Cad.No:8 Büyükçekmece-İstanbul-TURKEY e-mail: export@oztiryakiler.com.tr

web: www.oztiryakiler.com.tr COLD UNITS code: model: 79E4.06NTV.00 SINGLE SOLID DOOR GN SIZE VERTICAL TYPE REFRIGERATOR GN 600.00 NTV 1865 840 DIMENSIONS (Shipping) **DIMENSIONS (Net)** Width (mm) Width (mm) 890 Depth (mm) 840 Depth (mm) 2020 Height (mm) 2070 Height (mm) Weight (kg) 140 Weight (kg) 148 Volume (m³) 1,30 **TECHNICAL SPECIFICATIONS** 0/+10 °C cabinet capacity 560 L cooling temperature T (tropical), +43 °C - %65 Rh cooling Gas type R134a climate class ventilated * cooling capacity 0,24 cooling system (t)**ELECTRICITY** Power: 0,3 230V / NPE 50 Hz Supply Voltage: **Protection Class: IP** 21 **WATER-IN** Cold Water Inlet: °C Pressure (min-max) bar kPa Temperature (min-max) Hot Water Inlet: Hardness: DRAIN