

# Destination®

## Peripheral Guiding Sheath



Destination® Guiding Sheath is designed to perform as a guiding catheter and an introducer sheath.

Destination® is designed to be used for the introduction of interventional and diagnostic devices into the human vasculature, including but not limited to lower extremity, renal arteries, and carotid arteries.

### Product Characteristics

- Coil reinforcement inside the sheath which provides high anti-kinking characteristics
- Hydrophilic coating at the distal part of the sheath for good trackability
- Secured hemostasis tailored by Terumo's unique cross-cut valve (CCV items)
- Soft atraumatic tip
- PTFE inner layer which provides smooth device passage
- 5 different tip configurations available

### General Specifications

Maximum guidewire size	0.038" / 0.97 mm
Radiopaque marker	Gold coil marker at 5 mm from the distal tip of the sheath
Reinforcement inside the sheath	Stainless steel coil
Sheath inner layer	PTFE polytetrafluoroethylene

### Item Specifications

Inner diameter	Length	Shape	Valve	Hydrophilic coating length	Item reference
5 Fr / 0.076" / 1.9 mm	45 cm	Straight	CCV*	5 cm	GS*F5ST1C45
5 Fr / 0.076" / 1.9 mm	45 cm	Hockey stick	CCV	5 cm	GS*F5HS1C45
5 Fr / 0.076" / 1.9 mm	45 cm	Multipurpose	CCV	5 cm	GS*F5MP1C45
5 Fr / 0.076" / 1.9 mm	45 cm	Renal Double Curve	CCV	5 cm	GS*F5RDCC45
5 Fr / 0.076" / 1.9 mm	45 cm	Left Internal Mammary Artery	CCV	5 cm	GS*F5LIMC45
6 Fr / 0.087" / 2.2 mm	45 cm	Straight	CCV	5 cm	RSR01
6 Fr / 0.087" / 2.2 mm	45 cm	Hockey stick	CCV	5 cm	RSR02
6 Fr / 0.087" / 2.2 mm	45 cm	Multipurpose	CCV	5 cm	RSR03
6 Fr / 0.087" / 2.2 mm	45 cm	Renal Double Curve	CCV	5 cm	RSR13
6 Fr / 0.087" / 2.2 mm	45 cm	Left Internal Mammary Artery	CCV	5 cm	RSR14
7 Fr / 0.101" / 2.5 mm	45 cm	Straight	CCV	5 cm	RSR04
7 Fr / 0.101" / 2.5 mm	45 cm	Hockey stick	CCV	5 cm	RSR05
7 Fr / 0.101" / 2.5 mm	45 cm	Multipurpose	CCV	5 cm	RSR06
7 Fr / 0.101" / 2.5 mm	45 cm	Renal Double Curve	CCV	5 cm	RSR15
7 Fr / 0.101" / 2.5 mm	45 cm	Left Internal Mammary Artery	CCV	5 cm	RSR16
8 Fr / 0.115" / 2.9 mm	45 cm	Straight	CCV	35 cm	54-84501
6 Fr / 0.087" / 2.2 mm	65 cm	Straight	CCV	35 cm	RSP01
7 Fr / 0.101" / 2.5 mm	65 cm	Straight	CCV	35 cm	RSP02
8 Fr / 0.115" / 2.9 mm	65 cm	Straight	CCV	35 cm	54-86501
5 Fr / 0.076" / 1.9 mm	90 cm	Straight	TBV**	15 cm	GS*K5ST1T90B
5 Fr / 0.076" / 1.9 mm	90 cm	Multipurpose	TBV	15 cm	GS*K5MP1T90B
5 Fr / 0.076" / 1.9 mm	90 cm	Straight	CCV	15 cm	GS*K5ST1C90B
5 Fr / 0.076" / 1.9 mm	90 cm	Multipurpose	CCV	15 cm	GS*K5MP1C90B

\*CCV = cross-cut valve. \*\*TBV = Tuohy-Borst Valve.

Inner diameter	Length	Shape	Valve	Hydrophilic coating length	Item reference
6 Fr / 0.087" / 2.2 mm	90 cm	Straight	TBV	15 cm	RSC01
6 Fr / 0.087" / 2.2 mm	90 cm	Multipurpose	TBV	15 cm	RSC03
6 Fr / 0.087" / 2.2 mm	90 cm	Straight	CCV	15 cm	RSC05
6 Fr / 0.087" / 2.2 mm	90 cm	Multipurpose	CCV	15 cm	RSC07
7 Fr / 0.101" / 2.5 mm	90 cm	Straight	TBV	15 cm	RSC02
7 Fr / 0.101" / 2.5 mm	90 cm	Multipurpose	TBV	15 cm	RSC04
7 Fr / 0.101" / 2.5 mm	90 cm	Straight	CCV	15 cm	RSC06
7 Fr / 0.101" / 2.5 mm	90 cm	Multipurpose	CCV	15 cm	RSC08
8 Fr / 0.115" / 2.9 mm	90 cm	Straight	CCV	60 cm	54-89001
8 Fr / 0.115" / 2.9 mm	90 cm	Straight	TBV	60 cm	54-89006

All dilators are 0.038" (0.97 mm) wire compatible  
Please quote above item reference codes when placing an order