

NINGBO HORARI LIGHTING					
SL705 TECH. INFO					
Model	SL705	SL705	SL705		
Power	30W	60W	90W		
Solar panel	6V/7W	6V/9W	6V/13W		
Battery	3.2V 5000mAH	3.2V10000mAH	3.2V 15000mAH		
Chip	2835/48pcs	2835/96pcs	2835/144pcs		
Efficiency of LIGHT	90-100lm/w	90-100lm/w	90-100lm/w		
RA	>70	>70	>70		
PF	>0.9	>0.9	>0.9		
IP	IP65	IP65	IP65		
Body maerial	ABS	ABS	ABS		
Solar panel size	195*55*390MM	220*55*485MM	240*60*620MM		
Color temperature	6500K±500K	6500K±500K	6500K±500K		
Working time	13h±1h	13h±1h	13h±1h		
Rainy days	2days	2days	2days		
Charging time	3-5H	3-5H	3-5H		
Control mode	Light control （Working in the evening）+ radar sensor 100%lighting when people come,10%lighting when people leave				
Sensor distance	10-12M	10-12M	10-12M		
Height of pole	3-6Meters	3-7Meters	3-8Meters		
Working temperature	-25°C-60°C	-25°C-60°C	-25°C-60°C		
Lighting area	60m²	80m²	110m²		
Chip life	≥50000h	≥50000h	≥50000h		