





Specificații tehnice

[Acest tabel va fi completat de către **ofertant în coloanele 2, 3, 4, 6, 7**]

Numărul procedurii de achiziție: Informația o găsiți în SIA RSAP.						
Obiectul achiziției: Echipamente de producție video: pedestal și multicam recorder						
Denumirea bunurilor/ serviciilor	Denumirea modelului bunului/ serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standard e de referință
1	2	3	4	5	6	7
Lotul nr. 6						
6.1. Camera Headset	HMD-660X	China	Superlux	Headset Dynamic; Circumaural; Closed; SPL: 96 dB; Impedance: 150 Ω; Frequency range: 10 - 30,000 Hz; Input power: 100 mW; Microphone: Dynamic; Frequency range: 150 - 10000 Hz; SPL: 136 dB; Impedance: 250 Ω 3 m Spiral cable with 3.5 mm stereo mini jack for headphones and 6.3 mm screwable adapter - XLR microphone connection 	Headset Dynamic; Circumaural; Closed; SPL: 96 dB; Impedance: 150 Ω; Frequency range: 10 - 30,000 Hz; Input power: 100 mW; Microphone: Dynamic; Frequency range: 150 - 10000 Hz; SPL: 136 dB; Impedance: 250 Ω 3 m Spiral cable with 3.5 mm stereo mini jack for headphones and 6.3 mm screwable adapter - XLR microphone connection 	
6.2. Camera Headset	HMD685	China	Superlux	Intercom Headset Transducer principle Dynamic, Closed; Ear coupling Circumaural; Sensitivity 96 dB SPL Frequency Response 20-20,000Hz; Max. Input Power 100 Mw; Rated Impedance 400 Ω (Copper-coated aluminum wire); Earpads Leatherette; Caliper Pressure Approx. 4.5 N Connector 1.5-meter (4.92') straight cord; 4-pin XLR female plug; Finish Black Microphone; Transducer principle Dynamic, Cardioid; Frequency response 50-15,000 Hz 	Intercom Headset Transducer principle Dynamic, Closed; Ear coupling Circumaural; Sensitivity 96 dB SPL Frequency Response 20-20,000Hz; Max. Input Power 100 Mw; Rated Impedance 400 Ω (Copper-coated aluminum wire); Earpads Leatherette; Caliper Pressure Approx. 4.5 N Connector 1.5-meter (4.92') straight cord; 4-pin XLR female plug; Finish Black 	

				Polar Pattern Cardioid; Output voltage-64 dBV/Pa at; 1 kHz; Impedance 250 Ω	Microphone; Transducer principle Dynamic, Cardioid; Frequency response 50-15,000 Hz Polar Pattern Cardioid; Output voltage-64 dBV/Pa at; 1 kHz; Impedance 250 Ω	
--	--	--	--	--	---	--

Semnat: Semnat electronic Numele, Prenumele: Carabut Vladislav În calitate de: Director

Ofertantul: SC "Muzic-Prod" S.R.L. Adresa: Moldova, Chisinau, Ion Creanga

****Coloanele 2, 3, 4, 6, 7 se completează fără nici o abatere de la formular. Completarea defectuoasă a formularului atrage respingerea ofertei.***