

EC CERTIFICATE OF COMFORMITY

VEHICLE CATEGORY N2 (Incomplete Vehicles)

The Undersigned;

FEVZİ BALCI

(GROUP LEADER)

hereby certifies that;

0.1. Make (Trade name of manufacturer)	BMC
0.2. Type	415N22
Variant (a)	NYSL411
Version (a)	90Y39120M75VI
0.2.1. Commercial name	BMC 417
0.4. Vehicle category	N2
0.5. Name and address of manufacturer	BMC OTOMOTİV SANAYİ VE TİCARET A.Ş. Kemalpaşa Cad. No: 32 35060 İZMİR
0.6. Location and method of attachment of the statutory plates	IN THE CABIN, AT THE BEHIND SIDE OF THE DRIVER SEAT - RIVETED.
Location of the identification number	IT IS MOUNTED WITH THE NUMBERS ON THE RIGHT CHASSIS ARM.
0.9. Name and address of the manufacturer's representative (if any)	-
0.10. Vehicle identification number	NMC415CDSLH600153
0.11. Date of Manufacture of Vehicle	18.12.2024

conforms in all respects to the type described in approval (TR*2007/46*8128*04) type-approval number including extension number) issued on 26/04/2024 and cannot be permanently registered without further approvals.

Place /Date: İZMİR 03.03.2025	Signature:  BMC OTOMOTİV SAN. ve TİC. A.Ş.
---	--

General construction characteristics

1. Number of axles	2	and wheels	6
1.1. Number and position of axles with twin wheels	1		2. AXLE
2. Steered axles (number, position)			1, FRONT
3. Powered axles (number, position, interconnection)			1, (2nd AXLE)

Main dimensions

4. Wheelbase		4.1. Axle spacing	
1-2	3845 mm	2-3	-
5.1. Maximum permissible length		12000 mm	6.1. Maximum permissible width
			2550 mm
8. Fifth wheel lead for semi-trailer towing vehicle (maximum and minimum)		-	
12.1. Maximum permissible rear overhang		7045 mm	

Masses

14. Mass of the incomplete vehicle in running order 14.2 Actual Mass		2975 kg	
14.1. Distribution of this mass amongst the axles			
1. 1865 kg	2. 1110 kg	3. -	4. -
15. Minimum mass of the vehicle when completed		2975 kg	
15.1. Distribution of this mass amongst the axles			
1. 1865 kg	2. 1110 kg	3. -	4. -
16. Technically permissible maximum masses			
16.1. Technically permissible maximum laden mass		9000 kg	
16.2. Technically permissible mass on each axle			
1. 3200 kg	2. 6400 kg	3. -	4. -
16.3. Technically permissible mass on each axle group			
1. -	2. -	3. -	4. -
16.4. Technically permissible maximum mass of the combination			
17. Intended registration/in service maximum permissible masses in national/international traffic		9000 kg	
17.1. Intended registration/in service maximum permissible laden mass			
17.2. Intended registration/in service maximum permissible laden mass on each axle			
1. -	2. -	3. -	4. -
17.3. Intended registration/in service maximum permissible laden mass on each axle group			
1. -	2. -	3. -	4. -
17.4. Intended registration/in service maximum permissible mass of the combination		- kg	
18. Technically permissible maximum towable mass in case of			
18.1. Drawbar trailer		-	18.2. Semi-trailer
18.3. Centre-axle trailer		-	18.4. Unbraked trailer
19. Technically permissible maximum static mass at the coupling point			

Power plant

20. Manufacturer of the engine		CUMMINS	
21. Engine code as marked on the engine		B4.0EVI170	
22. Working principle		COMPRESSION IGNITION	
23.1. Hybrid (electric) vehicle		-	
23.2. Pure electric		-	
24. Number and arrangement of cylinders		4 INLINE	
25. Engine capacity		3956 cm3	
26. Fuel		DIESEL	
26.1. Mono Fuel / Bi fuel / Flex fuel		-	
27. Maximum net power		125 kW @ 2400RPM	
28. Gearbox (type)		MANUAL	

Maximum speed

29. Maximum speed	90 km/h
-------------------	---------

Axles and suspension

31. Position of lift axle (s)	-
32. Position of loadable axle (s)	-
33. Drive axle(s) fitted with air suspension or equivalent	-
35. Tyre /wheel combination	215/75 R 17.5 / 4x2/2

Brakes

36. Trailer brake connections mechanical/electric/pneumatic/hydraulic	-
37. Pressure in feed line for trailer braking system.....bar	-

Coupling device

44. Approval number or approval mark of coupling device (if fitted)	-
45. Types or classes of coupling devices which can be fitted	-
45.1. Characteristics values	D..... / V..... / S..... / U.....

Environment performance

46. Sound level Stationary: 84 dB(A) at engine speed: 1800 min-1 Drive-by: 75 dB(A)	
47. Exhaust emission level: EURO VI OBDE	
48. Exhaust emissions	
Number of the base regulatory act and latest amending regulatory act applicable EU 595/2009...EU 2019/1939	
1.1. test procedure: ESC / WHSC EURO VI	
CO:	0.0059 gr/kWh
THC:	0.0008 gr/kWh
NOx:	0.151 gr/kWh
THC+NOx:	0.1518 gr/kWh
Particulate:	0.0029 gr/kWh
NH3: 0.3 5 ppm Particulate: 5.84E+11	
2. test procedure: ETC / WHTC EURO VI	
CO:	0.028 gr/kWh
NOx:	0.072 gr/kWh
NMHC:	- gr/kWh
THC:	0.008 gr/kWh
CH4:-	NH3: 0,24 ppm
Particulate:	1.96E+11 48.1 CORRECTED VALUE OF SMOKE ABSORPTION COEFFICIENT (m ⁻¹): On the engine sticker

Miscellaneous

52. Remarks: The vehicle has 1 driver seat and 2 crew seats.
--