

**THE NETHERLANDS**
(N E D E R L A N D)**COMMUNICATION**

Concerning ⁽¹⁾:

- approval granted
- ~~approval extended~~
- ~~approval refused~~
- ~~approval withdrawn~~
- ~~production definitely discontinued~~

of a type of pneumatic tyre for motor vehicles pursuant to Regulation number 30.




Approval number: E4-30R-0275234

Extension number: 00

1. Manufacturer's name or trade mark(s) on the tyre type : UNIGRIP
2. Tyre type designation by the manufacturer : ROAD FORCE H/T
3. Manufacturer's name and address : Shandong New Continent Tire Co., Ltd.
Lushan Project Area, Economic Development Zone,
Yishui, Shandong, China 276400
4. If applicable, name and address of the manufacturer's representative : not applicable
5. Summarised description
 - 5.1. Tyre size designation : 225/65R17
 - 5.2. Category of use : ~~normal~~/snow/~~special use~~/~~temporary use~~ ⁽¹⁾
 - 5.3. Structure : ~~diagonal~~/~~bias belted~~/radial/~~run flat tyre~~ ⁽¹⁾
 - 5.4. Speed category symbol : H
 - 5.5. Load-capacity index : 102

6. Technical service and, where applicable, test laboratory approved for purposes of approval or of verification of conformity : TÜV Rheinland Kraftfahrt GmbH
Technologiezentrum Verkehrssicherheit
Typprüfstelle Fahrzeuge/Fahrzeugteile
Am Grauen Stein
D-51105 Köln (Poll)
7. Date of report issued by that service : September 20, 2014
8. Number of report issued by that service : 86-R30-0241/14-00
9. Reason(s) of extension (if applicable) : N.A.
10. Any remarks : ---
11. Approval : granted/~~extended/refused/withdrawn~~⁽¹⁾
12. Place : Zoetermeer
13. Date : 02-OCT-2014
14. Signature :
15. The list of documents in the approval file which are deposited at the administrative service having delivered the approval and which can be obtained upon request.
- Application form relating to ECE approval for a pneumatic tyre pursuant to Regulation number 30.
- The drawing of the tyre's sidewalls, tread and dimensioned cross-section.
- The test report as mentioned in item 8.

⁽¹⁾ Strike out what does not apply.



TREAD PATTERN
REFER TO ATTACHMENT NO.1

10	MAX.LOAD 850 kg(1874 lbs) MAX.PRESS 300 kPa(44 psi)	
9	PLIES: TREAD 2 POLYESTER + 2 STEEL + 1 NYLON SIDEWALL 2 POLYESTER	
8	MADE IN CHINA	
7	PRODUCT DATE	
6	DOT ****	
5	STEEL BELTED RADIAL TUBELESS	
4	102H	
3	225/65R17	13 M+S
2	REFER TO ATTACHMENT NO.1	12 SAFETY WARNING
1	REFER TO ATTACHMENT NO.1	11 0275234

225/65R17	102	H	T/L	724±7	228±8	165	8.2±0.3	2014.08.16
TIRE SIZE	LOAD INDEX	SPEED SYMBOL	TYPE	A (mm)	B (mm)	C (mm)	SKID DEPTH (mm)	DATE
CHECKED BY	刘杰		APPROVED BY	张峰		山东新大陆橡胶科技股份有限公司 SHANDONG NEW CONTINENT TIRE CO.,LTD		

Tyre size : 225/65R17
Manufacturer : Shandong New Continent Tire Co., Ltd.

TEST REPORT

according to the ECE-Regulation

Uniform provisions concerning the approval of pneumatic tyres for motor vehicles and their trailers

including all amendments until
... ECE-R30, Amend.02, Suppl. 17...

Approval Status

ECE approval : E4-30R-0275234 Ext.00

Structure of the Test Report

Item No.

- | | |
|----|-------------------------|
| 0. | General information |
| 1. | Tested object(s) |
| 2. | Test record |
| 3. | List of appendices |
| 4. | Statement of conformity |
-

The Test Report shall be reproduced and published in full by the client only. It shall however be reproduced partially with the written permission of the Testing Laboratory only.

Tyre size : 225/65R17
 Manufacturer : Shandong New Continent Tire Co., Ltd.

0. General Information

- 0.1. Trade name or mark(s) : UNIGRIP
- 0.2. Tyre type designation(s) by the manufacturer : ROAD FORCE H/T
- 0.3. Tyre size designation : 225/65R17
- 0.4. Manufacturer's name and address : Shandong New Continent Tire Co., Ltd.
Lushan Project Area, Economic Development Zone,
Yishui, Shandong, China 276400
- 0.5. No. of the information folder : n/a
-Date of issue : August 16, 2014
-Date of last change : ---

1. Tested object(s)

- 1.1. Object markings
- Trade name or mark : UNIGRIP
- Tyre type designation : ROAD FORCE H/T
- Plies of Tread / Sidewall : 2 POLYESTER + 2 STEEL + 1 NYLON /
2 POLYESTER
- Tyre size designation : 225/65R17
- Category of use : Snow
Indication of category of use : Word "M+S"
- Structure : radial
indication / symbol of structure : word "RADIAL", letter "R" in front of rim diameter
marking
- Speed category : H
- Load-Capacity Indices(L.I.) : 102
- Word in case of without inner tube : TUBELESS
- Word in case of reinforced tyre : n/a(Standard tyre)
- Date of manufacture : 3014
- 1.2. Worst case selection : n/a
- 1.3. Remarks : All versions of the types as stated in the information
folder are covered by the tested object(s) respectively.

Tyre size : 225/65R17
 Manufacturer : Shandong New Continent Tire Co., Ltd.

2. Test record

2.1. Equipment for measuring and testing : The test facilities / measurement equipment used were in compliance with the test requirements

2.2. Test results

Remarks concerning extension : ~~The type has been tested according to the modification(s) mentioned in appendix 0.~~

~~An actual practical test of the object was not necessary.~~
~~The results of the previous test(s) are still valid.~~

2.2.1. Dimension measurement according to Annex 6

Measuring rim : 6.5J x 17

Inflation pressure after mounting on measuring rim : 3.0 bar

Inflation pressure before conditioning : 1.8 bar

Conditioning of tyre : more than 24 hours

Inflation pressure after conditioning : 1.8 bar

Overall width at six equally spaced points				Height of six equally spaced tread wear indicators			
1.	228.7 mm	4.	229.0 mm	1.	1.8 mm	4.	1.9 mm
2.	228.9 mm	5.	228.4 mm	2.	1.8 mm	5.	1.8 mm
3.	228.9 mm	6.	228.7 mm	3.	1.8 mm	6.	1.8 mm
Max.:	229.0 mm						

Circumference : 2274 mm

Outer diameter : 723.8 mm

Tread depth / void to fill ratio in case of special use tyre : n/a

2.2.2. Load/speed performance test according to Annex 7

Test machine : GX-YLSN-1112

Diameter of test drum : 1.707 m

Test rim : 6.5J x 17

Inflation pressure before conditioning : 2.8 bar

Conditioning of tyre : more than 3 hours

Test-room temperature : 30.2 ~ 34.2 °C

Inflation pressure after conditioning : 2.8 bar

Tyre size : 225/65R17
 Manufacturer : Shandong New Continent Tire Co., Ltd.

Circumference before testing : 2275 mm

Outer diameter : 724.2 mm

Test load (80%) : 680 kg

Step	Step-Duration [min]	Total Duration [min]	Actual speed (km/h)
1.	10	10	0 – 170
2.	10	20	170
3.	10	30	180
4.	10	40	190
5.	20	60	200

Conditioning after testing : more than 6 hours

Circumference after conditioning, after testing : 2289 mm

Outer diameter : 728.6 mm

Difference outer diameter before and after testing (max. 3.5 %) : 4.4 mm
 : 0.61 %

Inspection after test : The tyre does not exhibit tread separation, ply separation, cord separation, chunking or broken cords.

2.3. Additional information : The results of the test refer exclusively to the object(s) mentioned under point 1. of this report.

Test site : Shandong New Continent Tire Co., Ltd.
 Lushan Project Area, Economic Development Zone,
 Yishui, Shandong, China 276400

Test date : Sep. 03 ~ 04, 2014

2.4. Remarks : ---

3. List of Appendices

Appendix 0 : List of modifications

4. Statement of conformity

The above mentioned information folder and the type described in that comply with the requirements mentioned on page 1. The mentioned test results refer to the object(s) described under point 1.1 of this report.

Engineering centre Shanghai, / September 20, 2014
 SR / AY



Su Rui
 Expert Technical Service

Tyre size : 225/65R17
Manufacturer : Shandong New Continent Tire Co., Ltd.

List of modifications

Appendix 0

Correction of : ---

Modification of : ---

Addition of : ---

Deletion of : ---