To Whom it May Concern

30 October 2024

Certificate of conformity to standards IEC 60118-0

This certificate confirms that OTICON hearing aids (Oticon Jet BTE, Oticon Play PX miniBTE T, Oticon PG10 BTE SP) presented for LP no. MTender ID ocds-b3wdp1-MD-1726664629180 (Acquisition of medical devices (hearing aids), in order to achieve the National Program on hearing aids, for 2025) have been measured according to IEC 60118-0 (Measurement of the performance characteristics of hearing aids) and international standards.

Oticon Jet 2 BTE

Maximum output: 130 dB;

Maximum gain: 66 dB;

Frequency range: 105 Hz - 7500 Hz

Noise level (omni): 21 dB;

Harmonic distortion coefficient:

500 Hz - <2%

800 Hz - 2%

1600 Hz - <2%

Oticon Play PX 2 miniBTE T

Maximum output: 132 dB;

Maximum gain: 63 dB;

Frequency range:100 Hz - 9500 Hz

Noise level (omni): 18 dB;

Harmonic distortion coefficient:

500 Hz - <4%

800 Hz - <4%

1600 Hz - <2%



Main +45 3917 7100 CVR no. 42334219





Oticon PG10 BTE SP

Maximum output:143 dB;

Maximum gain: 83 dB;

Frequency range: 100 Hz - 6500 Hz;

Noise level (omni): 18 dB;

Harmonic distortion coefficient:

500 Hz - <4%

800 Hz - <2%

1600 Hz - <2%

Yours sincerely

Oticon A/S

Claus F. Horneman

Regional Sales Director

oticon