

COMMUNICATION



106R-000326

issued by : Ministry of Transport
L.Svobody 1222/12
110 15 Praha 1
Czech Republic

concerning: ^{1/}

~~APPROVAL GRANTED~~
APPROVAL EXTENDED
~~APPROVAL REFUSED~~
~~APPROVAL WITHDRAWN~~
~~PRODUCTION DEFINITELY DISCONTINUED~~

of a type of pneumatic tyre for agricultural vehicles pursuant to Regulation No. 106

Approval No.: **106R-000326**

Extension No. : **01**

1. Manufacturer's name or trade mark (s) of the tyre: **PETLAS**
2. Tyre type designation by the manufacturer: **UN-1**
3. Manufacturer's name and address: **PETLAS TYRE INDUSTRY
AND TRADE COMPANY
Gölkhisar Mevkii
40200 Kirsehir
TURKEY**
4. If applicable, name and address of manufacturer's representative: **N/A**
5. Summarized description:
 - 5.1. Size of tyre: **see tyre dimensions list**
 - 5.2. Category of use: **Implement - Trailer**
 - 5.3. Structure: **diagonal (bias-ply)/bias belted/radial** ^{1/}
 - 5.4. Speed category symbol: **see tyre dimensions list**
 - 5.5. Load-capacity index:
 - 5.5.1. for traction (implement only): **-**
 - 5.5.2. for trailer (implement only): **see tyre dimensions list**



5.6. Whether the tyre is to be fitted with or without an inner tube ~~TUBE TYPE~~ / TUBELESS

5.7. The supplementary service description, if applicable: -

6. Technical Service and, where applicable,
test laboratory approved for purposes
of approval or of verification of conformity:

IGTT a.s.
Šternberská 446, Louky,
763 02 ZLÍN
CZECH REPUBLIC

7. Date of report issued by that service:

-

8. Number of report issued by that service:

-

9. Reason(s) of extension (if applicable):

New dimensions added

10. Any remarks:

-

11. Place:

Praha

12. Date:

04.06.2018

13. Signature:


Marek Brázdá
Marek Brázdá

14. Annexed to this communication is a list of documents in the approval file deposited at the Administrative Services having delivered the approval and which can be obtained upon request

List of attached documents

- Application for approval

^{1/} Strike out what does not apply.



Annex No.1

Tyre dimensions list from the same range

LIST OF SIZES COVERED BY REPRESENTATIVE TYRE	
SIZE	LOAD /SPEED INDEX
10.0/75-15.3 10PR	123 A8
10.0/75-15.3 10PR TL	123 A8
10.0/75-15.3 10PR TL REINFORCED	123 A8
10.0/75-15.3 12PR TL	126 A8
10.0/75-15.3 12PR TL REINFORCED	126 A8
10.0/75-15.3 14PR TL	130 A8
11.5/80-15.3 12PR TL	135 A8
11.5/80-15.3 12PR	135 A8
11.5/80-15.3 12PR TL REINFORCED	135 A8
11.5/80-15.5 14PR TL	139 A8
12.5/80-15.3 12PR TL	139 A8
12.5/80-15.3 12PR TL REINFORCED	139 A8
12.5/80-15.3 16PR TL	144 A8
10.5/65-16 10PR	123 A8
10.5/80-18 10PR	131 A8
10.5/80-18 12PR	137 A8
10.5/80-18 14PR	142 A8
12.5/80-18 12PR	142 A8
13.0/65-18 12PR	138 A8
13.0/65-18 14PR	141 A8
400/60-15.5 14PR TL	145 A8
400/60-15.5 14PR TL	145 A8
400/60-15.5 16PR TL	147 A8
400/60-15.5 18PR TL	149 A8
340/55-16 12PR TL	140 A8
15.0/55-17 14PR TL	137 A8
19.0/45-17 12PR TL	141 A8
500/50-17 10PR TL	143 A8
500/50-17 14PR TL	149 A8



APPLICATION FOR APPROVAL REGARDING ECE R106

1. Manufacturer's name or trade mark(s) on the tyre type : PETLAS
2. Tread pattern designation by the manufacturer : UN-1
3. Manufacturer's name and address : PETLAS TYRE INDUSTRY AND TRADE COMPANY.
Golhisar Mevkii 40200
Kirsehir TURKIYE
4. Summarised description for worst case tyre
 - 4.1. Size : 12.5/80-15.3 16PR UN1 TL 144 A8
 - 4.2. Category of use : Implement - Trailer
 - 4.3. Structure : Diagonal (Bias - Ply)
 - 4.4. Speed Category symbol : A8
 - 4.5. The load – capacity index : 144
 - 4.6. Tube or Tubeless type : TUBELESS
 - 4.7. Rims on which the tyre can be mounted : 9,00
 - 4.8. Measuring rims and test rims : 9,00
 - 4.9. The factor X : 0,74
 - 4.10. Cold inflation pressure(psi) : 71
 - 4.11. Inflation Pressure(psi) : 71
 - 4.12. Water Burst Test Pressure (kpa) : 1000

Attachment

1. Drawings of tread patterns

Product Performance Evaluation Manager



APPLICATION FOR APPROVAL REGARDING ECE R106

5. WORST CASE REPRESENTATIVE TYRES:

5.1.WATER BURST TEST:

WATER BURST TEST REPRESENTATIVE TYRE		
SIZE	LOAD / SPEED INDEX	REASON TO BE WORST CASE
12.5/80-15.3 16PR TL	144 A8	MAXIMUM INFLATION PRESSURE LOWEST LOAD INDEX

For Technical Drawings of Representative Tyres, Please See Attachment.

6. LIST OF SIZES COVERED BY REPRESENTATIVE TYRES:

LIST OF SIZES COVERED BY REPRESENTATIVE TYRE	
SIZE	LOAD /SPEED INDEX
10.0/75-15.3 10PR	123 A8
10.0/75-15.3 10PR TL	123 A8
10.0/75-15.3 10PR TL REINFORCED	123 A8
10.0/75-15.3 12PR TL	126 A8
10.0/75-15.3 12PR TL REINFORCED	126 A8
10.0/75-15.3 14PR TL	130 A8
11.5/80-15.3 12PR TL	135 A8
11.5/80-15.3 12PR	135 A8
11.5/80-15.3 12PR TL REINFORCED	135 A8
11.5/80-15.5 14PR TL	139 A8
12.5/80-15.3 12PR TL	139 A8
12.5/80-15.3 12PR TL REINFORCED	139 A8
12.5/80-15.3 16PR TL	144 A8
10.5/65-16 10PR	123 A8
10.5/80-18 10PR	131 A8
10.5/80-18 12PR	137 A8
10.5/80-18 14PR	142 A8
12.5/80-18 12PR	142 A8
13.0/65-18 12PR	138 A8
13.0/65-18 14PR	141 A8
400/60-15.5 14PR TL	145 A8
400/60-15.5 14PR TL	145 A8
400/60-15.5 16PR TL	147 A8
400/60-15.5 18PR TL	149 A8
340/55-16 12PR TL	140 A8
15.0/55-17 14PR TL	137 A8
19.0/45-17 12PR TL	141 A8
500/50-17 10PR TL	143 A8
500/50-17 14PR TL	149 A8

