


Coresponderea bunurilor oferite cerințelor din caietul de sarcini

	Cerintele din caietul de sarcini	Oferta
<p>Valve pneumatice</p>	<p>Rated voltag - 24V DC; Electrical entry (D) - DIN connector (with connector); Indicator light and surge voltage suppressor- Norre; Port size (10) -1; Thread(F)-G(PF); Flow path - External pilot (N.O./N.L.); Pilot valve option - Standard; Actiation - Common to NC, No; Response time - 30ms or less (at 0.5MPa); Max. operating frequer-rcy - 5cis (Min. operating freqrrency: 1cl30days as per JIS BB374 19B1); Ambient and fluid temperature Max.50'C; Lubrication - Not requirret (Use turbine oil class 1 ISO VG32 if lubrication is required); Manual override - Non-locking push style; Mounting position - Free Impact/Vibration resistance 150/50</p>	<p>VG342R-5DZ-10F-Q Valva SMC Japonia</p> <p>Pilot R (External Pilot) Voltage (24VDC) Lead Wire D (Din Connector) Surge Suppressor Z (Light & Surge Suppressor) Port Size 10 (1") Thread F (G) Passage External Pilot (N.O/N.C) Option Standard CE Marked Q (CE Marked) Weight - 1.100 Kg</p> 

Termen de livrare: 4 saptamani