

TECHNICAL DATA SHEET			
Name of Carpet	26 MM DUO GRASS		
Tufting Type		"5/16 inch" sand-rubber filled artificial turf	
Grass yarn	%100 PE Fibrilated, UV resistant		
Dtex/Denier	5.500 Dtex Light - 5.500 Dtex Dark		
Primary backing	100% Polypropylene UV-stablized, İşbir appr.160 gr/m2		
Coating	Carboxylated (SBR) Latex appr.900 gr/m2 with 5 mm perforation holes		
Pile height	55mm	±1mm	
Total thickness	57mm	±1mm	
Stitches per 10cm	14 Pcs	±%1	
Number of tufts/ m <sup>2</sup>	17 600	± %1	
Pile weight	400 g/ m <sup>2</sup>	± %3	
Backing weight	800 g/ m <sup>2</sup>	± %2	
Total weight	1.200 g/ m <sup>2</sup>	± %3	
Roll width	4.00m	±%1 (with or without Edging)	
Roll length	According to installation	According to installation Schedule	
Water permeability	60lt/min/ m <sup>2</sup>	60lt/min/ m <sup>2</sup>	
Color fastness		According to the highest standards, DIN 54004 (min 7) approve	
UV – stability	According to the highest standards 6000 hrs Weather –0-Mete Test, based on DIN 53387		
Infill Materials	None Fill System		
Warranty	AND THE PROPERTY OF THE PROPER	5 Years	













