

## FACO. Power Supply



### SPECIFICATIONS

DC Fixed outputs: + 5 V,  $\pm$  12 V, 1 A.  
 DC Variable outputs:  $\pm$  12 V, 0.5 A.  
 AC Outputs: 12 V or 24 V.  
 Outputs through 2 mm terminals, or connectors Sub-D of 25 pins (2 outputs).  
 Voltage LED indicators.  
 Robust construction.  
 Power: 110/220 VAC  
 Frequency: 50/60 Hz.

### DIMENSIONS AND WEIGHTS

Dimensions: 225 x 205 x 100 mm approx.  
 (8.85 x 8.07 x 3.93 inches approx.)  
 Weight: 2 kg approx.  
 (4.4 pounds approx.)

## EBC100. Base Unit, with built-in power supply



### SPECIFICATIONS

Hardware support and power supply.  
 Modules supporting unit.  
 DC Fixed outputs: + 5 V, + 12 V, -12 V.  
 DC Variable outputs:  $\pm$  12 V.  
 AC Outputs: 12 V or 24 V.  
 Outputs through either 2 mm contact terminals, or through 25 pins Sub-D connector.  
 Voltage LED indicators.  
 Robust construction.  
 Power: 110/220 VAC.  
 Frequency: 50/60 Hz.

### DIMENSIONS AND WEIGHTS

Dimensions: 410 x 298 x 107 mm approx.  
 (16.14 x 11.73 x 4.21 inches approx.)  
 Weight: 2 kg approx.  
 (4.4 pounds approx.)