



DE625N-E Cordless

BATTERY-POWERED SPREADER

- Certified Compliant to NFPA 1936, 2020 Edition
- Lightweight and powerful
- Easy to handle
- Brushless motor



The Spreader **Battery-Powered DE625N-E** is lightweight (21.5 kg), powerful (131 kN) and user friendly. **Protection rating - IP54.**

Thanks to the 625 mm spreading distance, it can face any task in the event of vehicle extrication.

Along with the Cutter, Ram, Combi-Tool and the Pedal Cutter, it completes the battery powered hydraulic Rescue Equipment. It works with DeWalt® FlexVolt™ 18V/54V or 20V/60V batteries, and delivers the same amount of force of a traditional Cutter.

Battery and charger not included

Max spreading distance	625 mm
Working pressure	70 MPa (700 bar)
Spreading force	174 kN (17.7 t)
HSF Highest spreading force*	60.6 kN (6.2 t)
LSF Lowest pulling force*	32.9 kN (3.4 t)
HPF Highest pulling force*	46 kN (4.7 t)
LPF Lowest pulling force*	26 kN (2.7 t)
Squeezing force	69 kN (7.0 t)
Motor	54V / 60V BRUSHLESS
Dimensions LxWxH (closed)**	787 x 282 x 244 mm
Dimensions LxWxH (open)**	701 x 625 x 244 mm
Weight**	21.5 kg
EN 13204 classification	AS 45/625-19

*NFPA 1936

**Dimensions and weight w/o battery