

## MEDICI MEDICAL SRL

Via Armellini, 13/B  
41013 Piumazzo di Castelfranco E. (MO) ITALY  
P.I./C.F.: 03423910367  
Tel.+39 059928707 – Fax.+39 0599530416  
E-mail: medici@new-med.it  
[www.medici-medical.com](http://www.medici-medical.com) - [www.vidix.it](http://www.vidix.it)



## DATA SHEET

PRODUCT:	<b>VIDIX® 4.0 STYLE</b> Videodermatoscope and high definition digital videocapillaroscope
BRAND:	<b>VIDIX®</b>
PRODUCER:	MEDICI MEDICAL SRL
Power supply:	Single phase
Voltage:	230 Vac, 50Hz
Max absorbed power:	300 W
Plugs available:	CH, UK, EU, US, SHUKO, IT
Cart dimensions:	170x80x70cm
Weight:	80kg
Class:	I
Year of start marketing:	2019
CERTIFICATIONS:	CE (in compliance with the essential requirements of the Directive MDD 93/42/CEE)
REGULATIONS:	CEI EN 60601-1 (1998) CEI EN 60601-1-2 (2007) CEI EN 60601-1-1 (2003) CEI UNI EN ISO 14971 CEI EN 62304 (2006) class A



## DIGITAL CAMERA

RESOLUTION:	5Mpx, with WIDE PIXEL TECHNOLOGY
SENSOR SIZE:	<b>2/3" SONY sensor</b> - the biggest and the best in the market
DIMENSIONS AND WEIGHT	21x17cm, <b>480g, carbon fibre shell, extremely light-weight and ergonomic</b>
MAGNIFICATIONS:	optical 7x-10x-20x-30x-50x-70x-100x (digital up to 400x)
TYPE OF ANALYSIS:	Immersion, polarized, close clinic, interdigital, macro at distance, trichoscopy
FOCUS:	Automatic in dermoscopic acquisition + Manual micro-focus
COMMANDS:	On board (buttons for acquisition and freeze, zoom in and zoom out, change setting, transition from dermatoscopic image acquisition to clinic, micro focus, increase or decrease of light intensity). Push-button panel with <b>LED and acoustic signal</b> .

**With just one hand it is possible to hold the camera and acquire images or zoom in and out**

ILLUMINATION:	Led
CABLE LENGHT:	3 m

ACCESSORIES INCLUDED:	No.1 IMMERSION EYEPIECE $\varnothing$ 3 cm No.1 POLARIZED EYEPIECE $\varnothing$ 2 cm No.1 INTERDIGITAL EYEPIECE No.1 ATTACHMENT SUPER MACRO for clinical macro images No.1 IMMERSION OIL 10ml BOTTLE
OPTIONAL ACCESSORIES:	No.1 FACE EYEPIECE $\varnothing$ 2 cm No.1 MICROEYEPIECE 150x No.1 INTRA ORAL ATTACHMENT <b>No.1 SPACER FOR CLOSE CLINICAL IMAGES</b>

All the eyepieces have a special magnetic ring for hooking automatically to the camera

**Possibility to use the same camera between 2 videodermatoscopes of the same brand**

**Ability to acquire with 1 single image a lesion up to 2,8 cm**

**Minimum camera zoom is 7x**

**Big LIVE mode of the camera, on the upper screen**

## SOFTWARE

---

NAME:	<b>DERMASCOPE</b>
VERSION:	Dermascope
FUNCTIONALITY:	Live camera view Image management (acquisition, saving, etc.) Patient management Follow-up for both clinical images and dermoscopic images Measurements and image analysis Real time comparison Pdf report
CONNECTIVITY:	Wi-Fi e-mail for images and reports Sharing databases, images and reports on the local network
OPERATIVITY:	Complete patient management with dedicated registry Dermoscopic, follow-up by comparison of historical images and live images Simplified mapping by dragging dermatoscopic images onto a clinical reference image or a shape Print reports in pdf and copy to external storage devices or direct CD-ROM burning Use of the function keys for quick and direct access to the main functions
	<b>Possibility to import database and images of our competitor</b>
OPTIONAL SW:	Dermoscopic and trichoscopic analysis through the DermaAnalisi module, DICOM module for managing images and reports in DICOM format
CERTIFICATIONS:	Software in compliance with the reference standard EN 62304

## HARDWARE

---

PC:	<b>MM DELL</b> – custom PC
MOTHER BOARD:	ASUS H270M-PLUS or superior
PROCESSOR:	CPU INTEL CORE i5-8600 at 3,1GHz or superior
RAM:	8G DDR3 2666MHz DDR4 or superior
HARD DISK:	1 HDD 1TB (data) + 1 SSD 256GB (operative system) <b>+ 1 HDD USB external 1TB for data backup</b>
BURNING:	DVD+-R/+RW
VIDEO CARD:	Videocard integrated in PC
POWER PACK:	ATX 650W
OPERATIVE SYSTEM:	Windows 10 Professional 64BIT
ROUTER:	TPLINK 300 MBIT or superior
PRINTER:	Wireless, color A4 format EPSON XP55 or superior
SCREEN:	Dual LCD LED 24" screen DELL
CART:	Ergonomic, equipped with locking system, easy to clean
TRANSFORMER:	TOR isolation transformer, in compliance with the reference standard EN61558-2-1 CEI 96-4

---

<b>WARRANTY</b>	<b>2 years - EXTENDIBLE</b>
-----------------	-----------------------------

---

## PACKING DETAILS

---

Wooden crate treated and marked in conformity with ISPM15 codes and regulation

Fully assembled: indicative dimension 190x90 h90cm - gross weight 130 kg

Partially assembled: indicative dimension 80x80 h120cm – gross weight 120 kg

