

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5.]

Numărul procedurii de achiziție _____ din _____
Obiectul achiziției: _____

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Tara de origine	Produsul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Lotul unic:						
Podium	Allustage	Germania	Allustage	Podium Extruded tube Ø 50 x 2 mm EN AW 6082 T6 Diagonals B: extruded tube Ø 18 x 2 mm EN AW 6082 T6 Ends C: aluminium cashing plate EN AC 42200 T6 UNI ENV 1999-1-1 (Eurocode 9)	Allu Stage A: extruded tube Ø 50 x 2 mm EN AW 6082 T6 Diagonals B: extruded tube Ø 18 x 2 mm EN AW 6082 T6 Ends C: aluminium cashing plate EN AC 42200 T6 UNI ENV 1999-1-1 (Eurocode 9)	
LED Screen	RO6 Outdoor	China	Lighting Group Co	LED DISPLAY 640 mm x 640 mm / cabinet - SMD2727 (WHITE) - 750 W/m ² - 250 W/m ² - Lux 16.7 mln. - 1920 Hz	LED DISPLAY 640 mm x 640 mm / cabinet brand:Lighting Tech Group Co., Ltd. SMD2727 (WHITE) Weight 12.5 kg IRIG1B 750 W/m ² 250 W/m ² Lux 16.7 mln.	

					Temperature -10000 1920 Hz IP65	
Echipament sunet	FBT Muse 210 LA	Italia	FBT	<p>Echipament sunet (echivalent FBT Muse 210 LA / FBT Mitus 218 SA) SUB: Subwoofer cu banda aerisita, cu sistem bass-reflex. Echipat cu doua difuzoare de frecventa joasa cu diametrul de 18" si bobina de 3.9". Frecventa de raspuns de la 30Hz la 100Hz.</p> <p>Amplificator clasa D cu putere de 2000W RMS TOP: Woofer: 2 X 10" bobina de 2.5" Driver 2 x 1" cu bobina de 1.7" Putere RMS: 900 W Raspuns frecventa: 55Hz-20000Hz SPL Maxim: 135 dB Dispersie driver: 90° x 10° Procesor de semnal digital</p>	<p>Echipament sunet FBT Muse 210 LA / FBT mitus 218 SA SUB: Subwoofer cu banda aerisita, cu sistem bass-reflex. Echipat cu doua difuzoare de frecventa joasa cu diametrul de 18" si bobina de 3.9". Frecventa de raspuns de la 30Hz la 100Hz.</p> <p>Amplificator clasa D cu putere de 2000W RMS TOP: Woofer: 2 X 10" bobina de 2.5" Driver 2 x 1" cu bobina de 1.7" Putere RMS: 900 W Raspuns frecventa: 55Hz-20000Hz SPL Maxim: 135 dB Dispersie driver: 90° x 10° Procesor de semnal digital</p>	
Echipament sunet	Markbass	Italia	Markbass	<p>Amplificator Bass (echivalent Markbass Little Mark III) Inputs: Unbalanced Jack and Balanced XLR Effects Send and Return EQ: 4-band EQ Variable Pre-shape Filter (VPP) with 380 Hz Center Frequency Vintage Loudspeaker Emulator (VLE) Frequency Range- 250Hz - 20 KHz Outputs: Balanced XLR Line Out, 1/4" Jack Tuner Out, Speakon Combi Speaker Out Output Power: 300W RMS @ 8Ohms, 500W RMS @ 4Ohms</p>	<p>Amplificator Bass Markbass Little Mark III Inputs: Unbalanced Jack and Balanced XLR Effects Send and Return EQ: 4-band EQ Variable Pre-shape Filter (VPP) with 380 Hz Center Frequency Vintage Loudspeaker Emulator (VLE) Frequency Range- 250Hz - 20 KHz Outputs: Balanced XLR Line Out, 1/4" Jack Tuner Out, Speakon Combi Speaker Out Output Power: 300W RMS @ 8Ohms, 500W RMS @ 4Ohms</p>	
Echipament sunet	Fender	SUA	Fender	<p>Amplificator Chitara (echivalent Fender Twin Amp) Features: Type Vintage Reissue Series Tube Amp Output 85 watts into 4 ohms Ohms 4 ohms Speakers 1-15" Custom</p>	<p>Amplificator Chitara Fender Twin Amp Features: Type Vintage Reissue Series Tube Amp Output 85 watts into 4 ohms Ohms 4 ohms Speakers 1-15" Custom Eminence@ 4 ohm Speaker</p>	

				<p>Eminence® 4 ohm Speaker with Ceramic Magnet, (Based on the Now Collectable JBL® D130F Speaker Used by Fender® in the '60s and '70s) Channels Dual Channel (Normal and Vibrato) Features Reverb Vibrato 2-Button Footswitch Tilt Back Legs Controls Normal Channel: Bright Switch, Volume, Treble, Middle, Bass Vibrato Channel: Bright Switch, Volume, Treble, Middle, Bass Reverb Vibrato: Speed, Intensity Covering Black Textured Vinyl with Silver Grille Cloth Weight 64 lbs. (34kg) Dimensions Height: 22" (55.9 cm) Width: 26.15" (66.4 cm) Depth: 10.5" (26.7 cm) Tube Complement 4 X 12AX7 2 X 12AT7 4 X 6L6 Solid State Rectifier Shipping Weight 70 lbs Cover Included Accessories 2-Button Footswitch for Reverb and Vibrato On/Off Footswitch Uses 2-Button Footswitch Acy</p>	<p>with Ceramic Magnet, (Based on the Now Collectable JBL® D130F Speaker Used by Fender® in the '60s and '70s) Channels Dual Channel (Normal and Vibrato) Features Reverb Vibrato 2-Button Footswitch Tilt Back Legs Controls Normal Channel: Bright Switch, Volume, Treble, Middle, Bass Vibrato Channel: Bright Switch, Volume, Treble, Middle, Bass Reverb Vibrato: Speed, Intensity Covering Black Textured Vinyl with Silver Grille Cloth Weight 64 lbs. (34kg) Dimensions Height: 22" (55.9 cm) Width: 26.15" (66.4 cm) Depth: 10.5" (26.7 cm) Tube Complement 4 X 12AX7 2 X 12AT7 4 X 6L6 Solid State Rectifier Shipping Weight 70 lbs Cover Included Accessories 2-Button Footswitch for Reverb and Vibrato On/Off Footswitch Uses 2-Button Footswitch Acy</p>
Echipament sunet (set)	Yamaha Drum Set	Indonesia /Germania	Yamaha Pearl Sennheiser	<p>Set de tobe (echivalent Drums Pearl's Masters Series) Set Microfoane (echivalent Sennheiser 904) Yamaha Studio Custom SET Set Microfoane (echivalent Shure SM 57)</p>	<p>Set de tobe Drums Pearl's Masters Series Set Microfoane Sennheiser 904 Yamaha Studio Custom SET Set Microfoane Shure SM 57</p>
Echipament sunet	Sennheiser	Romania	Sennheiser	<p>Wireless In Ear System (echivalent ew IEM G4 Twin) Consists of 2 x UHF bodypack receiver (EK IEM G4), 9.5" transmitter (SR IEM G4) and 2 x IE4 earphones Stereo / focus / mono modes 3.5 mm jack for earphones Adjustable limiter Adjustable 6.3mm headphone jack on the transmitter 1 x BNC antenna socket Inputs 2 x Jack / XLR female balanced combo</p>	<p>Wireless In Ear System Sennheiser ew IEM G4 Twin Consists of 2 x UHF bodypack receiver (EK IEM G4), 9.5" transmitter (SR IEM G4) and 2 x IE4 earphones Stereo / focus / mono modes 3.5 mm jack for earphones Adjustable limiter Adjustable 6.3mm headphone jack on the transmitter 1 x BNC antenna socket Inputs 2 x Jack / XLR female balanced combo</p>

Echipament sunet (set)	Allen&Heath SQ-5	Anglia	Allen&Heath	<p>Mixer sunet (echivalent SQ5)</p> <p>Mixer digital cu 48 canale Cu procesare FPGA de 96 KHz 17 faders / 6 layers 12x stereo mixes + LR3x stereo matrix 8x stereo FX engines + dedicated stereo returns DEEP procesarea permite integrarea plug-in-urilor direct în intrările mixerului și amestecarea canalelor Ecran tactil de 7 inch Slink port pentru audio / expansiune la distanță 64 port I / O pentru rețele audio 32 x 32 interfață audio USB Înregistrare directă SQ-Drive pe USB StageBox Ieșire AES</p> <p>Compatibil cu cardurile de rețea audio ME 1 și ME-500 și Dante sau Waves Monitorare (carcasa din Lemn) Microfoane radio Shure QLXD/ Beta 58/ SM 58, Shure SLXD, Sennheiser</p>	<p>Mixer sunet Allen & Heath SQ-5 Mixer digital cu 48 canale Cu procesare FPGA de 96 KHz 17 faders / 6 layers 12x stereo mixes + LR3x stereo matrix 8x stereo FX engines + dedicated stereo returns DEEP procesarea permite integrarea plug-in-urilor direct în intrările mixerului și amestecarea canalelor Ecran tactil de 7 inch Slink port pentru audio / expansiune la distanță 64 port I / O pentru rețele audio 32 x 32 interfață audio USB Înregistrare directă SQ-Drive pe USB StageBox Ieșire AES</p> <p>Compatibil cu cardurile de rețea audio ME 1 și ME-500 și Dante sau Waves Monitorare (carcasa din Lemn) Microfoane radio Shure QLXD/ Beta 58/ SM 58, Shure SLXD, Sennheiser</p>
Echipament sunet (set)	Digico SD 11	Anglia	Digico Grup	<p>Mixer sunet (echivalent Digico SD11)</p> <p>48 Input Channels with full processing 24 Aux/Sub-Group busses with full processing 8 x 8 Matrix with full processing Assignable channel layout User programmable macros Capable of redundantly mirroring with another SD11 console Snapshots for seamlessly changing many parameters at once Offline software iPad control Broadcast software option i software option</p>	<p>Mixer sunet Digico SD11</p> <p>48 Input Channels with full processing 24 Aux/Sub-Group busses with full processing 8 x 8 Matrix with full processing Assignable channel layout User programmable macros Capable of redundantly mirroring with another SD11 console Snapshots for seamlessly changing many parameters at once Offline software iPad control Broadcast software option i software option</p>

Lumini speciale	DTS Raptor	Italia	DTS lights	<p>12 x 100mm touch-sensitive, motorised faders 1 x 15" LCD high-resolution touchscreen 12 x 8-Segment LED bargraph meters 1 x 1/4" Headphone socket 1 x USB 2.0 slot 1 x PSU 1 x XLR3 1.2 – 12V Light connection 1 x Waves port (Optional) 16 x XLR Mic/Line Inputs 8 x XLR Line Outputs 1 x XLR AES/EBU Input (2 x channels) 1 x XLR AES/EBU Output (2 x channels) 2 x GPI 1/4" Jack 2 x GPO 1/4" Jack 1 x MIDI In/Thru/Out (5 pin DIN) 1 x Word Clock I/O BNC Rack is a 32 input, 8 output 32 Mic/Line Inputs at 48kHz or 28 Mic/Line inputs at 96kHz 8 Line Outputs 1 Output expansion card slot for adding 8 outputs MADI R45 Connectivity Optional Optics 7U Rack Mountable with supplied rackmount kit Gain Tracking™ Optional Redundant PSUs Can be used as a standalone rack</p>	<p>12 x 100mm touch-sensitive, motorised faders 1 x 15" LCD high-resolution touchscreen 12 x 8-Segment LED bargraph meters 1 x 1/4" Headphone socket 1 x USB 2.0 slot 1 x PSU 1 x XLR3 1.2 – 12V Light connection 1 x Waves port (Optional) 16 x XLR Mic/Line Inputs 8 x XLR Line Outputs 1 x XLR AES/EBU Input (2 x channels) 1 x XLR AES/EBU Output (2 x channels) 2 x GPI 1/4" Jack 2 x GPO 1/4" Jack 1 x MIDI In/Thru/Out (5 pin DIN) 1 x Word Clock I/O BNC Rack is a 32 input, 8 output 32 Mic/Line Inputs at 48kHz or 28 Mic/Line inputs at 96kHz 8 Line Outputs 1 Output expansion card slot for adding 8 outputs MADI R45 Connectivity Optional Optics 7U Rack Mountable with supplied rackmount kit Gain Tracking™ Optional Redundant PSUs Can be used as a standalone rack</p>
-----------------	------------	--------	------------	--	--

				<p>+/- 24 Moving head/ beam/ spot/ wash Chauvet 140 SR/ DTS Raptor/ Chauvet 375Z/ Showtec Q4</p> <p>Light output: 382.000 lux @ 5m Light source: Osaram Sirius hri 140w Zoom angle (degrees): beam – 3 to 11 degrees Spot – 7 to 21 Wash – 14 to 28 Colors 12+white Prism: 8-facet round, bidirectional rotation at variable speeds. Effects: pixel control, flower effect, virtual colour wheel, tungsten lamp effect, +/- 24 Par led Future light & Showtec 12x10w, 6 in 1 LWD (RGBWA+UV) 18x8w, RGBW</p>	<p>+/- 24 Moving head/ beam/ spot/ wash Chauvet 140 SR/ DTS Raptor/ Chauvet 375Z/ Showtec Q4</p> <p>Light output: 382.000 lux @ 5m Light source: Osaram Sirius hri 140w Zoom angle (degrees): beam – 3 to 11 degrees Spot – 7 to 21 Wash – 14 to 28 Colors 12+white Prism: 8-facet round, bidirectional rotation at variable speeds. Effects: pixel control, flower effect, virtual colour wheel, tungsten lamp effect, +/- 24 Par led Future light & Showtec 12x10w, 6 in 1 LWD (RGBWA+UV) 18x8w, RGBW</p>
Lumini speciale	Showtec Par LED 64	Germania	Showtec	<p>Par (e)chivalent LED Par 64 Short Q4-18) 18 x 8 W RGBW LED Par 40° fixed beam angle Double bracket for easy floor positioning DMX and manual control in Auto run and Sound-controlled mode RGBW colour mixing, dimmer and strobe function +/- 12 Futurelight par led 12x10 Slim Equipped with 12 high-power LEDs in the colors red, green, blue, amber, white and UV Flat housing form requires minimal space when rigging Extremely compact housing in a beautiful design Second mounting bracket for safe standing installation Locking possibility at the brackets with large metal butterfly screws Functions: static colors, RGBAW+UV color mixture, automatic color changes,</p>	<p>Par LED Showtec Par 64 Short Q4-18) 18 x 8 W RGBW LED Par 40° fixed beam angle Double bracket for easy floor positioning DMX and manual control in Auto run and Sound-controlled mode RGBW colour mixing, dimmer and strobe function +/- 12 Futurelight par led 12x10 Slim Equipped with 12 high-power LEDs in the colors red, green, blue, amber, white and UV Flat housing form requires minimal space when rigging Extremely compact housing in a beautiful design Second mounting bracket for safe standing installation Locking possibility at the brackets with large metal butterfly screws Functions: static colors, RGBAW+UV color mixture, automatic color changes,</p>

				<p>dimmer, strobe effect with adjustable speed, Master/Slave operation Addressing and setting via Control Board with four operating buttons and LED display Switch-mode power supply for operation between 100 and 240 volts P-Con terminals for power linking up to 8 units 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) Can be operated in 6; 10 CH mode The device is cooled by passive convection cooling Controlling by stand-alone; DMX; Sound to light via Microphone Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE Flicker-free Effect: Strobe effect; UV effect With a beam angle of 18°</p>	<p>dimmer, strobe effect with adjustable speed, Master/Slave operation Addressing and setting via Control Board with four operating buttons and LED display Switch-mode power supply for operation between 100 and 240 volts P-Con terminals for power linking up to 8 units 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) Can be operated in 6; 10 CH mode The device is cooled by passive convection cooling Controlling by stand-alone; DMX; Sound to light via Microphone Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE Flicker-free Effect: Strobe effect; UV effect With a beam angle of 18°</p>
Lumini speciale	Beam Chauvet q60	China	Chauvet	<p>Moving Head (tequivaleant Intimidator Beam Q60) DMX Channels: 12 or 16 DMX Connectors: 3-pin XLR Pan and Tilt: 540°/260° Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt Light Source: 1 LED (quad-color RGBW) 60 W, (4,5 A), 50,000 hours life expectancy Strobe Rate: 0 to 20 Hz Beam Angle: 3° Illuminance: 45,344 lux @ 2 m Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging) Color Temperature Range: 2000 to 8000 K</p>	<p>Moving Head Beam Q60 DMX Channels: 12 or 16 DMX Connectors: 3-pin XLR Pan and Tilt: 540°/260° Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt Light Source: 1 LED (quad-color RGBW) 60 W, (4,5 A), 50,000 hours life expectancy Strobe Rate: 0 to 20 Hz Beam Angle: 3° Illuminance: 45,344 lux @ 2 m Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging) Color Temperature Range: 2000 to 8000 K</p>

Mășină de fum	Antari Hz 400	Germania	Antari	Mășină de fum Hazer Lichid de fum Hazer Lucrările de montare, precum și operațiuni de instalare, ajustare și operare în timpul filmărilor. Materiale și elemente pasive/active necesare pentru interconectarea echipamentelor și punerea în funcțiune a acestora;	Mășină de fum Hazer Lichid de fum Hazer Lucrările de montare, precum și operațiuni de instalare, ajustare și operare în timpul filmărilor. Materiale și elemente pasive/active necesare pentru interconectarea echipamentelor și punerea în funcțiune a acestora;
Instalare, operare					
TOTAL					

Semnat: [Signature] Numele, Prenumele: Taiy Roda În calitate de: director
 Ofertantului: Taiy Stil SRL Adresa: L. Avram Ibră 39

