

LOTUL nr.7
SISTEM SONOR DE TRADUCERE SIMULTANĂ și TABLĂ INTERACTIVĂ

Simultaneous Wireless Interpretation System		
GENERIC SPECIFICATIONS		QUANTITY
Type:	infrared interpretation system	1
Number of listeners:	22	
Number of translator:	2	
IR Transmitter:	Frequency Range 2.0 - 6.0 Mhz; min. 6 channels with channel level indication; privacy protection system; compatibility with wired interpretation system; frequency stability - 10PPM; ALC automatic level control; Multiple audio input up to 12 channels simultaneously	
IR Receiver:	min. 22 IRR + 2x Spare IRR (infrared; Frequency range 2.0-6.0 MHz; Li-Ion battery with battery life up to 30 hours; LCD Panel with indication channel number, battery level, signal strength, volume and language name; up to 270° wide reception angle; Headphone detection function)	
IR Radiator:	min. 2x IR Radiators (Frequency range 2.0 - 6.0 MHz; IR output power for coverage min. 40m; Angle of half intensity min. ±20°; Compliant with IEC 60914 /IEC 61603; support system for eliminates disturbance from high frequency lighting systems; Standby/Working indication; Signal delay adjustment function; Synchronization ON/OFF with transmitter; Temperature control; support Multi-channels use for the same radiator)	
Interpreter Console:	min. 2x Interpreter Console + 1x Spare (Channel separation > 85 dB; Built-in speaker min. 2W; min. 2× Microphone/2× Record/2× Headphone interfaces; Frequency response 40Hz to 18kHz; LCD screen; min. 6 channel; Support direct interpretation and relay interpretation; Automatic channel interlocking; Support dual mic relay interpretation; Microphone selection function; min. 3x pre-select incoming channels; Personal volume adjustment and automatic feedback eliminator function; MUTE key to enable a brief muting of the microphone; Electret cardioid microphone with indicator ring	
Interpreter Headset:	min. 2x Headset + 1x Spare (Adjustable headband with closed ear cushions; Omni-directional dynamic microphone; Volume control on the cord; 3.5mm connector; 20-20kHz; min. 2m cord length)	
Stereo Headphone:	min. 22x Headphones with 3x Spare (Adjustable headband; 3.5mm connector; 20-20kHz)	
Hall sound system:	min. 10x Loudspeakers; 1x Mixer Amplifier; 2x Professional Microphone for speakers	
Accessories and Materials:	all necessary materials for the installation of the system must be included	
Installation:	all necessary work on the installation of the system must be included	
Warranty:	3 Years NBD support	

Interactive board		
GENERIC SPECIFICATIONS		QUANTITY
Type:	Interactive Board with Ultra Short Throw projector, Mobile Stand and sound system	1
Diagonal size/ Active Diagonal size:	min. 100" / 96"	
Technology:	IR Cell Optical LED	
Aspect Ratio:	16:9	
Surface coating:	Ceramic-Steel / Pre-painted Steel; Anti-scratch and Anti-reflection	
Ambient light reflection:	0	
Contact Points:	2/4/6/10 independent points; Finger / Marker Touch	
Multi-Touch:	Yes, 10-points	

Features:	Customizable toolbar; Drawing / writing tools with simultaneous writing and deleting; Recognition of gestures and handwriting; automatic detection markers and colors; Automatic calibration function; Writing surface with whiteboard marker; Easy cleaning; support up to 10 users which can write simultaneously with different colors; Integrated Internet browser; Integrated videoplayer; support and integration with MS Office formats; Built-in virtual keyboard	
Interfaces:	USB 2.0; WiFi	
Board Pens:	min. 4 colors	
Audio System:	built-in speakers with min. 20W RMS	
Stand:	Mobile (on a wheels) electrical height-adjustable (up to 50 cm) stand for interactive board and projector	
Ultra Short Throw projector		
Display System:	3 LCD	
Screen size support:	up to 110"	
Throw Distance:	0,4m - 0,6m	
Contrast ratio:	min. 3000:1	
Brightness:	min. 3300 lm	
Lamp Life:	up to 10k hours in ECO Mode	
Interfaces:	HDMI; RJ45; input RGB / Y PB PR; input/output VGA; USB Type-B and USB Type-A; S-Video; 2 Audio ports	
Warranty:	3 Years NBD On-site	