





Code	YGE12-235
Design Number	27352002E
Nominal Capacity (Ah)	235
Box Type / Number of Cells	C / 6
Box Material	PP
Voltage (V)	12
Electrolite Type	Gel
Weight (kg) (+ - %5)	78,4
Dimensions (mm) L / W / H (H1-H2)	518/274/213-236 [+5/-1mm]
Terminal Type	Round Type (DIN 72311-4) + M8 Optional
Float Voltage	13,6 - 13,8 VDC @25°C
Cycle Voltage	14,25 - 14,6 VDC @25°C
Recommended Charging Current Limit (Ah)	23,5
Discharge Cut-Off Voltage %100 Depth of Discharge D.O.D.	1,75 VDC @ (A) <=0,2 C
Capacity C20 (Ah)	235,0
Capacity C10 (Ah)	218,6
Capacity C5 (Ah)	200,3
Capacity C3 (Ah)	182,8
Self Discharge	Less than %2 per month @25°C
Storage Time	6 months @25°C. Charge Recommended Before Using
Cycle Life DOD %80	650
Cycle Life DOD %50	1200
Cycle Life DOD %20	3200





 Terminal Type A  
DIN 72311-4 Round Type

Layout (3)



 Terminal Type S  
(M-8 Optional)





**Yiğit Akü A.Ş.**

Organize Sanayi Bölgesi Oğuz Caddesi No: 2 Sincan / Ankara - TURKEY

Tel : +90 312 267 02 80 - Fax: +90 312 267 08 61 - 267 40 00

[endustriyel@yigitaku.com](mailto:endustriyel@yigitaku.com)

[www.yigitaku.com](http://www.yigitaku.com)