

Anexa nr.22
la Documentația standard nr. _____
din “ _____ ” _____ 20 _____

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5.]

Numărul procedurii de achiziție ocds-b3wdp1-MD-1751555023005 din 23/07/2025
Obiectul achiziției: <u>Achiziția Piese de schimb pentru tehnica de calcul</u>

Denumire a bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Lot 1. Placa de baza Intel (Socket 1200/1700)						
1.1	H510M-HDV/M.2 SE	China	Asrock	Chipset Intel H510 minimal, 2xDDR4- 3200. PCI-Ex.16x1, PCI-Ex1x1, 1xM.2 , VGA, DVI, HDMI - minimal	Asrock H510M-HDV/M.2 SE motherboard Chipset Intel H510, 2xDDR4- 3200. PCI-Ex.16x1, PCI-Ex1x1, 1xM.2 , VGA, DVI, HDMI	ISO, CE
1.2	H610M H V3	China	GIGABYTE	Chipset Intel H610 minimal, 2xDDR4-3200, 1xPCIe X16 4.0, 1xPCIe X1, 1xM.2, VGA, HDMI, DisplayPort - minimal	Gigabyte H610M H V3 DDR4 mATX Chipset Intel H610, 2xDDR4-3200, 1xPCIe X16 4.0, 1xPCIe X1, 1xM.2, VGA, HDMI, DisplayPort	ISO, CE
1.3	B760M E	China	GIGABYTE	Chipset Intel B760 minimal, 2xDDR5- 6400, 1xPCIe X16 4.0, 1xPCIe X1, 1xM.2, VGA, HDMI, DisplayPort - minimal	GIGABYTE B760M E Chipset Intel B760, 2xDDR5-6400, 1xPCIe X16 4.0, 1xPCIe X1, 1xM.2, VGA, HDMI, DisplayPort	ISO, CE
Lotul 2 Placa de baza AMD (Socket AM4/AM5)						
2.1	B450M Pro4 R2.0	China	Asrock	Chipset AMD B450 minimal, 2xDDR4- 3200, PCI-Ex.16x1, PCI-Ex1x1, 1xM.2 , VGA, DVI, HDMI - minimal	Asrock B450M Pro4 R2.0 Chipset AMD B450, 2xDDR4-3200, PCI-Ex.16x1, PCI-Ex1x1, 1xM.2 , VGA, DVI, HDMI	ISO, CE
2.2	B650MT	China	Biostar	Chipset AMD B650 minimal, 2xDDR5- 6400, 1 x PCIe 4.0 x16, PCI-Ex1x1, 1xM.2, DP, HDMI - minimal	Biostar B650MT Chipset AMD B650 minimal, 2xDDR5-6400, 1 x PCIe 4.0 x16, PCI-Ex1x1,	

					1xM.2, DP, HDMI - minimal	
Lotul 6 Memorii Statii de lucru						
6.1	GR3200D464 L22S/8G	PL	Goodram	RAM 8 DDR4 3200 MHZ, PC25600, CL16, 1.35V	Goodram GR3200D464L22S/8G memory module 8 GB 1 x 8 GB DDR4 3200 MHz	ISO, CE
6.2	Kit of 2*8GB	China	Kingston	RAM 16GB (Kit of 2*8GB) DDR4-3600 MHZ, PC28800, CL16, 1.35V	16GB (Kit of 2*8GB) DDR4-3600 Kingston FURY Beast DDR4, PC28800, CL17, 1.35V, Auto-overclocking, Asymmetric BLACK low-profile heat spreader, Intel XM	ISO, CE
6.3	Kit of 2*8GB	China	Kingston	RAM 32GB (Kit of 2*16GB) DDR5-5600 MHZ, PC48800, CL36, 1.25V	32GB (Kit of 2*16GB) DDR5-5600 Kingston FURY Beast DDR5 RGB, PC44800, CL40, 1.25V, Auto-overclocking, Asymmetric BLACK low-profile heat spreader, Int	ISO, CE
Lotul 8 Discuri Statii de lucru						
8.1	ST1000DM014	China	Seagate	500Gb, SATA 6 GB/s, 7200rpm	Seagate Barracuda ST1000DM014 internal hard drive 3.5" 1 TB Serial ATA III	ISO, CE
8.2	ST8000VX010	China	Seagate	8.00Tb, SATA 6GB/s, 256MB, 7200rpm, Surveillance, Preconizat p-u sisteme de supraveghere video 24/7	Seagate SkyHawk internal hard drive 8 TB 256 MB 3.5" Serial ATA III (ST8000VX010)	ISO, CE
8.3	ST1000LM049	China	Seagate	2.5" 500Gb, SATA 6 GB/s, 7200rpm, 7 mm	Seagate BarraCuda internal hard drive 1 TB 7200 RPM 128 MB 2.5" Serial ATA III (ST1000LM049)	ISO, CE
8.4	KC600	China	Kingston	2.5" SATA 6 Gbit/s, SSD 240GB – minimal, R/W 500 / 500MB/s, 80/80K IOPS – minimal	2.5" SATA SSD 256GB Kingston KC600 [R/W:550/500MB/s, 90K/80K IOPS, SM2259, 3D NAND TLC]	ISO, CE
8.5	970 EVO plus	China	970 EVO plus	PCIe 3.0 x4, R/W:3500/2300MB/s, min 300K/200K IOPS, TLC	SSD SAMSUNG, Gen3 x 4, 970 EVO plus, 250 GB, M.2, PCIe Gen3.0 x4, V-Nand 3bit MLC, R/W: 3500/2300 MB/s, „MZ-V7S250BW”	ISO, CE
8.6	SNV3S	China	Kingston	PCIe 3.0 x4, R/W:3400/2300MB/s, min 450K/370K IOPS, TLC	SSD KINGSTON, NV3, 500GB NVMe „SNV3S/500G”	ISO, CE
Lotul 9 Placi Video						
9.1	PULSE AMD Radeon RX 6400	China	SAPPHIRE	Placă video 4GB GDDR5, 128bit, DVI-D, HDMI, răcire activă, low profile, Fiecare cartela va include cate un cablu HDMI male - HDMI male de 3m.	SAPPHIRE „PULSE AMD Radeon RX 6400”, 4 GB GDDR6 64 biti, PCI Express 4.0 x 4, HDMI DisplayPort, sistem racire aer, „11315-01-20G” + Cable HDMI M to HDMI M 3m	ISO, CE
9.2	GeForce RTX 3060 OC 8G	China	Gigabyte	Placă video 8GB GDDR6, 128bit, DVI-D, DisplayPort, HDMI, Min: 2400 Cuda Cores Fiecare cartela va include cate un cablu HDMI male - HDMI male de 3m	Gigabyte GAMING GeForce RTX 3060 OC 8G (rev. 2.0) NVIDIA 8 GB GDDR6 + Cable HDMI M to HDMI M 3m	ISO, CE

9.3	GeForce RTX 3060 12 GB	China	Gigabyte	Placă video 12GB GDDR6, 192bit, 1 x PCIe 4.0 x16, DP, HDMI - minimal, Frecventa memorie 15000 MHz, Min: 3500 Cuda Cores Fiecare cartela va include cate un cablu DP male - DP male de 3m	Gigabyte RTX 3060 Windforce OC 12G NVIDIA GeForce RTX 3060 12 GB GDDR6 + Cable HDMI M to HDMI M 3m	ISO, CE
Lotul 10 Discuri Flash						
10.1	AUV150	China	ADATA	16Gb USB 2.0, R/W: 80/25 Mb/s - minimal	USB 3.2 ADATA 32 GB, cu capac, carcasa plastic, negru, „AUV150-32G-RBK”	ISO, CE
10.2	AUV150	China	ADATA	32Gb USB 3.0, R/W: 90/40 Mb/s - minimal	USB 3.2 ADATA 32 GB, cu capac, carcasa plastic, negru, „AUV150-32G-RBK”	ISO, CE
10.3	MUF-64BE4/APC	China	Samsung	64Gb USB 3.0, R/W: 200/120 Mb/s - minimal	USB Samsung MEMORY DRIVE FLASH USB3.1 64GB/BAR PLUS MUF-64BE4/APC SAMSUNG, „MUF-64BE4/APC	ISO, CE
10.4	MUF-128BE4/APC	China	Samsung	128Gb USB 3.0, R/W: 200/120 Mb/s - minimal	USB flash drive Samsung MUF-128BE4/APC - MUF-128BE4/APC	ISO, CE
10.5	MUF-256BE4/APC	China	Samsung	256Gb USB 3.0, R/W: 200/120 Mb/s - minimal	MEMORIE USB Samsung 256 GB BAR Plus „MUF-256BE4/APC”	ISO, CE
Lotul 11 Monitoare						
11.1	LS24D600E AUXEN	China	Samsung	Monitor 24” WQHD 2560x1440, Rata de maximă de reîmprospătare: 100 Hz (minim), Luminozitate (tipica): 350 cd/m ² , VGA + DVI + HDMI - minimal, Speakers	Monitor IPS LED Samsung 24" LS24D600EAUXEN, QHD (2560 x 1440), HDMI, DisplayPort, Pivot, 100 Hz, 5 ms	ISO, CE
11.2	LS27D600U AUXEN	China	Samsung	Monitor 27” WQHD 2560x1440, Rata de maximă de reîmprospătare: 100 Hz (minim), Luminozitate (tipica): 350 cd/m ² , HDMI+DP - minimal, Speakers	Monitor IPS LED Samsung 27" LS27D600UAUXEN, QHD (2560 x 1440), HDMI, DisplayPort, Pivot, 100 Hz, 5 ms	ISO, CE
Lotul 15 Tastatura si mouse						
15.1	TKR101	China	Esperanza	Tastatura cu fir, format classic, Eng,Ro,Ru, Color: Black, Keycaps: Round Edge ,Character: Laser Engraving , Adjustable Keyboard Legs: Yes, Minimal Cable Length: 150 cm, Hardware Connectivity: USB	Keyboard Esperanza Titanium TKR101 - Russian Layout / Office keyboard standard, 107 buttons,, Eng,Ro,Ru, Color: Black, Keycaps: Round Edge ,Character: Laser Engraving , Adjustable Keyboard Legs: Yes, Minimal Cable Length: 150 cm, Hardware Connectivity: USB	ISO, CE
15.2	B100	China	Logitech	Mouse optic cu fir, USB , 3 butoane , Lungimea Firului minimum 1.8M, culoare neagră, mod rezoluție de urmărire -1000 dpi, poziționarea-ambidextrous	Logitech Corded Optical Mouse B100, 1000 DPI, Black3 butoane , Lungimea Firului minimum 1.8M, culoare	ISO, CE

					neagră, mod rezoluție de urmărire -1000 dpi, poziționarea-ambidextrous	
Lotul 18 Casca audio						
18.1	EncorePro HW510	China	Poly	<i>Plantronics EncorePro HW510, Mono, 89433-02 (Mono)</i>	Headset Poly EncorePro HW510, noise-canceling microphone,	ISO, CE
18.2	DA85	China	Poly	<i>Plantronics 201852-01 DA80 USB Audio Processor</i>	Poly DA85 USB Audio Processor	ISO, CE

(Semnat electronic) _____ Numele, Prenumele: Constantin Alexandru în calitate de: director

Ofertantul: Triomac SRL Adresa: Orhei, str Stefan cel Mare 3, of 16