## HIGH VACUUM, HIGH FLOW HOSPITAL SUCTION ASPIRATORS





## and HOSPI PLUS

Designed for professional aspiration of bodily fluids, tissues or bones of patients during or after surgery.

Oiless and maintenance free piston type pumps provide high performances. Excellent suction capacities and max vacuum built up within a few seconds. Available with vacuum gauge and autoclavable jars made of Makrolon<sup>®</sup> with 200 ml (2 l jar) or 500 ml (4 or 5 l jars) graduation optional 2-3 litres Flovac jars with disposable liners, not compatible with safety trap bottle. Wide range of versions with different features

- 60 l/m (Clinic Plus) or 90 l/m (Hospi Plus) flow rate; - 2, 4 or 5 l jars; Membrane keyboard for 28119-20, 28160, 28162, 28195



Clinic Plus Basic and Hospi Plus Basic without

121 Rir Saf An Au Co

Air

Foo

Cha

Power Cord with Schuko plug

Multilingual manual: GB, FR, IT, ES , DE, GR, PL, RO

Clinic Plus Full and Hospi Plus Full with foot

switch and electronic flow direction regulator foot switch and electronic flow direction regulator TECHNICAL SPECIFICATIONS

10			
	CLINIC PLUS	HOSPI PLUS	MAIN APPLICATIO
Operating voltage:		) Hz ———————————————————————————————————	EMERGENCY DEPT
Maximum suction:	- 0.90 bar (675 mmHg)		GENERAL SURGER
Operating cycle:	continuous	continuous	GYNAECOLOGY
Flow:	60 l/min	90 l/min	NEUROSURGERY
Power:	230 VA	385 VA	OBSTETRICS
Noise level:	51.7 dBA	46.4 dBA	OPERATING THEAT
Norms:	EN 60601-1-1, EN 60601-1-	2 —	DENTAL PRACTICE
	93/42 FEC		Dennierinaerie



4 antistatic castors with brake

- MPR system for versatility;

- footswitch and flow direction diverter. High standards of safety in overflow protection system Double security valve integrated in the jar and hydrophobic filter (all models), safety trap bottle (only MPR models). MPR (Multi Purpose Rail) models

2 or 3 | Flovac

This system enhances the versatility for easy and quick exchange of different accessories, with no need for tools. Equipped with five connections for rings of various diameters to fit jars of different sizes and types (2l, 3l, 5l), cannula holders and safety trap bottle.



		230 V	110 V	CLINIC and HOSPI PLUS	Jars	switch	direction diverter*		
n foot		28194	28118	CLINIC Basic	2x2	-	-		
egulator			28195	-	CLINIC Full	2x2	yes	yes	
AIN APPLICATIONS			28196		CLINIC Basic	2x4	-	-	
EMERC	SENCY I	DEPT.	28198	28119**	CLINIC Full	2x4	yes	yes	
GENERAL SURGERY			28159	-	CLINIC Basic MPR	2x5	-	-	
GYNAECOLOGY			28160		CLINIC Full MPR	2x5	yes	yes	
			28200	-	HOSPI Basic	2x2	-	-	
NEUROSURGERY			28203		HOSPI Full	2x2	yes	yes	
OBSTETRICS			28201	-	HOSPI Basic	2x4	-	-	
PERATING THEATRE					HOSPI Full	2x4	yes	yes	
DENTAL PRACTICE			28161	-	HOSPI Basic MPR	2x5 l	-	-	
			28162	-	HOSPI Full MPR	2x5	yes	yes	
*Allows to direct suctioned liquids to any of the 2 jars **with 2x5 l jars									
US Code				ACCESSORIES FOR CLINIC/HOSPI PLUS MPR					
full	basic	Hospi full	28150	<b>28150</b> Safety trap bottle 220 ml with tube - spare					
MPR	MPR	MPR	28151	Multipurpose stainless steel rail - optional					
2	2	2	28154	Ring for 2 l autoclavable jar - optional					
2	2	2	28155						
2	1	2	28156	56 Ring for 2 or 3   Flovac jar - optional					
1	2	2		MEMBRANE KEYBOARD - spare					
1	2	2	28170	Mem. Keyboard for 28198					

28171 Mem. Keyboard for 28119-20, 28160, 28162, 28195 28172 Mem. Keyboard for 28203, 28204 JAR HOLDERS - spare

28108 Jar holder 2 l\* for 28194-5, 28118, 28200, 28203 28109 Ring adapter for 28108 \*Needs 28109

STANDARD ACCESSORIES CLINIC PLUS and HOSPI PLUS										
	Clinic,	Clinic,	Clinic	Clinic	Hospi	Hospi				
	Hospi	Hospi	basic	full	basic	full				
	basic	full	MPR	MPR	MPR	MPR				
1°C autoclavable jar with overflow valve system (2, 4 or 5 l)	2	2	2	2	2	2				
ngs to accommodate 5 l jars	-	-	2	2	2	2				
ifety Trap Bottle (220 ml)	-	-	1	2	1	2	12			
ntibacterial & Hydrophobic Filter (single-patient)	1	1	1	1	2	2				
utoclavable silicone tubes Ø 8x14 mm length 150 cm	1	1	1	1	2	2				
onical Connector Ø 10-11-12mm	1	1	1	1	2	2				
r suction inlet	1	1	1	1	2	2				
ootswitch with intermittent or continuous operation	-	1	-	1	-	1	1			
hange-Over System from jar to jar by soft-touch keys	-	1	-	1	-	1				