

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție ocds-b3wdp1-MD-1679412085754 din 06/04/2023
Obiectul achiziției: Echipament audio

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
<b>Bunuri/servicii</b>						
Lotul 2						
Combo de chitară electrică	<b>VT40X</b>		<b>Vox</b>	<b>Combo for Electric Guitar</b> Power: 40 W @ 5 Ohm Equipped with: 1x 10" Speaker Valvetronix tube preamp 11 Amp models (20 when using Tone Room - editor/librarian software): Deluxe CL, Tweed 4x10, Vox AC30, Boutique OD, VOX AC30TB, Brit 800, Brit OR MKII, Double Rec, Boutique CL. Effects: Pedal 1-type: 4 (Comp, Chorus, Overdrive, Distortion) Pedal 2-type: 4 (Flanger, Phaser, Tremolo, Delay) Reverb type: 4 (Room, Spring, Hall, Plate) Memory slots: 33 (60 when using Tone Room - editor/librarian software) User programs: 8 (2 banks x 4 channels) 6.3 mm Jack input, AUX in Headphone connector Foot pedal connector Mini USB port (type B) Including power adapter	<b>Combo for Electric Guitar Vox VT40X</b> Power: 40 W @ 5 Ohm Equipped with: 1x 10" Speaker Valvetronix tube preamp 11 Amp models (20 when using Tone Room - editor/librarian software): Deluxe CL, Tweed 4x10, Vox AC30, Boutique OD, VOX AC30TB, Brit 800, Brit OR MKII, Double Rec, Boutique CL. Effects: Pedal 1-type: 4 (Comp, Chorus, Overdrive, Distortion) Pedal 2-type: 4 (Flanger, Phaser, Tremolo, Delay) Reverb type: 4 (Room, Spring, Hall, Plate) Memory slots: 33 (60 when using Tone Room - editor/librarian software) User programs: 8 (2 banks x 4 channels) 6.3 mm Jack input, AUX in Headphone connector Foot pedal connector Mini USB port (type B) Including power adapter	

				Warranty hardware 2 years	Warranty hardware 2 years
<b>Lotul 3</b>					
Combo de chitară electrică	<b>LT25</b>		<b>Rumble</b>	<b>Bass Combo</b> Power: 25 Watt 1x 8" Loudspeaker 15 Amplifier models 20 Effects, 50 Factory and 30 user presets Gain, Bass, Mid, Treble, Master controls Preset Select, Back, Save Button, Menu Button, Tap Tempo/Tuner Button USB Output for recording and firmware updates Stereo aux Headphone output Foot-switch connection Warranty hardware 2 years	<b>Bass Combo Amp Fender Rumble LT25</b> Power: 25 Watt 1x 8" Loudspeaker 15 Amplifier models 20 Effects, 50 Factory and 30 user presets Gain, Bass, Mid, Treble, Master controls Preset Select, Back, Save Button, Menu Button, Tap Tempo/Tuner Button USB Output for recording and firmware updates Stereo aux Headphone output Foot-switch connection Warranty hardware 2 years
<b>Lotul 4</b>					
Combo de chitară electrică	<b>HB-40MFX</b>		<b>Electric Guitar Modelling</b>	<b>Electric Guitar Modelling Combo 40 W</b> Speaker configuration: 1x 10" 5 Amp voicings, incl. Clean, Crunch, Lead, OD1 and OD2 4 Fully programmable presets Multi-FX DSP with 5 individual digital effects: Reverb, Delay, Chorus, Tremolo and Phaser, each with adjustable parameters Controls for gain, volume, treble, mid, bass and FX as well as a master volume Mini-jack connection for aux line and headphones Bluetooth audio receiver for playing backing tracks from an external source Digital guitar tuner with LED display Output for external speaker 240 V 50/60 HZ switching power supply 12 mm wooden cabinet Warranty hardware 2 years	<b>Electric Guitar Modelling Combo 40 W HB-40MFX</b> Speaker configuration: 1x 10" 5 Amp voicings, incl. Clean, Crunch, Lead, OD1 and OD2 4 Fully programmable presets Multi-FX DSP with 5 individual digital effects: Reverb, Delay, Chorus, Tremolo and Phaser, each with adjustable parameters Controls for gain, volume, treble, mid, bass and FX as well as a master volume Mini-jack connection for aux line and headphones Bluetooth audio receiver for playing backing tracks from an external source Digital guitar tuner with LED display Output for external speaker 240 V 50/60 HZ switching power supply 12 mm wooden cabinet Warranty hardware 2 years
<b>Lotul 5</b>					
Microfon set pentru tobe	<b>PGA Drumkit 7</b>		<b>Shure</b>	<b>Drum microphone set</b> PG Alta Series 1x PGA52 bass drum microphone 3x PGA56 snare / tom microphones 1x PGA57 snare microphone 2x PGA81 overhead microphones 3x Tom mounts 7x 4.6 m XLR cables Case	<b>Drum microphone set Shure PGA Drumkit 7</b> PG Alta Series 1x PGA52 bass drum microphone 3x PGA56 snare / tom microphones 1x PGA57 snare microphone 2x PGA81 overhead microphones 3x Tom mounts 7x 4.6 m XLR cables Case

				Warranty hardware 2 years	Warranty hardware 2 years
<b>Lotul 6</b>					
Microfon dinamic	EV ND76		Electro-Voice	<b>Dynamic large diaphragm vocals microphone</b> (Equivalent EV ND76) Polar pattern: Cardioid Frequency range: 70 - 17,000 Hz Max. SPL: 140 dB 2.4 mV / Pascal Impedance: 350 Ohm Black zinc diecast housing ABS polycarbonate Incl. microphone holder and bag Warranty hardware 2 years	<b>Dynamic large diaphragm vocals microphone</b> EV ND76 Polar pattern: Cardioid Frequency range: 70 - 17,000 Hz Max. SPL: 140 dB 2.4 mV / Pascal Impedance: 350 Ohm Black zinc diecast housing ABS polycarbonate Incl. microphone holder and bag Warranty hardware 2 years
<b>Lotul 7</b>					
Microfon vocal	EV RE520		Electro-Voice	<b>Vocal Microphone</b> (Equivalent EV RE520) Working principle: Condensor Directional characteristic: Supercardioid Frequency range: 40 - 20,000 Hz Max. Sound pressure level: 150 dB Output impedance: 200 ohms Sensitivity: 5.6 mV / Pa (-45 dBV / Pa) @ 1 kHz Requires +48 V phantom power Includes bag Warranty hardware 2 years	<b>Vocal Microphone</b> EV RE520 Working principle: Condensor Directional characteristic: Supercardioid Frequency range: 40 - 20,000 Hz Max. Sound pressure level: 150 dB Output impedance: 200 ohms Sensitivity: 5.6 mV / Pa (-45 dBV / Pa) @ 1 kHz Requires +48 V phantom power Includes bag Warranty hardware 2 years
<b>Lotul 9</b>					
Microfon vocal	Beta87A		Shure	<b>Condenser vocal microphone</b> (Equivalent Beta87A) -Supercardioid polar pattern -Linear transmission range for precise, detailed and true to original song and speech. -Extremely precise supercardioid characteristic over the entire frequency range for the greatest possible feedback resistance with maximum amplification. -Built-in, three-layer wind protection minimizes pop and breathing noises. -Operation with phantom power -Frequency range: 50 Hz - 20 kHz -Output impedance: 100 ohms -Idle sensitivity: -54 dBV / Pa (2 mV) -Maximum sound pressure level: 140.5 dB SPL -Inherent self-noise (equivalent sound pressure): 23.5 dB (A) -Includes microphone clip and storage bag Warranty hardware 2 years	<b>Condenser vocal microphone</b> Beta87A -Supercardioid polar pattern -Linear transmission range for precise, detailed and true to original song and speech. -Extremely precise supercardioid characteristic over the entire frequency range for the greatest possible feedback resistance with maximum amplification. -Built-in, three-layer wind protection minimizes pop and breathing noises. -Operation with phantom power -Frequency range: 50 Hz - 20 kHz -Output impedance: 100 ohms -Idle sensitivity: -54 dBV / Pa (2 mV) -Maximum sound pressure level: 140.5 dB SPL -Inherent self-noise (equivalent sound pressure): 23.5 dB (A) -Includes microphone clip and storage bag Warranty hardware 2 years

<b>Lotul 10</b>					
Cablu Multicore	<b>M-Studio</b>		<b>Cables the sssnake</b>	<b>Studio Multicore Cables</b> 4x Female XLR in the stagebox 4x Balanced 6.3 mm female jack (socket) in stagebox 4x Male XLR on fanout cable 4x Balanced 6.3 mm male jack (plug) in the fanout cable Length: 10	<b>Studio Multicore Cables the sssnake M-Studio</b> 4x Female XLR in the stagebox 4x Balanced 6.3 mm female jack (socket) in stagebox 4x Male XLR on fanout cable 4x Balanced 6.3 mm male jack (plug) in the fanout cable Length: 10
<b>Lotul 11</b>					
Cablu pentru instrument muzical	TMI 9 PP Vintage		<b>Cables the sssnake</b>	Double sided 6.3mm mono jack Metal connectors Textile coated Colour: Black Length: min 9 m	Cable For Guitar / Bass the sssnake TMI 9 PP Vintage Black Double sided 6.3mm mono jack Metal connectors Textile coated Colour: Black Length: min 9 m
<b>Lotul 12</b>					
Saundcard USB	Volt 476 OptiPlex 3000 SFF	China	Universal Audio Dell	<b>4-Channel audio Interface</b> (Equivalent Universal Audio Volt 476) 24 bit / 192 kHz 2 microphone preamps +48 V phantom power Switchable air function 2 Mic/Instrument/Line inputs: XLR/6.3 mm jack combo balanced 2 Line inputs: 6.3 mm jack 4 Line outputs: 6.3 mm jack balanced Stereo headphone output: 6.3 mm jack MIDI input and output USB-C connection <i>Incl. USB cable (type C to A)</i> <i>Include brand computer, Small Form Factor</i> Minimum requirements: Operating System: Windows 11 Pro 64-bit English; Processor: 6C/12T, up to 4.6 GHz Cache: 18MB, equivalent i5-12500; Memory: 16 GB DDR4; Hard Drive: SSD 512 GB for System; Graphics Card: Integrated Graphics; Network interface: Integrated 10/100/1000 Gigabit Ethernet LAN, Bluetooth; External I/O Ports: Front: 2 USB2.0 port, 1 USB3.2, 1 USB3.2 Type-C® port, 1 audio jack; Rear: 3+1 USB3.2 ports, 2 USB2.0 ports, 2 DisplayPort1.4 ports, 1 line-out/in audio port, 3 SATA3.0 slots for 3.5/2.5-inch HDD, and optical drive, 1 PCIe x16 slot, 1 PCIe x4 slot; Keyboard: USB Wireless Mouse and Keyboard (Eng/Ru);	<b>4-Channel audio Interface</b> Universal Audio Volt 476 24 bit / 192 kHz 2 microphone preamps +48 V phantom power Switchable air function 2 Mic/Instrument/Line inputs: XLR/6.3 mm jack combo balanced 2 Line inputs: 6.3 mm jack 4 Line outputs: 6.3 mm jack balanced Stereo headphone output: 6.3 mm jack MIDI input and output USB-C connection <i>Incl. USB cable (type C to A)</i> <i>Include brand computer, Small Form Factor</i> Dell OptiPlex 3000 SFF, 180 W internal power supply unit (PSU), 85% Efficient, 80 Plus Bronze, Trusted Platform Module (Discrete TPM Enabled), EPEAT 2018 Registered (Silver), ENERGY STAR Qualified, 12th Generation Intel Core i5-12500 (6 Cores/18MB/12T/3.0GHz to 4.6GHz/65W), Intel Integrated Graphics, 16GB (1x16GB) DDR4 non ECC memory, M.2 2230 512GB PCIe NVMe Class 35 Solid State Drive, No Optical Drive, No Additional Add In Cards, No Media Card Reader, No Wireless LAN Card (no WiFi enablement), No PCIe add-in card, No

				Optical drive, SD card slot; Warranty: 2 years.	Additional Video Ports, Dell Multi-Device Wireless Keyboard and Mouse - KM7120W - Russian (QWERTY), PORTS: Front: 2 x USB 2.0 ports, 2 x USB 3.2 Gen 1 ports, Universal audio jack, Rear: 2 x USB 3.2 Gen 1 ports, 2 x USB 2.0 ports with Smart Power On, 1 x RJ45 Ethernet port, 1 x DisplayPort 1.4 port, 1 x HDMI 1.4b port, 1 x Kensington security-cable slot, DIMENSIONS: Height: 290.00mm, Width: 92.60mm, Depth: 292.80mm, Weight (minimum): 3.71kg, Weight(maximum): 5.03kg, MEMORY OPTIONS: 2 x DDR4 Slots, Maximum memory: 64 GB, SLOTS: Half-height Gen 4 PCIe x 16 slot, Half-height Gen 3 PCIe x1 slot, M.2 2230 slot for WiFi and Bluetooth card, M.2 2230/2280 slot for SSD, 2 x SATA 3.0 slots for 3.5/2.5-inch HDD, and slim optical drive, Windows 11 Pro, English, Hungarian, Slovenian, Romanian, Russian, 3y ProSupport and Next Business Day Onsite Service	
<b>Lotul 13</b>						
Microfon	SM 7 B		Shure	<p><b>Microphone</b> (Equivalent SM7B)</p> <ul style="list-style-type: none"> <li>- Dynamic Speaker and Recording Microphone</li> <li>- Polar pattern: Cardioid</li> <li>- Frequency range: 50 – 20,000 Hz</li> <li>- Sensitivity -59.0 dB (1.12 mV)</li> <li>- Bass roll-off switch</li> <li>- Mid-boost switch</li> <li>- Impedance: 150 ohms</li> <li>- Shielding against electromagnetic interference</li> <li>- Swivel mount</li> <li>- XLR connector</li> <li>- Includes switch cover plate and windscreen</li> </ul> <p><b>Microphone Arm</b> ( Equivalent Gator Frameworks Deluxe)</p> <ul style="list-style-type: none"> <li>- Table microphone arm with cable guide</li> <li>- Cables up to 8mm in diameter can be attached to the underside of the arms with a clip system</li> <li>- Aluminium construction</li> <li>- Locking centre joint</li> <li>- 3/8» Rhreaded connection with 5/8» adapter</li> </ul>	<p>Shure SM 7 B</p> <p>Dynamic Speaker and Recording Microphone</p> <p>Polar pattern: Cardioid</p> <p>Frequency range: 50 - 20,000 Hz</p> <p>Sensitivity -59.0 dB (1.12 mV)</p> <p>Bass roll-off switch</p> <p>Mid-boost switch</p> <p>Impedance: 150 ohms</p> <p>Shielding against electromagnetic interference</p> <p>Swivel mount</p> <p>XLR connector</p> <p>Dimensions: 190 x 64 x 96 mm</p> <p>Weight: 766 g</p> <p>Includes switch cover plate and windscreen</p> <p>Suitable foam windscreen: Art.263050</p> <p>Suitable replacement pop-up windscreen: Art.157230</p> <p>Roadworx Microphone Arm</p>	

				<ul style="list-style-type: none"> <li>- Table clamp up to 56 mm or table feed-through up to 45 mm (20 mm hole)</li> <li>- Length upper arm: 43 cm</li> <li>- Length lower arm: 43 cm</li> <li>- Colour: Black</li> <li>- <b>Microphone Cable</b> Length: 3 m (equivalent Mogami xlr cable)</li> </ul>	<p>Table microphone arm with cable guide Cables up to 8 mm in diameter can be attached to the underside of the arms with a clip system Aluminium construction Locking centre joint 3/8" Rhreaded connection with 5/8" adapter Table clamp up to 56 mm or table feed-through up to 45 mm (20 mm hole) Length upper arm: 43 cm Length lower arm: 43 cm Colour: Black Cordial CTM 3 FM-BK Professional Microphone Cable Length: 3 m XLR female -&gt; XLR male Neutrik connectors Colour: Black</p>
<b>Lotul 14</b>					
Microphone Stand	Mic Stand Round Base Boom		Roadworx	<p>Microphone Stand (Equivalent Roadworx Mic Stand Round Base Boom) With boom arm and round metal base Length from approx. 92 to 150 cm Boom arm length: 70 cm Threads: 3/8" with 5/8" adapter Base diameter 290 mm Weight: 3.7 kg</p>	<p>Microphone Stand Roadworx Mic Stand Round Base Boom With boom arm and round metal base Length from approx. 92 to 150 cm Boom arm length: 70 cm Threads: 3/8" with 5/8" adapter Base diameter 290 mm Weight: 3.7 kg</p>
<b>Lotul 15</b>					
Level Amplifier	<b>CL-1 Mic Activator</b>		<b>Cloudlifter</b>	<p><b>1-Channel Level Amplifier</b> (Equivalent cloudlifter) +25 dB for dynamic or passive ribbon microphones To be used in conjunction with a microphone amplifier with standard phantom power on mixers/preamplifiers/audio interfaces with mic input Requires phantom power XLR input and output Metal casing included band for fixing to microphone stand Warranty hardware 2 years.</p>	<p><b>1-Channel Level Amplifier Cloudlifter CL-1 Mic Activator</b> +25 dB for dynamic or passive ribbon microphones To be used in conjunction with a microphone amplifier with standard phantom power on mixers/preamplifiers/audio interfaces with mic input Requires phantom power XLR input and output Metal casing included band for fixing to microphone stand Warranty hardware 2 years.</p>
<b>Lotul 17</b>					
Microfon	C417 PP		AKG	<p><b>General Specifications</b> (Equivalent AKG C417 PP) Type Pre-polarized condenser microphone Polar Pattern Omnidirectional</p>	<p><b>General Specifications</b> AKG C417 PP Type Pre-polarized condenser microphone Polar Pattern Omnidirectional</p>

				<p>Audio frequency bandwidth 20 - 20000 Hz  Equivalent noise level 34 dB-A  Sensitivity 7 mV/Pa  Signal to Noise 60 dB-A  Electrical impedance 200 Ohms  Recommended load impedance 1000 Ohms  Cable length 1.5 m (5 ft.)  Type XLR  Gender Female  Contacts 3-pin  Current 2 mA  Warranty hardware 2 years.</p>	<p>Audio frequency bandwidth 20 - 20000 Hz  Equivalent noise level 34 dB-A  Sensitivity 7 mV/Pa  Signal to Noise 60 dB-A  Electrical impedance 200 Ohms  Recommended load impedance 1000 Ohms  Cable length 1.5 m (5 ft.)  Type XLR  Gender Female  Contacts 3-pin  Current 2 mA  Warranty hardware 2 years.</p>	
<b>Lotul 28</b>						
Microfon pentru instrument	MD 421-II		Sennheiser	<p><b>Microphone</b> (Equivalent Sennheiser MD 421-II)  Operating Principal Pressure Gradient  Capsule Dynamic  Polar Pattern Cardioid  Frequency Range 30 Hz to 17 kHz  Impedance 200 Ohms  Sensitivity in free field, no load (1kHz)  2 mV/Pa +- 3 dB  Connectivity  Output Connectors (Analog) 1 x XLR 3-Pin  Warranty hardware 2 years</p>	<p><b>Microphone</b> Sennheiser MD 421-II  Operating Principal Pressure Gradient  Capsule Dynamic  Polar Pattern Cardioid  Frequency Range 30 Hz to 17 kHz  Impedance 200 Ohms  Sensitivity in free field, no load (1kHz)  2 mV/Pa +- 3 dB  Connectivity  Output Connectors (Analog) 1 x XLR 3-Pin  Warranty hardware 2 years</p>	
<b>Lotul 29</b>						
Microfon	MV7B		Shure	<p><b>Dynamic Podcast microphone</b> (Equivalent MV7B)  Control of microphone gain, headphone level, monitor mixing, mute over touch panel interface  Individual adjustments via the ShurePlus motif desktop app possible (e.g., amplification, compression and EQ presets)  Internal shockmount  Directional characteristics: unidirectional (cardioid)  A / D converter: 16/24 bit, 44.1 / 48 kHz  Frequency range: 50 - 16,000 Hz  Adjustable gain: 0 to +36 DB  Sensitivity: XLR -55 DBV / PA (1.78 mV) at 1 kHz  USB -47 DBFS / PA at 1 kHz (with minimal reinforcement)  Flat Mode 1 Pa = 94 DB SPL  USB Maximum SPL 132 DB SPL  DSP modes (presets): near / far, dark / natural / bright  Power supply via USB or LIGHTNING connection  MFI certified  XLR output impedance: 314 ohms at 1 kHz  5/8" Thread  XLR output  XLR output</p>	<p><b>Dynamic Podcast microphone</b> MV7B  Control of microphone gain, headphone level, monitor mixing, mute over touch panel interface  Individual adjustments via the ShurePlus motif desktop app possible (e.g., amplification, compression and EQ presets)  Internal shockmount  Directional characteristics: unidirectional (cardioid)  A / D converter: 16/24 bit, 44.1 / 48 kHz  Frequency range: 50 - 16,000 Hz  Adjustable gain: 0 to +36 DB  Sensitivity: XLR -55 DBV / PA (1.78 mV) at 1 kHz  USB -47 DBFS / PA at 1 kHz (with minimal reinforcement)  Flat Mode 1 Pa = 94 DB SPL  USB Maximum SPL 132 DB SPL  DSP modes (presets): near / far, dark / natural / bright  Power supply via USB or LIGHTNING connection  MFI certified  XLR output impedance: 314 ohms at 1 kHz  5/8" Thread  XLR output  Micro USB output</p>	

				Micro USB output 3.5 mm Jack headphone output Warranty hardware 2 years	3.5 mm Jack headphone output Warranty hardware 2 years	
<b>Lotul 30</b>						
Double Ear Intercom Headset	HMD685		Superlux	<p>Double Ear Intercom Headset (equivalent HMD685) Professional intercom headsets with flexible anti-vibration gooseneck boom microphones. The headset is lightweight, provides extra soft ear cushions and headband paddings for outstanding wearing comfort even during extra soft ear cushions Headset is provided with a dynamic vocal unidirectional patterned microphone, featuring excellent acoustic performance and a reliable noise suppression.</p> <p>HEADPHONE Transducer principle : dynamic, closed Ear coupling : Circumaural Frequency response : 20~20,000 Hz Impedance Double-ear: 200 Ω Sensitivity : 96 dB SPL at 1 kHz, 1 mW Max. Input Power : 100 mW Caliper pressure : approx. 4.5 N Connector : 1.5-meter (4.92') straight cord, 4-pin XLR female plug</p> <p>MICROPHONE Transducer principle : dynamic, cardioid Frequency response : 50~15,000 Hz Polar Pattern : cardioid Sensitivity : -64 dBV/Pa (0.6 mV/Pa) at 1 kHz Impedance : 250 Ω</p>	<p>Double Ear Intercom Headset equivalent HMD685 Professional intercom headsets with flexible anti-vibration gooseneck boom microphones. The headset is lightweight, provides extra soft ear cushions and headband paddings for outstanding wearing comfort even during extra soft ear cushions Headset is provided with a dynamic vocal unidirectional patterned microphone, featuring excellent acoustic performance and a reliable noise suppression.</p> <p>HEADPHONE Transducer principle : dynamic, closed Ear coupling : Circumaural Frequency response : 20~20,000 Hz Impedance Double-ear: 200 Ω Sensitivity : 96 dB SPL at 1 kHz, 1 mW Max. Input Power : 100 mW Caliper pressure : approx. 4.5 N Connector : 1.5-meter (4.92') straight cord, 4-pin XLR female plug</p> <p>MICROPHONE Transducer principle : dynamic, cardioid Frequency response : 50~15,000 Hz Polar Pattern : cardioid Sensitivity : -64 dBV/Pa (0.6 mV/Pa) at 1 kHz Impedance : 250 Ω</p>	
<b>TOTAL</b>						

Semnăt: Numele, Prenumele: Constantin Alexandru În calitate de: director  
Ofertantul: Triomac SRL Adresa: Orhei, str Stefan cel Mare 3, of 16



### Specificații de preț

[Acest tabel va fi completat de către ofertant în coloanele 5,6,7,8 și 11 la necesitate, iar de către autoritatea contractantă – în coloanele 1,2,3,4,9,10]

	Numărul procedurii de achiziție ocds-b3wdp1-MD-1679412085754 din 06/04/2023
	Obiectul achiziției: Echipament audio

Cod CPV	Denumirea bunurilor/serviciilor	Unitatea de măsură	Cantitatea	Preț unitar (fără TVA)	Preț unitar (cu TVA)	Suma fără TVA	Suma cu TVA	Termenul de livrare/prestare	Clasificație bugetară (IBAN)	Discount %
1	2	3	4	5	6	7	8	9	10	11
	<b>Bunuri/servicii</b>									
	Lotul 2									
32323100-4	Combo de chitară electrică	buc	1	6800,00	8160,00	6800,00	8160,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 2</b>					6800,00	8160,00			
	Lotul 3									
32323100-4	Combo de chitară electrică	buc	1	5400,00	6480,00	5400,00	6480,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 3</b>					5400,00	6480,00			
	Lotul 4									

32323100-4	Combo de chitară electrică	buc	1	3140,00	3768,00	3140,00	3768,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 4</b>					3140,00	3768,00			
	Lotul 5									
32323100-4	Microfon set pentru tobe	set	1	13950,00	16740,00	13950,00	16740,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 5</b>					13950,00	16740,00			
	Lotul 6									
32323100-4	Microfon dinamic	buc	2	4850,00	5820,00	9700,00	11640,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 6</b>					9700,00	11640,00			
	Lotul 7									
32323100-4	Microfon vocal	buc	2	7850,00	9420,00	15700,00	18840,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 7</b>					15700,00	18840,00			
	Lotul 9									
32323100-4	Microfon vocal	buc	6	7550,00	9060,00	45300,00	54360,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 9</b>					45300,00	54360,00			
	Lotul 10									
32323100-4	Cablu Multicore	buc	1	2390,00	2868,00	2390,00	2868,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 10</b>					2390,00	2868,00			
	Lotul 11									

32323100-4	Cablu pentru instrument muzical	buc	6	240,00	288,00	1440,00	1728,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 11</b>					1440,00	1728,00			
	Lotul 12									
32323100-4	Saundcard USB	buc	1	32990,00	39588,00	32990,00	39588,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 12</b>					32990,00	39588,00			
	Lotul 13									
32323100-4	Microfon	buc	4	11400,00	13680,00	45600,00	54720,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 13</b>					45600,00	54720,00			
	Lotul 14									
32323100-4	Microphone Stand	buc	1	830,00	996,00	830,00	996,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 14</b>					830,00	996,00			
	Lotul 15									
32323100-4	Level Amplifier	buc	1	3950,00	4740,00	3950,00	4740,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 15</b>					3950,00	4740,00			
	Lotul 17									
32323100-4	Microfon	buc	6	4060,00	4872,00	24360,00	29232,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 17</b>					24360,00	29232,00			
	Lotul 28									

32323100-4	Microfon pentru instrument	buc	4	9740,00	11688,00	38960,00	46752,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 28</b>					38960,00	46752,00			
	Lotul 29									
32323100-4	Microfon	buc	1	6590,00	7908,00	6590,00	7908,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 29</b>					6590,00	7908,00			
	Lotul 30									
32323100-4	Double Ear Intercom Headset	buc	10	2090,00	2508,00	20900,00	25080,00	În decurs de 40 de zile de la intrarea contractului în vigoare.	MD54TRPCCC518430A00044AA	
	<b>Total lot 30</b>					20900,00	25080,00			
	<b>TOTAL</b>					278000,00	333600,00			

Semnat: Numele, Prenumele: Constantin Alexandru În calitate de: director  
Ofertantul: Triomac SRL Adresa: Orhei, str Stefan cel Mare 3, of 16