

Motor ventilator unitate interioara	Model		YKFG-13-4-38L-4
	lesire	W	40
	Condensator	uF	1.2
	Viteza (Hi/Mi/Lo)	r/min	1030 / 900 / 750
Serpentina unitate interioara	a. Numar de randuri		2.0
	b. Pas tub(a)x pas rand(b)	mm	19.5x11.6
	c. Distanta aripioare	mm	1.2
	d. Tip aripioare (cod)		Aluminiu hidrofilic
	e. Diametru ext. tub si tip	mm	Φ5, canal interior tub
	f. Lungime x inaltime x latime serpentina	mm	595x78x23.2+595x117x23.2+595x78x23.2
	g. Numar circuite		4
Debit aer unitate interioara (Hi/Mi/Lo)		m3/h	466/360/325
Nivel zgomot unitate interioara (Hi/Mi/Lo/Si)		dB(A)	38.5/32/25
Nivel zgomot unitate interioara (Hi)		dB(A)	54.0
Unitate interioara	Dimensiuni(W*D*H)	mm	805x194x285
	Ambalare (W*D*H)	mm	870x270x365
	Masa neta/bruta	Kg	7.6/9.7
Motor ventilator unitate interioara	Model		ZKFN-34-10-1
	lesire	W	/
	Condensator	uF	0
	Viteza (Hi/Mi/Lo)	r/min	760/450
Serpentina unitate exterioara	a. Numar de randuri		1
	b. Pas tub(a)x pas rand(b)	mm	21x22
	c. Distanta aripioare	mm	1.3
	d. Tip aripioare (cod)		Aluminiu hidrofilic
	e. Diametru ext. tub si tip	mm	Φ7, canal interior tub
	f. Lungime x inaltime x latime serpentina	mm	740x462x22
	g. Numar circuite		2
Debit aer unitate exterioara		m3/h	1750
Nivel zgomot unitate exterioara		dB(A)	55.5
Nivel max. zgomot unitate exterioara		dB(A)	62.0
Unitate exterioara	Dimensiuni(W*D*H)	mm	720x270x495
	Ambalare (W*D*H)	mm	835x300x540
	Masa Neta/bruta	Kg	23.2/25.0
Refrigerant	tip		R32
	GWP		675
	Cantitate incarcare	Kg	0.55
Presiune proiectata		MPa	4.3/1.7
Conducte refrigerant	Lateral lichid/ lateral gaz	mm (inch)	6.35mm (1/4in)/9.52mm (3/8in)
	Lungime max. conducta refrigerant	m	25
	Diferenta max. de nivel	m	10
Conexiuni cablaj			1.5x5//
Tip stecher			//fara
Tip termostat			Comanda de la distanta
Temperatura lucru	Unitate interioara(racire/ incalzire)	°C	17~32/0~30
	Unitate exterioara(racire/ incalzire)	°C	-15~50/-15~30
Domeniu aplicare minim-maxim		m2	12~18

Caracteristici principale

-  **Racire si incalzire**
-  **Control prin WIFI**
-  **Funcție Follow me**
-  **Auto curatare**
-  **Auto restart**
-  **Mod noapte (Sleep mode)**

CONTER

breeze

POWERED BY

Midea®

ISO 9001

BUREAU VERITAS
Certification

