



ElettriKa

ELECTRIC LOCK FOR DOORS AND GATES

CISA "ElettriKa" is the ideal solution for managing the opening and closing of all kinds of doors and gates, guaranteeing high resistance to forced entry.

MAIN FEATURES AND BENEFITS

- Rotary hook deadbolt for increased resistance to forced entry.
- Self-adjustable floor striker ensuring perfect closure over time.
- Steel casing to protect the lock.
- Electric release system for increased resistance to vibrations and impact strength.





Elettika

Technical features:

- Painted protective steel case
- Metal striker with stainless steel swinging pin
- Rotary hook deadbolt in extruded aluminium
- 12V ac power supply
- Current absorption 3 A
- Non-handed and with a variable backset from 50 to 80 mm

Supplied as standard:

- Striker
- Instruction sheet
- Fixing screws
- 2 spacers for the striker
- 3 keys item 1.01070.10.1

On request:

- Booster device item 1.07022.00.0
- Booster plus device item 1.07022.10.0
- Coil set BTicino device item 1.07025.10.0
- Microswitch device item 1.07023.00.0
- Lighted indicator kit item 1.07126.01.0

Certification:







- ELETTRIKA is certified according to the European standard prEN 14846:08:


| 3 | X | 2 | 0 | 0 | M | 6 | 0 | 2 |






- Security degree 6
(2,000 Kg lateral push resistance)

Hand:
0 = Non-handed



Type	Description	Cylinder	Throws	Backset	Unit weight Kg	Pieces	ITEM Type Dim. Hand Fin. Pers. Spec.
	• Back plate for lock and striker to be welded	 Art. 1 0G150 00 0 Fin.12	50÷80	2,750	6	1	1A721 00 0
	• Version with BTicino coil item 1.07025.10.0		50÷80	2,710	6	1	1A721 00 0 00 PA
	• Version with Booster item 1.07022.00.0		50÷80	2,710	6	1	1A721 00 0 00 PB
	• Version with Booster Plus item 1.07022.10.0		50÷80	2,710	6	1	1A721 00 0 00 PC
	• Galvanized version • Welding plate and striker spacer	 Art. 1 0G150 00 0 Fin.12	50÷80	2,800	1	1	1A721 00 0 79
	• Back plate for lock and striker to be welded • Inner push-button • Hold open device	 Art. 1 0G150 00 0 Fin.12	50÷80	2,800	6	1	1A731 00 0
	• Version with BTicino coil item 1.07025.10.0		50÷80	2,800	6	1	1A731 00 0 00 PA
	• Version with Booster item 1.07022.00.0		50÷80	2,800	6	1	1A731 00 0 00 PB
	• Version with Booster Plus item 1.07022.10.0		50÷80	2,800	6	1	1A731 00 0 00 PC
	• Galvanized version • Welding plate and striker spacer • Inside button • Hold-open device • Galvanized protective case	 Art. 1 0G150 00 0 Fin.12	50÷80	2,800	1	1	1A731 00 0 79

Type	Description	Cylinder	Throws	Backset	Unit weight 	Pieces 	ITEM				
							Type	Dim.	Hand	Fin.	Pers. Spec.
	• Inner push-button • SUPPLIED AS STANDARD: - Striker - Weld plate - Weld striker spacer - Strike spacer set (2pcs) - Fixing screws - Keys item 1.01070.10.1 - Instruction sheet	 Art. 1 06200 55 0 Fin.12	50÷80	2,780	6	1	1A611 00 0 00 DF				

Type	Description	 Unit weight	 Pieces	ITEM			
				Type	Dim.	Hand	Pers. Spec.
	- Booster device may be combined with ElettriKa rim lock to have the following function: Tension adaptor for tension different from 12 V ac (12 Vdc - 24 Vac - 24Vdc) Electrical input reduction Undersized power supply Electric hold open device (ElettriKa only) - Supplied as standard: Fixing screws Instructions sheet - Please note: Booster device may be combined also with all electric locks (electric striker included)	0,085	1	1	07022	00	0
	- Booster Plus device may be combined with ElettriKa rim lock to have the following function: Electronic opening timer with 5 different options (120 sec default) Door condition signal Electric hold open device Tension adaptor for tension different from 12 V ac (12 Vdc - 24 Vac - 24Vdc) Electrical input reduction Undersized power supply - Supplied as standard: Pin to deactivate hold open catch Fixing screws Instructions sheet - ON REQUEST: Open door indicator item 1.07126.01.0	0,185	1	1	07022	10	0
	- Coil for BTicino intercommunication system audio - Swing ref. 344702-03-04 - Video intercommunication system video Swing ref. 344802-03-04 combined with ElettriKa rim lock give door control signal - Supplied as standard: Fixing screws Instructions sheet	0,092	1	1	07025	10	0
	- Microswitch Give a signal to operate motor may be installed directly on the ElettriKa rim lock - Supplied as standard: instruction sheet	0,007	1	1	07023	00	0
	Open door indicator	0,005	1	1	07126	01	0

**Technical features:**

- Zinc-plated steel case and striker
- Dead-locking latch
- 12 V ac
- Current absorption 2,5 A
- External cylinder length: 55 mm.

Supplied as standard:

- Striker
- Instruction sheet
- Fixing screws
(except series 11921-11931)
- 3 keys item 1.01070.10.1
(C2000 key bow)

On request:

- Booster module item 1.07022.00.0

Certifications:

- This electric lock series is certified according to the European standard EN 14846:08:

| 3 | C | 2 | 0 | 0 | L | 3 | 0 | 2 |

Security degree 3

(500 Kg lateral push resistance and 200 Kg front push resistance)









Hand:










1 = R.H. inwards ☐

2 = L.H. inwards ☐

3 = R.H. outwards ☐

4 = L.H. outwards ☐

Type	Description	Cylinder	Throws	Backset	Unit weight Kg	Pieces	ITEM				
							Type	Dim.	Hand	Fin.	Pers. Spec.
 • Protective back plate • Spacer	 1 02139 00 0	50	2,140	5	1	11721	50	1			
		50	2,140	5	1	11721	50	2			
		60	2,140	5	1	11721	60	1			
		60	2,140	5	1	11721	60	2			
		70	2,140	5	1	11721	70	1			
		70	2,140	5	1	11721	70	2			
		80	2,140	5	1	11721	80	1			
		80	2,140	5	1	11721	80	2			
 • Protective back plate • Spacer • Push-button • Hold-open device	 1 02110 00 0	50	2,180	5	1	11731	50	1			
		50	2,180	5	1	11731	50	2			
		60	2,180	5	1	11731	60	1			
		60	2,180	5	1	11731	60	2			
		70	2,180	5	1	11731	70	1			
		70	2,180	5	1	11731	70	2			
		80	2,180	5	1	11731	80	1			
		80	2,180	5	1	11731	80	2			
 • Manual throw deadbolt • Protective back plate • Spacer	 1 02145 00 0	2	50	2,200	5	1	11761	50	1		
		2	50	2,218	5	1	11761	50	2		
		2	60	2,290	5	1	11761	60	1		
		2	60	2,290	5	1	11761	60	2		
		2	70	2,280	5	1	11761	70	1		
		2	70	2,222	5	1	11761	70	2		
		2	80	2,230	5	1	11761	80	1		
		2	80	2,250	5	1	11761	80	2		
 • Manual throw deadbolt • Protective back plate • Spacer • Push-button	 1 02145 00 0	2	50	2,205	1	1	11771	50	1		
		2	50	2,205	1	1	11771	50	2		
		2	60	2,280	1	1	11771	60	1		
		2	60	2,280	1	1	11771	60	2		
		2	70	2,210	1	1	11771	70	1		
		2	70	2,210	1	1	11771	70	2		
		2	80	2,231	1	1	11771	80	1		
		2	80	2,251	1	1	11771	80	2		

Type	Description	Cylinder	Throws	Backset	Kg Unit weight	Pieces	ITEM			
							Type	Dim.	Hand	Fin.
	• For automated and up-and-over gates • Protective back plate • External cylinder length: 70 mm.	 1 02142 00 0	80	2,100	1	1	11823	80	1	
			80	2,100	1	1	11823	80	2	
		 1 02139 00 0	50	1,450	1	1	11921	50	1	
			50	1,450	1	1	11921	50	2	
			60	1,559	1	1	11921	60	1	
			60	1,472	1	1	11921	60	2	
			70	1,472	1	1	11921	70	1	
			70	1,476	1	1	11921	70	2	
			80	1,470	1	1	11921	80	1	
			80	1,475	1	1	11921	80	2	
	• Push-button • Hold-open device	 1 02110 00 0	50	1,475	1	1	11931	50	1	
			50	1,475	1	1	11931	50	2	
			60	1,550	1	1	11931	60	1	
			60	1,472	1	1	11931	60	2	
			70	1,475	1	1	11931	70	1	
			70	1,478	1	1	11931	70	2	
			80	1,470	1	1	11931	80	1	
			80	1,472	1	1	11931	80	2	
	• FOR OUTWARD OPENING GATES	 1 02139 00 0	50	1,539	1	1	11921	50	3	
			50	1,538	1	1	11921	50	4	
			60	1,614	1	1	11921	60	3	
			60	1,534	1	1	11921	60	4	
			70	1,533	1	1	11921	70	3	
			70	1,538	1	1	11921	70	4	
			80	1,539	1	1	11921	80	3	
			80	1,534	1	1	11921	80	4	
	• FOR OUTWARD OPENING GATES • Push-button • Hold-open device	 1 02110 00 0	50	1,536	1	1	11931	50	3	
			50	1,530	1	1	11931	50	4	
			60	1,532	1	1	11931	60	3	
			60	1,532	1	1	11931	60	4	
			70	1,530	1	1	11931	70	3	
			70	1,534	1	1	11931	70	4	
			80	1,532	1	1	11931	80	3	
			80	1,532	1	1	11931	80	4	