

BCS-P-EIP28FSR3L2-AI2

8Mpx dome IP camera, 1/2.7" sensor, 2.8 mm lens.



Index: 11110
GTIN13/EAN13: 5904890706989
URL: <https://bcs.pl/gb/8mpx/3181-bcs-p-eip28fsr3l2-ai2-5904890706989.html>



Description

8Mpx dome IP camera, 1/2.7" sensor, 2.8 mm lens, IR Illuminator - 30m - white light, from BCS Point series. Resolution: 8MPX (3840x2160), video compression: H.265 / H.265 + / H.264 / H.264+ / MJPEG, background compensation: BLC / HLC / WDR (120dB), microphone, speaker, motion detection, privacy mask, perimeter protection, object recognition, face detection, people counting, web service support, IP67 white housing. Power supply: DC 12V / PoE (802.3af). Dimensions: Ø111 x 95mm.

Product Details

Product	BCS-P-EIP28FSR3L2-AI2
Brand	BCS POINT
NDAA	National Defense Authorization Act
Camera type	Dome
Resolution	8 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	3840(H)×2160(V)
Lens	fixed
Focal length	2.8 mm

Aperture	F2.0
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H: 112.4° V: 60.1°
DORI	Detect 84m / Observe 33m / Recognize 17m / Identify 8m
Min illumination	0.01Lux(F2.0,AGC) 0Lux(B/W,IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	2D/3D DNR
Defog	Digital
Image rotate	Mirror, Flip 0°/90°/180°/270°
Stream support	3
Resolutions	8M(3840×2160) / 5M(3072×1728) / 4M(2560×1440) / 2M(1920×1080) / 720P(1280×720) / D1(720×576) / (640×360) / 2CIF(704×288) / CIF(352×288)
Main stream	3840×2160@20fps 3072×1728@30fps 2560×1440@30fps 1920×1080@30fps 1280×720@30fps
Second stream	1920×1080@30fps 1280×720@30fps 720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
Third stream	720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
Bitrate	128Kbps~16Mbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR
Illuminator type	IR LED + White Light
Illuminator	30m
NightColor	Yes
Microphone	Yes
Loudspeaker	Yes
Active deterrence function ADC	Sound-optical alarm
Audio compression	G.711
Memory card slot	microSD 256GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Network security	HTTPS, SSL, TLS, Digest Authentication, Login Authentication, Account Lockout, IP address filtering, ARP protection
Power supply type	12VDC / PoE(802.3af)
Power consumption	max 5W
Housing color	White
IP class	IP67
Working environment	-30℃~+60℃ max 95% RH
Dimensions	Ø111×95mm
Weight	0.42kg
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion

Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - Face detection	Face detection and tracking, snapshot
Ai - People counting	People counting for intrusion and crossline, counting people in/out

Accessories



BCS-AD23



BCS-P-A173



BCS-P-U112



BCS-P-U113



BCS-ADU-B