



DONGFENG TRACTOR

75-85hp wheeled tractor



DF804



Standard:

Combination meter,
Draft and position control and floating control,
Linkage type, double-acting clutch,
Full hydraulic steering,
Spring suspension seat with seat belt,
Suspended pedal, flat floor, side shift

Option:

Dual-hydraulic output, Air braking system, Folding ROPS and Sunshade, Rear ballast,
Cab with heater, Dual hydro-cylinder high pressure raising appliance.

MAIN SPECIFICATIONS



Model	DF754	DF800	DF804	DF850	DF854
ENGINE					
Type	4 cylinder, direct-injection, water-cooled 4-cycle diesel engine				
Model	LR4B3-T67X-U2	LR4B3-T67Y1-U2		LR4M5-T67Y-U2	
Engine Gross, HP(kW)	75(55.1)	80(58.8)		85(62.5)	
PTO, HP(kW)	64.5(47.4)	68.8(50.6)		73.1(53.8)	
Rated Speed, rpm	2300	2300		2300	
Displacement, L	4.94	4.94		4.94	
Fuel Tank Capacity, L	82	82		82	
TRANSMISSION					
Gearbox	12F/12R Meshing sleeve, side shift	12F/12R Meshing sleeve, side shift		12F/12R Meshing sleeve, side shift	
Max forward speed, km/h	1.5-35.3	1.5-35.3		1.5-35.3	
Steering	Full hydraulic steering	Full hydraulic steering		Full hydraulic steering	
Clutch	Linkage type, double-acting clutch	Linkage type, double-acting clutch		Linkage type, double-acting clutch	
Brake	Wet disc brake	Wet disc brake		Wet disc brake	
Differential Lock	Mechanical	Mechanical		Mechanical	
Drive Type	4WD	2WD	4WD	2WD	4WD
PTO					
Rear P.T.O, rpm	540/1000	540/1000		540/1000	
Spline size	6- φ 35 Rectangular spline	6- φ 35 Rectangular spline		6- φ 35 Rectangular spline	
HYDRAULICS					
Pump Type	CBN-F320	CBN-F320		CBN-F320	
Implement pump, L/min	46	46		46	
Remotes Valves (Option)	2	2		2	
3-Point Hitch	CAT. 2	CAT. 2		CAT. 2	
Hydraulic lift Control type	Draft and position control and floating control Dual hydro-cylinder high pressure raising appliance(option)				
Lift Capacity 610 mm behind@ lift balls, kg	1500	1500		1500	
DIMENSIONS					
Overall Length, mm	4120	4120	4120	4120	4120
Overall Width, mm	1980	1980	1980	1980	1980
Overall Height(Top of Cab), mm	2900	2900	2900	2900	2900
Wheelbase, mm	2080	2060	2080	2060	2080
Min.Ground Clearance, mm	380	465	380	465	380
Min.Turning Radius, m	4.2	3.9	4.2	3.9	4.2
Structure weight with cab, kg	2970	2760	2970	2760	2970
TIRES					
AG, Front /Rear	9.5-24/14.9-30	7.50-16/16.9-30	9.5-24/16.9-30	7.50-16/16.9-30	9.5-24/16.9-30