

# **Declaration of Performance**

## EN. Nr. RO-B-F-002

1. Unique identification code of the product-type is given in Table 1:

Table 1

| Product name       | Product form | Code of the product type |  |
|--------------------|--------------|--------------------------|--|
| FASSADE, TF Thermo | Slab         | BF                       |  |

### 2. Intended application:

Thermal insulation for buildings (ThIB).

#### 3. Manufacturer:

SAINT-GOBAIN CONSTRUCTION PRODUCTS ROMANIA SRL

BUCURESTI, SOS. PIPERA, NR. 43, Cladirea Floreasca Park, corp A, etaj 3, birourile 25-41, sector 2.

#### 4. Authorised representative

Not revelant

## 5. System or systems of assessment and verification of constancy of performance:

System 1 and system 3.

#### 6. a. Harmonised standard: SR EN 13162:2012 + A1:2015

Notified body AEROQ No. 1840 performed the determination of the product type, the initial inspection of the manufacturing plant and of the factory production control under system 1, the continuous surveillance, assessment and evaluation of the factory production control and issued certificate of constancy of performance for reaction to fire no. 1840-CPR-99/91/EC/0114-07.

Notified testing laboratory No.1841 performed the test reports for the other relevant declared characteristics.

7. Declared performance

| Essential characteristics              | Performance                         | Abreviation | Unit              | Declared<br>performance |
|--|-------------------------------------|-------------|-------------------|-------------------------|
| Reaction to fire                       | Reaction to fire                    | RtF         | Euroclass         | A1                      |
| Realease of Dangerous Substances       | Realease of Dangerous<br>Substances |             |                   | NPD                     |
| Acoustic absorption index              | Sound absorption                    | ap, au      |                   | NPD                     |
| I Impact Noise Transmission Index      | Dynamic stiffness                   | s'          | MN/m <sup>3</sup> | NPD                     |
|  | Thickness                           | dı          | mm                | NPD                     |
|  | Compressibility                     | c           | mm                | NPD                     |
|  | Air flow resistivity                | AFr         | kPa s/m²          | NPD                     |
| Direct airborne sound insulation index | Air flow resistivity                | AFr         | kPa s/m²          | NPD                     |
| Continous glowing combustion           | Continous glowing combustion        |             |                   | NPO                     |
| uol Bay                                | Thermal Resistance                  | Ro          | m² K/W            | Table 2                 |
|  | Thermal Conductivity                | λο          | W/(m K)           | 0,035                   |

