Kodak alaris



S2060w Scanner

Capture information at the point of entry with an easy to use network document scanner

Developed in the USA

Specifications

Product Highlights	Network models, including wireless connectivity, enabl multiple users to easily share scanners in a distributed environment. Integrate easily using our Web API, so no device drivers need to be installed on the host com- puter, tablet, or mobile device.
Throughput Speeds *	60 ppm / 120 ipm
Feeder Capacity	Up to 80 sheets of 80 g/m² (20 lb.) paper
Connectivity	 USB 3.2 Gen 1x1 USB 3.2 Gen 1x1 = USB 3.1 Gen 1 = USB 3.0 (5Gbps) USB 2.0 compatible Wireless Network 802.11 b/g/n and 10/100 Ethernet
Maximum Document Size The maximum document size supported by the scanner will vary based on the output image resolution and image com- pression used.	216 mm x 3000 mm (8.5 in. x 118 in.)
Minimum Document Size	52 mm x 52 mm (2.05 in. x 2.05 in.) 50 mm x 50 mm (2 in x 2 in) using hand feeding and straight paper path
Paper Thickness & Weight	 27–433 g/m² (7.2–160 lb.) paper Hard card thickness up to 1.25 mm (0.05 in.)
Maximum Optical Resolution	600 dpi
Accessories & Consumables	 Stacking Deflector Accessory Integrated A4/Legal Flatbed KODAK A3 Size Flatbed Accessory Passport Flatbed Accessory Carrier Sleeves (5 PACK) Feed Roller Kit Pre-Separation Pad & Roller Kit
Acoustical Noise	 Off or Ready mode: < 20 dB(A) Scanning: <50 dB(A)
Approvals and Product Certifications	 Argentina (S mark) Australia/New Zealand (RCM) Canada (cTUVus & ICES-003) China (CCC) European Union (CE) European Union (GS Mark) India (BIS) Japan (VCCI) Mexico (NOM) Russia/Eurasian Economic Union (EAC) South Korea (KC) Taiwan (BSMI) US (cTUVus & FCC)

Barcode Reading	○ Codabar
	 Code 128
	• Code 3 of 9
	• EAN-13
	• EAN-8
	 Interleaved 2 of 5
	• PDF417
	• QR
	• UPC-A
	• UPC-E
	○ OFC-L
Bundled Software	 Capture Pro Limited Edition
Choose one and download from the web	• Smart Touch
Data Security	This scanner processes scanned data exclusively
•	through volatile memory ensuring image data is effec-
	tively erased upon shut down. Read more about data
	security.
	-
Dimensions & Weight	W eight: 3.3 kg (7.2 lbs.) Depth: 204 mm (8.0 in.), not in-
	cluding input tray and output tray
	Width: 312 mm (12.3 in.) Height: 182.5 mm (7.2 in.), no
	including input tray
	Depth with Input Tray: 269 mm (10.6 in.)
	Height with Input Tray: 231.6 mm (9.1 in.)
Electrical Requirements	100-240 V (International); 50-60 Hz
Environmental Certification	• 2008 EuP
	 ENERGY STAR Qualified
	• EPEAT Gold
File Format Outputs	• BMP
· · · · · · · · · · · · · · · · · · ·	Native scanner and driver file format
	∘ JPEG
	Native scanner and driver file format
	 Single-page TIFF
	Native scanner and driver file format
	• Microsoft Excel
	available with bundled applications
	 Microsoft Word available with bundled applications
	 Multipage TIFF
	available with bundled applications
	 PDF
	available with bundled applications
	• Text searchable PDF
	available with bundled applications
	• PNG
	available with bundled applications
	• RTF
	available with bundled applications
Image Output Resolution Options	Up to 1200 dpi
	Supported DPI: 75, 100, 150, 200, 240, 250, 260, 300, 400, 500, 600, 120
Network Protocols	• DHCP (or static IP)

Network Protocols

• DHCP (or static IP)

- -

Operating System Compatibility	• WINDOWS Server 2016 X64 Editions
operating offeren companying	• WINDOWS Server 2012 R2 X64 Editions
	• WINDOWS 8.1 (32-bit and 64-bit)
	 WINDOWS 10 (32- and 64-bit)
	• WINDOWS 11 (64 bit)
	• Ubuntu 16.04 64-bit and 32-bit
	• Ubuntu 18.04 64-bit
	 Ubuntu 20.04 64-bit
	• Open SUSE 11.3 (i586) 32-bit
	 Open SUSE LEAP 15.1 64-bit
	 SUSE Linux Enterprise Desktop 12.2 64-bit
	 SUSE Linux Enterprise Desktop 15 SP1 for 64-bit
	 WINDOWS XP SP3 (32-bit and 64-bit) (available only in
	China)
Operating Temperature / Operating Humidity	• Operating Temperature 10-35° C (50-95° F)
	• Operating Humidity 15% - 80% RH
Operator Control Panel	3.5 inch (89 mm) graphical color touchscreen LCD with
	operator control buttons
Optional Software	• Capture Pro Software
	 Info Input Solution
Paper Handling (SurePath) Features	 Controlled stacking
	 Enhanced jam recovery
	 Intelligent Document Protection
	 Interactive multifeed with image display on host
	 Length Multifeed Detection
	 Ultrasonic Multifeed Technology
	• Operator overrides
Perfect Page Image Enhancement Software	 Adaptive threshold processing
	 Add or remove border
	 Aggressive cropping
	 Auto white balance
	 Autocrop
	 Automatic Brightness/Contrast
	 Automatic color balance
	 Automatic color detection
	 Automatic orientation
	 Automatic photo cropping
	 Background color smoothing
	 Barcode reading
	 Black and white image segmentation Brightness and contrast adjustment
	 Brightness and contrast adjustment Content based blank as a merecular
	 Content-based blank page removal
	• Deskew
	• Digital stamping
	 Dual stream scanning
	 Electronic color dropout
	 Enhanced color adjustment
	 Enhanced color management
	 Fixed cropping
	 Fixed thresholding
	o Halftono romoval
os://www.alarisworld.com/en-us/solutions/document-scanners/deskto	pp/s∠uouw-scanner#Brocnures

0	пантоне	ге	IIUVdI

0	Image	edge	fill
---	-------	------	------

0	Image hole fill
---	-----------------

- Image merge
- Image split

iThresholding

- Lone Pixel Noise Removal
- Long document scanning (up to 3000 mm/118 in.)
- Majority rule noise removal
- Multicolor dropout
- Multiple document output

• Running: less than 36 watts

- Orthogonal rotation
- Output Compression-CCITT Group IV, JPEG, Uncompressed Output
- Relative cropping
- Sharpening
- Sleeve scanning (for scanning A3 documents or multiple small documents)

Dual RGB LED Illumination CIS (CMOS); Grayscale out-

put bit depth is 256 levels (8-bit); color output bit depth is 24 bits (8 x 3); color capture bit depth is 48 bits (16 x

- Streak filtering
- Sleep Mode: less than 5.0 watts
 Standby: less than 0.5 watts
 Up to 9,000 pages per day
 Recommended PC Configuration
 Minimum PC configuration with scanning application: Intel Core i3 processor or faster, at least 4 GB RAM (Microsoft Windows)

Scanning Technology

Power Consumption

Standard Software And Drivers

- Citrix certifiedKOFAX certified
- ISIS Drivers
- LINUX (TWAIN and SANE) Drivers
- TWAIN Drivers
- WIA Drivers

Price

\$\$

3)

* Throughput speed may vary depending on your choice of driver application software, operating system, PC and selected image processing features.

Warranty

Included warranty

3-Year Advanced Unit Replacement Plan

(AUR)

Same Model Replacement Remote Support

Extended Warranty and Post-Warranty Options

Advanced Unit Replacement Plan
(AUR)
Next Business Day Response
Same Model Replacement
Remote Support

Professional services

Kodak Alaris offers an array of Professional Services. The Professional Services range from Technical Assistance offerings (e.g., Installation, Training) to Optimization Services (e.g., Capture Workflow Assessments) and more. To inquire or purchase, complete the form below.

Contact

To contact us, complete our information request form below and we will get in touch with you soon.

`
S2060w Scanner
ivacy Policy and allow Kodak Alaris sales representatives to contact me
ewsletters, tips and hints, articles, and product updates.
reCAPTCHA Privacy - Terms

Privacy Policy | Legal / Site Terms

© 2022 Kodak Alaris Inc. TM/MC/MR: Alaris, ScanMate. All trademarks and trade names used are property of their respective holders. The Kodak trademark and trade dress are used under license from Eastman Kodak Company.