



UĞURLU

TARIM MAKİNALARI HAY.VE TAR.ÜR.SAN.TİC.LTD.ŞTİ



MANUFACTURER DECLARATION OF CONFORMITY CERTIFICATE

ÜRETİCİ UYGUNLUK BEYAN SERTİFİKASI

The manufacturer hereby declares that the trailer complies with the requirements of the following EU Regulations/ EEC Directives at the time of manufacture

Üretici işbu belge ile treylerin imalat sırasında aşağıdaki AB Yönetmelikleri/ EEC Direktiflerinin gerekliliklerini karşıladığını beyan eder.

WE Confirm the following features of the vehicle

Aracın aşağıdaki özelliklerini onaylıyoruz

WATER TANK INFORMATION (SU TANKI BİLGİLERİ)

1	Brand (Marka)	UĞURLU
2	Type,variant and version(tip, varyant ve versiyon)	Water Tank, 1 Axle, 4 Tons (pump) (Su Tankı , 1 Dingil, 4 Ton, pompalı)
3	Color(Renk)	Green – (Yeşil)
4	Trailer category (according to ECE) Treyler kategorisi (ECE'ye göre)	R3
5	Manufacturer (Üretici Firma)	UĞURLU TARIM MAKİNALARI HAY.VE TAR.ÜR.SAN.TİC.LTD.ŞTİ
6	Vehicle identification number (VIN) (Araç kimlik numarası (VIN)	
7	Total kg	1320
8	Length(mm) Width(mm) Height(mm) Uzunluk(mm) Genişlik(mm) Yükseklik(mm)	4500 /2050/ 2200
9	Unladen vehicle weight (kg) (Boş araç ağırlığı (kg)	840.kg
10	Maximum allowable weight (kg) (izin verilen maksimum ağırlık (kg)	4,000 KĞ
11	Floorarea (Taban alanı)	-----
12	Number of axles (Dingil sayısı)	1
13	Technically permissible maximum speed (km/h) (Teknik olarak müsaade edilen maksimum hız (km/sa)	40 KM /h
14	Electrical installation (Elektrik Tesisatı)	12 v
15	Braking Force (Frenleme Kuvveti)	40 KM /h
16	Brake(Fren)	HYDRAULIC BRAKES
17	Pumping pressure(Pompa Basıncı)	16 Bar
18	Tire sizes (LastikEbatları)	11,5/80. 15.3
19	Air Tank(Hava Tankı)	-----

UĞURLU TARIM MAKİNALARI
HAY.VE TAR.ÜR.SAN.TİC.LTD.ŞTİ
Develi V.D.No : 056 036 05 96
Tel: 0 352 621 66 88 Fax:0 352 621 20 71
DEVELİ / KAYSERİ

www.ugurlutarim.com.tr

+90 352 621 66 88
+90 533 215 81 03

info@ugurlutarim.com.tr

Bahçelievler Mah. Şehit Üstğ. Ömer Mavi Cad No: 108 Develi / Kayseri / TURKEY

6.1. Length : 4000 mm

7.1. Width : 2 100 mm

8. Height : 1660 mm

11. Rear Length : 940 mm

12.1 The vehicle's upper structure and mass (es) in running order (kg) : 1960 kg

14.1 Maximum laden mass from a technical point of view : 6.960 kg

14.2 Distribution of the among the axles

Front : 5000 kg

Rear : 5000 kg

14.3 Permissible mass on every axle from a technical point of view

Front : 5000 kg

Rear : 5000 kg

32. Tires and wheels

Front : 900/16

Rear : 900/16

44. Maximum speed : 40 km/h

FLM TARIM OTOMOTIV
ŞAH. VE Şİ. LTD. ŞTİ.
Yık. Yeni Sanayi Sitesi Şişli SK. No. 7 BALIKESİR
Şube: Yeni Sanayi Sitesi Şişli SK. No. 10 BALIKESİR
Tel : (0 266) 246 53 81 - Faks : (0 266) 246 53 89
Tic Sic. No. 11021 Mersis No. 0359013469700019
Karesi Vergi Dairesi : 388 013 4687



Main Dispositions:

- ✦ Dual-function clutch
- ✦ Twin turning speeds of P.T.O.
- ✦ Power steering
- ✦ Soft start switch
- ✦ Metal sheet hood
- ✦ Combined meters
- ✦ Quality seat system
- ✦ Seat belt

Options:

- ✦ Creeper gear
- ✦ Cab
- ✦ Hydraulic outlet
- ✦ Air brake system

Tractor Parameters	Model		DF-804/854
	Drive Type		4WD
	Overall Dimensions L × W × H(mm)		4240 × 2050 × 2810
	Wheel Track(mm)	Front	1610
		Rear	1620-2020(1620)
	Wheel Base(mm)		2362
	Ground Clearance(mm)	Under Front Axle	379
	Rated Traction Force(N)		18600/19200
	Construction Mass(Kg)		3575
	Min. Turning Radius(m)		4.1
	Theoretical Speed(km/h)	Forward	2.30,3.60,5.80,8.00,10.0,15.6,25.0,34.9
Reverse		3.10,4.80,7.70,10.80	
Engine Specifications	Model		LRC4108T/4MC-T
	Type		4-cylinder,Upright inline cylinder radiator cooling,4-storke cycle,direct-injetion
	Rated Power(Kw/hp)		59.0/80.0,62.5/85.0
	Rated Fuel Consumption(g/kw/h)		≤242
	Rated Speed(rpm)		2300
	Bore × Stroke(mm)		108 × 135/110 × 135
	Total Displacement(L)		4.94/5.13
Drive System	Clutch		Dry Independent type dual Function clutch
	Gear Box		4 × (2+1) × 2
	Main Drive		One Pair of Spiral Bevel Gear
	Differential		Obturation,four bevel gears
	Differential Lock		Mesh gear
	Final Transmissions		Planetary reduction gear
Travelling Mechanism	Tyre	front	11.2-24
		rear	13.6-38,16.9-34
	Steering Gear		Hydraulic streering
	Brake		Oil immersed muliplate disc
Working Device	Hydraulic System	Lifting Capacity at 610 mm Behind Lift Point(Kg)	3200
		3-point Suspension	Category:II
	P.T.O.Shaft	Rotating Speed(rpm)	540/1000
		Spline size	6- φ 35 Rectangular spline