



FC39/2

Combined refrigerator freezers

+2° + 12°/ - 10° - 30°C from 200/100 to 700/700 lt > Capacity 300 lt



FC39/2 Model

Refrigerator compartment: 200LT - Freezer compartment: 100LT

Structure

External structure in hot-dip galvanized steel, anti-corrosion treated and PVC film coated.
Scotch-brite stainless steel internal structure.

Insulation

60 mm of insulation obtained by injection of high density polyurethane CFC-free foam for excellent product preservation and best energy saving

Door

Two self-closing solid doors with folding magnetic gasket on four sides for perfect closing. Right hand opening or left hand on request. Locks with key.

Light

LED light (energy saving up to 70%) with automatic switch at door opening in refrigerator compartment. Manual switch on control panel.

Internal fittings

3 scotch-brite stainless steel shelves, removable and adjustable in height in refrigerator compartment.

2 scotch-brite stainless steel drawers with telescopic ball-bearing slides and Plexiglas frontal side in freezer compartment.

Temperature range

Refrigerator compartment: between +2°C and +12°C. Factory preset to +4°C.

Freezer compartment: between -10°C and -30°C. Factory preset to -25°C.

Digital adjustable setting with an increment of 0.1°C.

Refrigeration system

Two completely sealed, silent and highly efficient hermetic compressors and ventilated air condensers (suitable also for tropical countries). Forced-air cooling system in refrigerator compartment conceived to achieve maximum temperature uniformity and stability even in case of frequent door openings. Evaporator fan shuts off during door openings. Static evaporator in freezer compartment.

CFC-free R452a refrigerant gas. CFC/HCFC-free R290 refrigerant gas for European countries.

Defrosting

Fully automatic defrosting cycle and auto-evaporation of condensed water in refrigerator compartment. Manual defrost in freezer compartment.

Capacity

Refrigerator compartment: 200LT

Freezer compartment: 100LT

Voltage

230V/50 Hz (on request 230V/60 Hz, 115V/60 Hz)

Absorption

Refrigerator compartment: 155 Watt

Freezer compartment: 175 Watt

Gas

CFC-free R452a refrigerant gas. CFC/HCFC-free R290 refrigerant gas for European countries.

Control panel and alarms

Available:

LGK-2 digital control panel

<https://www.frimed.it/en/control-panel.html#lk-2>

TP-1 full touch control panel

<https://www.frimed.it/en/control-panel.html#tp-1>

Data logger

To record temperatures and alarms in refrigerator and freezer compartments. Download data on USB pen drive.

Standard

- 3 shelves in refrigerator compartment
- 2 drawers in freezer compartment
- Four one way wheels with stabilizing adjustable feet
- 2 locks with key
- Power cord with Schüko type plug (or British plug on request)
- Protection fuses (on power switch and electronic mainboard)
- RFI filter
- Password protected power switch and settings
- Electronic control panel with alarm system
- Remote contact (dry, volt-free) for alarm
- Data logger with USB port to download readings and data
- Memory of latest alarms visible on screen

Optional accessories

- Sliding drawers (up to 3) in scotch-brite stainless steel, with see-through frontal side and telescopic ball-bearings slides in refrigerator compartment
- Internal dividers for drawers
- Additional shelf
- Smooth shelf with borders
- Castors with two frontal brakes
- Weekly temperature chart recorder working with 1,5 V battery, equipped with 52 disks and a pen
- 12V back-up battery (LGK-2) or rechargeable batteries (TP-1 full touch) supplying energy to control panel in order to display temperature and generate alarms in case of power failure
- GSM module to send SMS alarm messages to mobile phones, showing date, time, cabinet temperature and type of alarm (LGK-2)
- LAN Port to connect the appliance via ethernet on PC to monitor correct functioning

(LGK-2)

- Cloud system (TP-1 full touch)
- Independent safety thermostat (DIN 13277 conformity)
- Test hole (Ø 25 mm) for external user sensor
- Electric digital key lock (TP-1 full touch)
- Power supply 115V/60Hz

External dimensions and unit net weight

600x600x1970 (wxdxh-mm)-kg. 127

Dimensions of packaging and shipping weight

- carton box on pallet: 700x700x2200 (wxdxh-mm)-kg. 137
- wooden crate (option on request): 960x840x2260 (wxdxh-mm)-kg. 203

Equipment in accordance with:

Low voltage Directive 2014/35/UE, Electromagnetic Compatibility Directive 2014/30/UE

The picture doesn't necessarily show the product in its standard version.

©Copyright FRI.MED. S.r.l.

Strada Fontaneto 44 10023 Chieri (TO) - Italy
p.IVA /C.F. 07356760012