

rpm measuring instrument

testo 465 - Non-contact rpm measurement

Easy one-hand operation

Storage of mean/min./max. values as well as last measurement value

Measurement distance up to 600 mm

Robust design thanks to SoftCase (protective cover)



With the testo 465, you can measure rpm easily without contact using only one hand. The measuring instrument is thus suitable for measurements on rotating parts such as ventilators and shafts. Simply attach a reflective marker (optional) to the measurement object, point the visible red beam of light at the reflective marker, and measure. The distance to the measurement object is up to 600 mm. The measuring instrument stores mean, min. and max. values as well as the last measurement value. The SoftCase included in delivery protects the instrument from impact, ensuring an especially long working life.

Technical data / Accessories

testo 465

testo 465 RPM measuring instrument with transport case incl. reflectors and batteries



Part no. 0563 0465

Accessories

Sensor type	Optically with mod. light beam
Meas. range	+1 to +99999 rpm
Accuracy ±1 digit	±0.02% of mv
Resolution	0.01 rpm 1 rpm (+1 to +99.99 rpm) (+1000 to +99999 rpn 0.1 rpm (+100 to +999.9 rpm)
Conoral toohni	and data
General techni	
Oper. temp.	0 to +50 °C
Oper. temp. Storage temp.	0 to +50 °C -20 to +70 °C
Oper. temp.	0 to +50 °C
Oper. temp. Storage temp.	0 to +50 °C -20 to +70 °C
Oper. temp. Storage temp. Battery type	0 to +50 °C -20 to +70 °C 2 AA batteries or rech. battery
Oper. temp. Storage temp. Battery type Display	0 to +50 °C -20 to +70 °C 2 AA batteries or rech. battery 5-figure LCD display, 1-line

40 h

Part no.

Accessories for measuring instrument		
Reflectors, self-adhesive (1 pack = 5 off, each 150 mm long)	0554 0493	
ISO calibration certificate/rpm optical and mechanical rpm measuring instruments; cal. points 500; 1000; 3000 rpm	0520 0012	
ISO calibration certificate/rpm optical rpm measuring instruments; calibration points 10; 100; 1000; 10000; 99500 rpm	0520 0022	
ISO calibration certificate/rpm Calibration points freely selectable from 10 to 99500 rpm	0520 0114	
DAkkS calibration certificate/rpm Optical rpm probes, 3 points in instrument measurement range (1 to 99,999 rpm)	0520 0422	

Battery life

0981 9914/msp/A/01.2012

Testo Inc. 40 White Lake Rd. Sparta, NJ 07871 800-227-0729 Email: info@testo.com

www.testo.com