

YC-315EL



- Real Air Cooling

The multi-duct vortex refrigeration system and finned evaporator can prevent frosting completely and improve temperature uniformity to a large extent.

Real Energy Saving

The refrigerator is equipped with "M + Energy Core" power management system and complete air cooling design, improving energy saving efficiency by more than 40%.

M Real Visibility

The electrical heating + LOW-E design with double considerations can achieve a better anti-condensation effect for the glass door.

Real Safety

Seven temperature probes can ensure high precision of temperature control with nearly no fluctuation and thus can improve safety.



Scope of Application

Suitable for storage of biological products, vaccines, drugs, reagents, etc. Suitable for use in pharmacies, pharmaceutical factories, hospitals, centers for disease prevention & control, clinics, etc.

Performance Data / Cooling Curve Cooling Air Temp 325 10 10 10 20 30 40 50 60 70 80 90 100 110 120 130 140 (min) External Dimensions

opeomedicin chare	
2~8°C Pharmacy Refrigerator	
Model	YC-315EL
Cabinet Type	Upright
Capacity(L)	315
Internal Size(W*D*H)mm	580*533*1122
External Size(W*D*H)mm	650*673*1762
Package Size(W*D*H)mm	717*732*1815
NW/GW (Kgs)	87/99
Performance	
Temperature Range	2~8°C
Ambient Temperature	16~32°C
Cooling Performance	5°C
Climate Class	N
Controller	Microprocessor
Display	Digital display
Refrigeration	
Compressor	1pc
Cooling Method	Air cooling
Defrost Mode	Automatic
Refrigerant	R600a
Insulation Thickness (mm)	L/R: 35, B: 52
Construction	
External Material	PCM
Inner Material	HIPS
Shelves	4+1(coated steel wired shelf)
Door Lock with Key	Yes
Lighting	LED
Access Port	1pc. Ø 25 mm
Casters	4+ (2 leveling feet)
Data Logging/Interval/Memory capacity	USB/Record every 10 minutes/100,000 data
Door with Heater	Yes
Alarm	
Temperature	High/Low temperature, High ambient temperature
Electrical	Power failure, Low battery
System	Sensor failure, Door ajar, Built-in USB datalogger failure, Condenser overheating
Electrical	
Power Supply (V/HZ)	220-240~/50
Rated Current (A)	1.35
Power Consumption (KWh/24h)	3.37
Rated Power (W)	245
Accessories	
Standard	RS485, Remote alarm contact, Backup battery

 $^{^{\}star}$ The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading.

^{*}There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.

