

Table Top Low Speed Centrifuge



Introduction:

BKC-TL4MII is a microcomputer controlled desktop low-speed automatic balancing centrifuge. It has a steel body with plastic-sprayed surface, so it has good rigidity, high strength, novel shape, beautiful appearance, low noise, low temperature rise, safety and reliability.

This machine adopts DC brushless maintenance-free motor drive, microcomputer control, door cover protection, make your operation more safe, more convenient, more reliable.

Application:

It can be widely used in the separation of particles of different density in scientific research laboratories and production department such as radioimmunity, biochemistry and pharmacy.

Features:

- * It can store 20 programs, automatic memory from the last running programs.
- * Power failure self-recovery, improve efficiency.
- * The program is adjustable during running, convenient and fast.
- * Adjustable acceleration levels: 16, deceleration levels: 16.
- * It has continuous, instantaneous, point operation modes.
- * LCD display, real-time display of all operating parameters.
- * Program memory function, automatic memory of the last running parameters.
- * English and Chinese could be change freely.

Technical Parameters:

Model	BKC-TL4MII
Max. Speed	4000rpm
Max. RCF	2250xg
Max. Capacity	4*100ml
Speed Precision	±1% or 20rpm
Time Range	1s~999min
Power Supply	AC 110/220V ,50/60Hz
Consumption	250W
Noise	≤65dB
External Size(L*W*H)mm	430*350*270
Package Size(L*W*H)mm	490*420*325
Net Weight/Gross Weight(kg)	18/22



12*10ml

12*20ml

24*10ml

4*50ml

6*50ml

4*100ml

Rotor:

No.	Rotor	Capacity	Max.Speed(rpm)	Max.RCF(xg)
No.1	Angle Rotor	8*15ml	4000	2100
No.2		12*10ml		2200
No.3		12*15ml		2200
No.4		12*20ml		2150
No.5		18*10ml		2250
No.6		24*10ml		2250
No.7		4*50ml		2100
No.8		6*50ml		2100
No.9		4*100ml		2100
No.10		12*5/7ml		2150
No.11		30*5/7ml		2250