

Low Speed Table centrifuge



INTELLIGENT

Intelligent control system

- ☐ Equipped with five groups of programs.
- ☐ Program group shortcut key, large storage space, can store 99 program groups, convenient to call at any time.
- ☐ Automatic electronic door lock.
- ☐ One key short-time centrifuge button.



EXCELLENT

Excellent kernel performance

- ☐ HD large LCD display and the parameters can be revised during operation without shutdown.
- ☐ Microcomputer control ,AC frequency conversion brush-less motor with fast speed and stable operation.
- ☐ 10 gear acceleration /deceleration with linear drive.
- ☐ Two modes can be set: start timing/ arrival revolution timing.


SAFE

Careful and safe

- ☐ With rotor automatic identification system .
Over speed,over heat,unbalance
- ☐ protections with auto lid lock.
- ☐ Steel Structure,centrifuge chamber made
of stainless steel with Environmentally
friendly anti-corrosion coating treatment.


DETAIL

Intimate detail design

- ☐ Special noise reduction system.
An intimate tool rack is provided for
accompanying tools to guard the
instrument at all times.
- ☐ The front of the fuselage is designed
with an operation SOP guide map,
which makes it easier and more
standard for laboratory personnel to
use the instrument.
- ☐ Equipped with rotor lid that can be
quickly locked for easy use.
- ☐ Ergonomic, low opening height, close
the centrifuge lid with one press.

* All products can be customized, designed and produced according to customer requirements.

DT35C Low Speed Table Centrifuge














Technical Parameter



Model	DT35C
Max Speed	5500rpm
Max RCF	4919 × g
Max Capacity	4 × 250ml
Timer	1s ~ 99h59min
Revolutions/min	± 10r/min
Voltage	AC 220 ± 22V 50Hz 10A
Power	550W
Noise Level	≤ 62dB (A)
Size	545 × 330 × 365 (mm)
Net Weight	48kg
Automatic rotor identification	Yes

Rotor Parameter

Rotor NO.	Rotor Pictures	Rotor Capacity (ml)	Max Capacity (r/min)	Max RCF (× g)
Angle Rotor				
1		6 × 50ml (W)	5500rpm	3645 × g
2		24 × 15ml (W)	5000rpm	4145 × g
Swing-out rotor				
3		4 × 50ml	4000rpm	2951 × g
		4 × 100ml	4000rpm	2951 × g
		8 × 50ml	4000rpm	2951 × g

Rotor NO.	Rotor picture	Rotor Capacity (ml)	Max Capacity (r/min)	Max RCF (× g)
3		8 × 100ml	4000rpm	2951 × g
		16 × 10/15ml Optional	4000rpm	2951 × g
		24 × 10/15ml Optional	4000rpm	2951 × g
		32 × 10/15ml Optional	4000rpm	2951 × g
		48 × 2~7ml Blood collection tube	4000rpm	2951 × g
		64 × 5ml Blood collection tube	4000rpm	2951 × g
4		4 × 250ml Round bottom	4000rpm	3040 × g
		4 × 250ml Round bottom (with biosafety lid)	4000rpm	3040 × g
		4 × 250ml Oval cup	4000rpm	3040 × g
		56 × 5ml Blood collection tube	4000rpm	3040 × g
		16 × 50ml Conical/round bottom	4000rpm	3040 × g
		36 × 15ml	4000rpm	3040 × g
5		Micro-plate 2 × 2 × 96 hole	4000rpm	2057 × g

* All products can be customized, designed and produced according to customer requirements.