



## HEXOL CA G2 OPTIMUM

GREASE

### PRODUCT DESCRIPTION

HEXOL Ca G2 OPTIMUM is a calcium-base lubricating grease, with adding 10% graphite, generally used water resistant product. Suitable for lubricating points where among water resistance the sealing ability is required and the operating temperature does not exceed +60°C. Especially suitable for lubrication of pivots, joints in agriculture and industry where dust is typical.

### PERFORMANCE FEATURES

- meets ISO 6743-9: L-XBAHA 2; DIN 51502; KF2C-20; NLGI 2 specifications;
- excellent dynamic water resistance;
- good lubricating characteristic;
- good sealing-ability;
- long-lasting corrosion protection;
- temperature range: between -20°C and +60°C.

### APPLICATION

Suitable for lubricating points where among water resistance and sealing ability is required and the operating temperature does not exceed +60°C.

Suitable for lubricating bearings operated at high speed and load.

### PROPERTIES

Appearance	black, homogeneous
Dropping point [°C]	95
Penetration after 60 strokes at 25 °C [0,1 mm]	235
Corrosion at 60 °C/ 3 h (copper) [grade]	1b
Dynamic water - resistance at 79 °C [mass %]	2

### PACKAGING

<input checked="" type="checkbox"/> 0.4Kg	<input checked="" type="checkbox"/> 1Kg	<input checked="" type="checkbox"/> 4Kg	<input checked="" type="checkbox"/> 15Kg	<input checked="" type="checkbox"/> 180Kg	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 208L	<input type="checkbox"/> 1000L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input type="checkbox"/> 10L	<input type="checkbox"/> 20L	<input type="checkbox"/> 60L		

HEXOL INTERNATIONAL LTD

HEXOL LUBE SRL

Oradea Metropolitan Area • 417166 Paleu, 1A Ardealului st, Bihor • Romania  
Tel +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com

REV.  
2019