

din “ ____ ” _____ 2022

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Procedura de achiziție: nr. ocds-b3wdp1-MD-1649666936152 din 11.04.2022
Obiectul achiziției: Achiziționarea comutatorilor gestionate cu 28 porturi inclusiv 4 SFP (Small Form-factor Pluggable)

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Bunuri/servicii						
Lotul 1	Comutator gestionat cu 28 porturi inclusiv 4 SFP (Small Form-factor Pluggable)					
Comutator gestionat cu 28 porturi inclusiv 4 SFP (Small Form-factor Pluggable)	Catalyst 1000 24port GE, POE, 4x1G SFP	SUA	Cisco	28x ports (24x 10/100/1000 Ethernet PoE+ ports; 4x 1000BASE-T SFP-based ports) - Switching bandwidth: 56 Gbps - Forwarding rate: 41.67 Mpps - Advanced Layer 2 and basic Layer 3 features - DRAM: 512 MB / Flash memory: 256 MB - CPU: ARMv7 800 MHz - Available PoE power: 195W. Support IEEE 802.3af PoE and IEEE 802.3at PoE+ (up to 30W per port) - Management: RMON, SNMP, TELNET, SSH, Console access, Cisco Prime, Cisco	28x ports (24x 10/100/1000 Ethernet PoE+ ports; 4x 1000BASE-T SFP-based ports) - Switching bandwidth: 56 Gbps - Forwarding rate: 41.67 Mpps - Advanced Layer 2 and basic Layer 3 features - DRAM: 512 MB / Flash memory: 256 MB - CPU: ARMv7 800 MHz - Available PoE power: 195W. Support IEEE 802.3af PoE and IEEE 802.3at PoE+ (up to 30W per port) - Management: RMON, SNMP, TELNET, SSH, Console access, Cisco Prime, Cisco	

				Network Plug and Play, and Cisco DNA Center - Network Security: Access control list (ACL L2/L3/L4, MAC,IP,Port based); Port security; IP Source Guard; BPDU guard; Storm control - Authentication: MAC/Certificate/Web-based 802.1X authentication, RADIUS server support - Maximum SPAN sessions: 4 - IPv4/IPv6 static routes, Routing Information Protocol (RIP), 256 unicast routes, 384 IPv4/IPv6 ACL - Standards: IEEE 802.1D Spanning Tree Protocol, IEEE 802.1p, IEEE 802.1Q VLAN, IEEE 802.1w, IEEE 802.1X, IEEE 802.3ad, IEEE 802.3af and IEEE 802.3at, IEEE 802.3ah (100BASE-X single/multimode fiber only), IEEE 802.3x full duplex on 10BASE-T, 100BASE-TX, and 1000BASE-T ports, IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab	Network Plug and Play, and Cisco DNA Center - Network Security: Access control list (ACL L2/L3/L4, MAC,IP,Port based); Port security; IP Source Guard; BPDU guard; Storm control - Authentication: MAC/Certificate/Web-based 802.1X authentication, RADIUS server support - Maximum SPAN sessions: 4 - IPv4/IPv6 static routes, Routing Information Protocol (RIP), 256 unicast routes, 384 IPv4/IPv6 ACL - Standards: IEEE 802.1D Spanning Tree Protocol, IEEE 802.1p, IEEE 802.1Q VLAN, IEEE 802.1w, IEEE 802.1X, IEEE 802.3ad, IEEE 802.3af and IEEE 802.3at, IEEE 802.3ah (100BASE-X single/multimode fiber only), IEEE 802.3x full duplex on 10BASE-T, 100BASE-TX, and 1000BASE-T ports, IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab Garantie: 24 luni	
TOTAL						

Semnăt:_____

Numele, Prenumele: Cioban Alexei

În calitate de: Director

Ofertantul: IT-LAB GRUP SRL

Adresa: mun. Chisinau; str-la Studentilor 2/4 of 217