

Specificații tehnice

Numărul procedurii de achiziție nr. și data indicate în SIA RSAP MTender la procedura de achiziție în cauză
Obiectul achiziției: Echipament de rețea

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Bunuri						
Lotul 1						
1.1 Router tip 1	RB760iGS (hEX S with case)	Lituania, China	MikroTik	Specifications CPU core count 2 CPU nominal frequency 880 MHz CPU Threads count 4 Switch chip model MT7621A Dimensions 113 x 89 x 28 mm RouterOS license 4 Operating System RouterOS Size of RAM 256 MB Storage size 16 MB Storage type FLASH MTBF Approximately 100'000 hours at 25C Tested ambient temperature -40°C to 70°C IPsec hardware acceleration Yes Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 12-57 V Max power consumption 24 W Max power consumption without attachments 6 W Cooling type Passive PoE in 802.3af/at PoE in input Voltage 12-57 V PoE-out PoE-out ports Ether5 PoE out Passive PoE up to 57V Max out per port output (input 18-30 V) 500 mA Max out per port output (input 30-57 V) 500 mA Max total out (A) 500 mA	Specifications CPU core count 2 CPU nominal frequency 880 MHz CPU Threads count 4 Switch chip model MT7621A Dimensions 113 x 89 x 28 mm RouterOS license 4 Operating System RouterOS Size of RAM 256 MB Storage size 16 MB Storage type FLASH MTBF Approximately 100'000 hours at 25C Tested ambient temperature -40°C to 70°C IPsec hardware acceleration Yes Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 12-57 V Max power consumption 24 W Max power consumption without attachments 6 W Cooling type Passive PoE in 802.3af/at PoE in input Voltage 12-57 V PoE-out PoE-out ports Ether5 PoE out Passive PoE up to 57V Max out per port output (input 18-30 V) 500 mA Max out per port output (input 30-57 V) 500 mA Max total out (A) 500 mA	

				Ethernet 10/100/1000 Ethernet ports 5 Fiber SFP ports 1 Peripherals Memory card type microSD Memory Cards 1 Number of USB ports 1 USB Power Reset Yes USB slot type USB type A Max USB current (A) 1 Other PCB temperature monitor Yes Voltage Monitor Yes Mode button Yes Beeper Yes Certification & Approvals Certification CE, EAC, ROHS IP IP20 Case included Yes Warranty 12 months	Ethernet 10/100/1000 Ethernet ports 5 Fiber SFP ports 1 Peripherals Memory card type microSD Memory Cards 1 Number of USB ports 1 USB Power Reset Yes USB slot type USB type A Max USB current (A) 1 Other PCB temperature monitor Yes Voltage Monitor Yes Mode button Yes Beeper Yes Certification & Approvals Certification CE, EAC, ROHS IP IP20 Case included Yes Warranty 12 months	
1.2 Router tip 2	RouterBOARD 3011UiAS-RM with 1U rackmount case and power	Letonia, Lithuania	MikroTik	Specifications Architecture ARM 32bit CPU IPQ-8064 CPU core count 2 CPU nominal frequency 1.4 GHz Switch chip model QCA8337 Dimensions 443 x 92 x 44 mm RouterOS license 5 Operating System RouterOS Size of RAM 1 GB Storage size 128 MB Storage type NAND MTBF Approximately 200'000 hours at 25C Tested ambient temperature -20°C to 70°C IPsec hardware acceleration Yes Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 10-30 V Max power consumption 30 W Max power consumption without attachments 10 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 10-30 V PoE-out PoE-out ports Ether10 PoE out Passive PoE Max out per port output (input 18-30 V) 600 mA Max total out (A) 600 mA Ethernet	Specifications Architecture ARM 32bit CPU IPQ-8064 CPU core count 2 CPU nominal frequency 1.4 GHz Switch chip model QCA8337 Dimensions 443 x 92 x 44 mm RouterOS license 5 Operating System RouterOS Size of RAM 1 GB Storage size 128 MB Storage type NAND MTBF Approximately 200'000 hours at 25C Tested ambient temperature -20°C to 70°C IPsec hardware acceleration Yes Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 10-30 V Max power consumption 30 W Max power consumption without attachments 10 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 10-30 V PoE-out PoE-out ports Ether10 PoE out Passive PoE Max out per port output (input 18-30 V) 600 mA Max total out (A) 600 mA Ethernet	

				10/100/1000 Ethernet ports 10 Fiber SFP ports 1 Peripherals Serial console port RJ45 Number of USB ports 1 USB Power Reset Yes USB slot type USB 3.0 type A Max USB current (A) 1 Other PCB temperature monitor Yes Voltage Monitor Yes Beeper Yes Certification & Approvals Certification CE, EAC, ROHS IP IP20 1U rackmount case and power included Yes Warranty 12 month	10/100/1000 Ethernet ports 10 Fiber SFP ports 1 Peripherals Serial console port RJ45 Number of USB ports 1 USB Power Reset Yes USB slot type USB 3.0 type A Max USB current (A) 1 Other PCB temperature monitor Yes Voltage Monitor Yes Beeper Yes Certification & Approvals Certification CE, EAC, ROHS IP IP20 1U rackmount case and power included Yes Warranty 12 month	
1.3 Router tip 3	RouterBOARD 4011iGS+ with 1U rackmount case	Letonia, Lithuania	MikroTik	Specifications Architecture ARM 32bit CPU AL21400 CPU core count 4 CPU nominal frequency auto (533 - 1900) MHz Switch chip model RTL8367SB Dimensions 228 x 120 x 30 mm RouterOS license 5 Operating System RouterOS (v7 only) Size of RAM 1 GB Storage size 512 MB Storage type NAND MTBF Approximately 200'000 hours at 25C Tested ambient temperature -40°C to 70°C IPsec hardware acceleration Yes Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 12-57 V Max power consumption 33 W Max power consumption without attachments 18 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 18-57 V PoE-out PoE-out ports Ether10 PoE out Passive PoE up to 57V Max out per port output (input 18-30 V) 600 mA Max out per port output (input 30-57 V) 420 mA Max total out (A) 600 mA Ethernet 10/100/1000 Ethernet ports 10 Fiber	Specifications Architecture ARM 32bit CPU AL21400 CPU core count 4 CPU nominal frequency auto (533 - 1900) MHz Switch chip model RTL8367SB Dimensions 228 x 120 x 30 mm RouterOS license 5 Operating System RouterOS (v7 only) Size of RAM 1 GB Storage size 512 MB Storage type NAND MTBF Approximately 200'000 hours at 25C Tested ambient temperature -40°C to 70°C IPsec hardware acceleration Yes Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 12-57 V Max power consumption 33 W Max power consumption without attachments 18 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 18-57 V PoE-out PoE-out ports Ether10 PoE out Passive PoE up to 57V Max out per port output (input 18-30 V) 600 mA Max out per port output (input 30-57 V) 420 mA Max total out (A) 600 mA Ethernet 10/100/1000 Ethernet ports 10 Fiber	

				SFP+ ports 1 Peripherals Serial console port RJ45 Other PCB temperature monitor Yes Voltage Monitor Yes Certification & Approvals Certification CE, EAC, ROHS IP IP20 1U rackmount case included Yes Warranty 12 month	SFP+ ports 1 Peripherals Serial console port RJ45 Other PCB temperature monitor Yes Voltage Monitor Yes Certification & Approvals Certification CE, EAC, ROHS IP IP20 1U rackmount case included Yes Warranty 12 month	
1.4 Router tip 4	Cloud Router Switch 326-24G-2S+RM with RouterOS L5,1U rackmount enclosure	Letonia, China	MikroTik	Specifications Architecture ARM 32bit CPU 98DX3236 CPU core count 1 CPU nominal frequency 800 MHz Switch chip model 98DX3236 Dimensions 443 x 144 x 44 mm RouterOS license 5 Operating System RouterOS / SwitchOS Size of RAM 512 MB Storage size 16 MB Storage type FLASH MTBF Approximately 200'000 hours at 25C Tested ambient temperature -40°C to 60°C Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 10-30 V Max power consumption 24 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 10-30 V Ethernet 10/100/1000 Ethernet ports 24 Fiber SFP+ ports 2 Peripherals Serial console port RJ45 Certification & Approvals Certification CE, EAC, ROHS IP IP20 RouterOS L5 included Yes 1U rackmount enclosure included Yes Warranty 12 months	Specifications Architecture ARM 32bit CPU 98DX3236 CPU core count 1 CPU nominal frequency 800 MHz Switch chip model 98DX3236 Dimensions 443 x 144 x 44 mm RouterOS license 5 Operating System RouterOS / SwitchOS Size of RAM 512 MB Storage size 16 MB Storage type FLASH MTBF Approximately 200'000 hours at 25C Tested ambient temperature -40°C to 60°C Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 10-30 V Max power consumption 24 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 10-30 V Ethernet 10/100/1000 Ethernet ports 24 Fiber SFP+ ports 2 Peripherals Serial console port RJ45 Certification & Approvals Certification CE, EAC, ROHS IP IP20 RouterOS L5 included Yes 1U rackmount enclosure included Yes Warranty 12 months	
1.5 Router tip 5	CRS328-24P-4S+RM with RouterOS L5, 1U rackmount enclosure	Letonia, China	MikroTik	Specifications Architecture ARM 32bit CPU 98DX3236 CPU core count 1 CPU nominal frequency 800 MHz Switch chip model 98DX3236	Specifications Architecture ARM 32bit CPU 98DX3236 CPU core count 1 CPU nominal frequency 800 MHz Switch chip model 98DX3236	

				Dimensions 443 x 300 x 44 mm RouterOS license 5 Operating System RouterOS / SwitchOS Size of RAM 512 MB Storage size 16 MB Storage type FLASH MTBF Approximately 200'000 hours at 25C Tested ambient temperature -20°C to 60°C Powering Number of AC inputs 1 AC input range 100-240 Max power consumption 494 W Max power consumption without attachments 44 W Cooling type 2 fans PoE-out PoE-out ports Ether1-Ether24 PoE out 802.3af/at Max out per port output (input 18-30 V) 1000 mA Max out per port output (input 30-57 V) 450 mA Max total out (A) 20 A Ethernet 10/100/1000 Ethernet ports 24 Fiber SFP+ ports 4 Peripherals Serial console port RJ45 Other CPU temperature monitor Yes Current Monitor Yes PCB temperature monitor Yes Voltage Monitor Yes Mode button Yes Certification & Approvals Certification CE, EAC, ROHS IP IP00 RouterOS L5 included Yes 1U rackmount enclosure included Yes Warranty 12 months	Dimensions 443 x 300 x 44 mm RouterOS license 5 Operating System RouterOS / SwitchOS Size of RAM 512 MB Storage size 16 MB Storage type FLASH MTBF Approximately 200'000 hours at 25C Tested ambient temperature -20°C to 60°C Powering Number of AC inputs 1 AC input range 100-240 Max power consumption 494 W Max power consumption without attachments 44 W Cooling type 2 fans PoE-out PoE-out ports Ether1-Ether24 PoE out 802.3af/at Max out per port output (input 18-30 V) 1000 mA Max out per port output (input 30-57 V) 450 mA Max total out (A) 20 A Ethernet 10/100/1000 Ethernet ports 24 Fiber SFP+ ports 4 Peripherals Serial console port RJ45 Other CPU temperature monitor Yes Current Monitor Yes PCB temperature monitor Yes Voltage Monitor Yes Mode button Yes Certification & Approvals Certification CE, EAC, ROHS IP IP00 RouterOS L5 included Yes 1U rackmount enclosure included Yes Warranty 12 months	
1.6 Router tip 6	Cloud Router Switch 112-8P-4S-IN with POE-out and with RouterOS L5	Letonia, China	MikroTik	Specifications Architecture MIPSBE CPU QCA8511 CPU core count 1 CPU nominal frequency 400 MHz Switch chip model QCA8511 Dimensions 200 x 142 x 44 mm RouterOS license 5 Operating System RouterOS Size of RAM 128 MB Storage size 16 MB Storage type FLASH	Specifications Architecture MIPSBE CPU QCA8511 CPU core count 1 CPU nominal frequency 400 MHz Switch chip model QCA8511 Dimensions 200 x 142 x 44 mm RouterOS license 5 Operating System RouterOS Size of RAM 128 MB Storage size 16 MB Storage type FLASH	

				MTBF Approximately 200'000 hours at 25C Tested ambient temperature -20°C to 60°C Powering Number of DC inputs 2 (DC jack) DC jack input Voltage 18-28 V / 48-57 V Max power consumption 160 W Max power consumption without attachments 10 W Cooling type Passive PoE-out PoE-out ports Ether1-Ether8 PoE out 802.3af/at Max out per port output (input 18-30 V) 1 A Max out per port output (input 30-57 V) 450 mA Max total out (A) 2.8A (18V-28V) & 1.4A (48V-57V) A Ethernet 10/100/1000 Ethernet ports 8 Number of 1G Ethernet ports with PoE-out 8 Fiber SFP ports 4 Peripherals Serial console port RJ45 Other PCB temperature monitor Yes Certification & Approvals Certification CE, EAC, ROHS IP IP20 POE-out included Yes RouterOS L5 included Yes Warranty 12 months	MTBF Approximately 200'000 hours at 25C Tested ambient temperature -20°C to 60°C Powering Number of DC inputs 2 (DC jack) DC jack input Voltage 18-28 V / 48-57 V Max power consumption 160 W Max power consumption without attachments 10 W Cooling type Passive PoE-out PoE-out ports Ether1-Ether8 PoE out 802.3af/at Max out per port output (input 18-30 V) 1 A Max out per port output (input 30-57 V) 450 mA Max total out (A) 2.8A (18V-28V) & 1.4A (48V-57V) A Ethernet 10/100/1000 Ethernet ports 8 Number of 1G Ethernet ports with PoE-out 8 Fiber SFP ports 4 Peripherals Serial console port RJ45 Other PCB temperature monitor Yes Certification & Approvals Certification CE, EAC, ROHS IP IP20 POE-out included Yes RouterOS L5 included Yes Warranty 12 months	
1.7 Router tip 7	RBD52G-5HacD2HnD-TC (hAP ac2 with RouterOS L4)	Letonia, China	MikroTik	Specifications Architecture ARM 32bit CPU IPQ-4018 CPU core count 4 CPU nominal frequency 716 MHz Switch chip model IPQ-4018 Dimensions 34 x 119 x 98mm RouterOS license 4 Operating System RouterOS Size of RAM 128 MB Storage size 16 MB Storage type FLASH MTBF Approximately 100'000 hours at 25C Tested ambient temperature -40°C to 50°C IPsec hardware acceleration Yes Wireless capabilities Wireless 2.4 GHz Max data rate 300 Mbit/s Wireless 2.4 GHz number of chains 2 Wireless 2.4 GHz standards 802.11b/g/n Antenna gain dBi for 2.4 GHz 2.5	Specifications Architecture ARM 32bit CPU IPQ-4018 CPU core count 4 CPU nominal frequency 716 MHz Switch chip model IPQ-4018 Dimensions 34 x 119 x 98mm RouterOS license 4 Operating System RouterOS Size of RAM 128 MB Storage size 16 MB Storage type FLASH MTBF Approximately 100'000 hours at 25C Tested ambient temperature -40°C to 50°C IPsec hardware acceleration Yes Wireless capabilities Wireless 2.4 GHz Max data rate 300 Mbit/s Wireless 2.4 GHz number of chains 2 Wireless 2.4 GHz standards 802.11b/g/n Antenna gain dBi for 2.4 GHz 2.5	

				Wireless 2.4 GHz chip model IPQ-4018 Wireless 2.4 GHz generation Wi-Fi 4 Wireless 5 GHz Max data rate 867 Mbit/s Wireless 5 GHz number of chains 2 Wireless 5 GHz standards 802.11a/n/ac Antenna gain dBi for 5 GHz 2.5 Wireless 5 GHz chip model IPQ-4018 Wireless 5 GHz generation Wi-Fi 5 WiFi speed AC1200 Ethernet 10/100/1000 Ethernet ports 5 Peripherals Number of USB ports 1 USB Power Reset Yes USB slot type USB type A Max USB current (A) 1 Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 12-30 V Max power consumption 21 W Max power consumption without attachments 16 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 18-28 V Certification & Approvals Certification CE, FCC, IC, EAC, ROHS IP IP20 Other Mode button Yes Wireless specifications<table><tr><th>2.4 GHz</th><th>Transmit (dBm)</th></tr><tr><td>Receive Sensitivity</td><td></td></tr><tr><td>1MBit/s</td><td>27</td></tr><tr><td>-100</td><td></td></tr><tr><td>11MBit/s</td><td>27</td></tr><tr><td>-94</td><td></td></tr><tr><td>6MBit/s</td><td>27</td></tr><tr><td>-96</td><td></td></tr><tr><td>54MBit/s</td><td>24</td></tr><tr><td>-78</td><td></td></tr><tr><td>MCS0</td><td>27</td></tr><tr><td>-96</td><td></td></tr><tr><td>MCS7</td><td>23</td></tr><tr><td>-73</td><td></td></tr><tr><th>5 GHz</th><th>Transmit (dBm)</th></tr><tr><td>Receive Sensitivity</td><td></td></tr><tr><td>6MBit/s</td><td>26</td></tr><tr><td>-96</td><td></td></tr><tr><td>54MBit/s</td><td>22</td></tr><tr><td>-80</td><td></td></tr></table>	2.4 GHz	Transmit (dBm)	Receive Sensitivity		1MBit/s	27	-100		11MBit/s	27	-94		6MBit/s	27	-96		54MBit/s	24	-78		MCS0	27	-96		MCS7	23	-73		5 GHz	Transmit (dBm)	Receive Sensitivity		6MBit/s	26	-96		54MBit/s	22	-80		Wireless 2.4 GHz chip model IPQ-4018 Wireless 2.4 GHz generation Wi-Fi 4 Wireless 5 GHz Max data rate 867 Mbit/s Wireless 5 GHz number of chains 2 Wireless 5 GHz standards 802.11a/n/ac Antenna gain dBi for 5 GHz 2.5 Wireless 5 GHz chip model IPQ-4018 Wireless 5 GHz generation Wi-Fi 5 WiFi speed AC1200 Ethernet 10/100/1000 Ethernet ports 5 Peripherals Number of USB ports 1 USB Power Reset Yes USB slot type USB type A Max USB current (A) 1 Powering Number of DC inputs 2 (DC jack, PoE-IN) DC jack input Voltage 12-30 V Max power consumption 21 W Max power consumption without attachments 16 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 18-28 V Certification & Approvals Certification CE, FCC, IC, EAC, ROHS IP IP20 Other Mode button Yes Wireless specifications<table><tr><th>2.4 GHz</th><th>Transmit (dBm)</th><th>Receive</th></tr><tr><td>Sensitivity</td><td></td><td></td></tr><tr><td>1MBit/s</td><td>27</td><td>-</td></tr><tr><td>100</td><td></td><td></td></tr><tr><td>11MBit/s</td><td>27</td><td>-</td></tr><tr><td>94</td><td></td><td></td></tr><tr><td>6MBit/s</td><td>27</td><td>-</td></tr><tr><td>96</td><td></td><td></td></tr><tr><td>54MBit/s</td><td>24</td><td>-</td></tr><tr><td>78</td><td></td><td></td></tr><tr><td>MCS0</td><td>27</td><td>-</td></tr><tr><td>96</td><td></td><td></td></tr><tr><td>MCS7</td><td>23</td><td>-</td></tr><tr><td>73</td><td></td><td></td></tr><tr><th>5 GHz</th><th>Transmit (dBm)</th><th>Receive</th></tr><tr><td>Sensitivity</td><td></td><td></td></tr><tr><td>6MBit/s</td><td>26</td><td>-</td></tr><tr><td>96</td><td></td><td></td></tr><tr><td>54MBit/s</td><td>22</td><td>-</td></tr><tr><td>80</td><td></td><td></td></tr></table>	2.4 GHz	Transmit (dBm)	Receive	Sensitivity			1MBit/s	27	-	100			11MBit/s	27	-	94			6MBit/s	27	-	96			54MBit/s	24	-	78			MCS0	27	-	96			MCS7	23	-	73			5 GHz	Transmit (dBm)	Receive	Sensitivity			6MBit/s	26	-	96			54MBit/s	22	-	80			
2.4 GHz	Transmit (dBm)																																																																																																									
Receive Sensitivity																																																																																																										
1MBit/s	27																																																																																																									
-100																																																																																																										
11MBit/s	27																																																																																																									
-94																																																																																																										
6MBit/s	27																																																																																																									
-96																																																																																																										
54MBit/s	24																																																																																																									
-78																																																																																																										
MCS0	27																																																																																																									
-96																																																																																																										
MCS7	23																																																																																																									
-73																																																																																																										
5 GHz	Transmit (dBm)																																																																																																									
Receive Sensitivity																																																																																																										
6MBit/s	26																																																																																																									
-96																																																																																																										
54MBit/s	22																																																																																																									
-80																																																																																																										
2.4 GHz	Transmit (dBm)	Receive																																																																																																								
Sensitivity																																																																																																										
1MBit/s	27	-																																																																																																								
100																																																																																																										
11MBit/s	27	-																																																																																																								
94																																																																																																										
6MBit/s	27	-																																																																																																								
96																																																																																																										
54MBit/s	24	-																																																																																																								
78																																																																																																										
MCS0	27	-																																																																																																								
96																																																																																																										
MCS7	23	-																																																																																																								
73																																																																																																										
5 GHz	Transmit (dBm)	Receive																																																																																																								
Sensitivity																																																																																																										
6MBit/s	26	-																																																																																																								
96																																																																																																										
54MBit/s	22	-																																																																																																								
80																																																																																																										

				MCS0 26 -96 MCS7 21 -75 MCS9 19 -70 RouterOS L4 included Yes Warranty 12 months	MCS0 26 96 MCS7 21 75 MCS9 19 70 RouterOS L4 included Yes Warranty 12 months	- - - -	
1.8 Router tip 8	C52iG-5HaxD2HaxD-TC (hAP ax2 with RouterOS L4 license,International version)	Letonia, China	MikroTik	Specifications Architecture ARM 64bit CPU IPQ-6010 CPU core count 4 CPU nominal frequency 864 MHz Switch chip model IPQ-6010 RouterOS license 4 Operating System RouterOS (v7 only) Size of RAM 1 GB Storage size 128 MB Storage type NAND MTBF Approximately 100'000 hours at 25C Tested ambient temperature -40°C to 50°C IPsec hardware acceleration Yes Wireless capabilities Wireless 5 GHz Max data rate 1200 Mbit/s Wireless 5 GHz number of chains 2 Wireless 5 GHz standards 802.11a/n/ac/ax Antenna gain dBi for 5 GHz 4 Wireless 5 GHz chip model QCN-5052 Wireless 5 GHz generation Wi-Fi 6 Wireless 2.4 GHz Max data rate 574 Mbit/s Wireless 2.4 GHz number of chains 2 Wireless 2.4 GHz standards 802.11b/g/n/ax Antenna gain dBi for 2.4 GHz 4.5 Wireless 2.4 GHz chip model QCN-5022 Wireless 2.4 GHz generation Wi-Fi 6 WiFi speed AX1800 Ethernet 10/100/1000 Ethernet ports 5 Number of 1G Ethernet ports with PoE-out 1 Powering Number of DC inputs 2 (PoE-IN, DC jack) DC jack input Voltage 12-28 V Max power consumption 27 W Max power consumption without attachments 12 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 18-28 V PoE-out PoE-out ports Ether 1	Specifications Architecture ARM 64bit CPU IPQ-6010 CPU core count 4 CPU nominal frequency 864 MHz Switch chip model IPQ-6010 RouterOS license 4 Operating System RouterOS (v7 only) Size of RAM 1 GB Storage size 128 MB Storage type NAND MTBF Approximately 100'000 hours at 25C Tested ambient temperature -40°C to 50°C IPsec hardware acceleration Yes Wireless capabilities Wireless 5 GHz Max data rate 1200 Mbit/s Wireless 5 GHz number of chains 2 Wireless 5 GHz standards 802.11a/n/ac/ax Antenna gain dBi for 5 GHz 4 Wireless 5 GHz chip model QCN-5052 Wireless 5 GHz generation Wi-Fi 6 Wireless 2.4 GHz Max data rate 574 Mbit/s Wireless 2.4 GHz number of chains 2 Wireless 2.4 GHz standards 802.11b/g/n/ax Antenna gain dBi for 2.4 GHz 4.5 Wireless 2.4 GHz chip model QCN-5022 Wireless 2.4 GHz generation Wi-Fi 6 WiFi speed AX1800 Ethernet 10/100/1000 Ethernet ports 5 Number of 1G Ethernet ports with PoE-out 1 Powering Number of DC inputs 2 (PoE-IN, DC jack) DC jack input Voltage 12-28 V Max power consumption 27 W Max power consumption without attachments 12 W Cooling type Passive PoE in Passive PoE PoE in input Voltage 18-28 V PoE-out PoE-out ports Ether 1 PoE out Passive PoE		

				PoE out Passive PoE Max out per port output (input 18-30 V) 600 mA Max total out (A) 0.6 A Total output current 0.6 Total output power 16.8W RouterOS included Yes Warranty 12 months	Max out per port output (input 18-30 V) 600 mA Max total out (A) 0.6 A Total output current 0.6 Total output power 16.8W RouterOS included Yes Warranty 12 months	
TOTAL						

Semnata:_____

Numele, Prenumele: Cioban Alexei

În calitate de: Director

Ofertantul: IT-LAB GRUP SRL

Adresa: mun. Chisinau; str-la Studentilor 2/4 of 217