

# Laboratory Refrigerator



BPR-5V50(G)



BPR-5V100(G)

## Technical Parameters

Model	BPR-5V50(G)	BPR-5V100(G)
External Size(W*D*H)mm	495*548*683	495*548*934
Internal Size(W*D*H)mm	415*405*455	415*405*706
Capacity	50L	100L
Temperature Range	2-8°C	
Temperature Accuracy	0.1°C	
Control System	Microprocessor Control	
Alarm	Audible and visual alarm for: High and low temperature,Door Ajar	
Refrigeration Type	Forced air refrigeration system	
Refrigerant	R600a	
Climate Type	N, SN	
Glass Door	Toughened with electric heating function,no condensation	
Construction	Constructure	Unibody design& High Pressure and High Density Cyclopentane Foaming
	Internal material	Cold-rolled steel coated with anti-bacteria powder
	External material	Cold-rolled steel coated with anti-bacteria powder
Consumption	95W	100W
Power Supply	AC220V±10%, 50/60Hz; AC110V±10%, 50/60Hz	
Shelves	2pcs, cold drawn steel wire impregnated shelf	3 pcs,cold drawn steel wire impregnated shelf
Door Lock	1 pc	
Accessory	Optional: Probe Access Port, Remote Alarm; Standard: USB Port	
Package Size(W*D*H)mm	560*668*858	560*668*1109
Gross Weight(kg)	49	61