



Viale G.di Vittorio, 30
20090 Pantigliate (MI) Italy

Phone. 02.55230061

<http://www.histoline.com>

email: histoline@histoline.com

Technical Sheet

HISTO-PRO300 Vacuum Tissue Processor



Revision Date: 16/02/2017

INDEX

1.Features	3
1.2 Information and use of the instrument.....	4
1.3 Processor capacity	8
2.Technical features	9
2.1 Technical Data	9
2.2 Paraffin stations.....	9
2.3 Process chamber	9
2.4 Stationing reagents.....	10
2.5 Hardware and software.....	10
2.6 Capacity	10
2.7 Dimensions and weight	10
2.8 Instrument equipment	10

1.Features



1.2 Information and use of the instrument

The Histo-Pro 300 is an automatic tissue processor is designed for the laboratories of Histology and research.

This recently-built instrument Histo-Line Laboratories home combines the simplicity of use of the same by operators with maximum safety and reliability.


Clarity and ease of access to the controls can be found in front of the instrument, equipped with a touch screen color screen attached to the control panel.

It equipped with an intelligent software and easy to use, with an alarm system as a reminder or failure of the instrument

Multiple system of sample protection.

- S6 Histo-Pro 300 processes all biological tissues, both with standard protocols and substitutes do not as toxic as Diaphane (xylene substitute and d-lemonene). For both the processor is designed with optimized protocols and adaptable to all circumstances.
- S3 The software maintains all the necessary protocols, with the option to set: the reagents used, the processing time, the operating temperature, the stirring time.





Using the control panel, you can view and modify the operating parameters, such as processing programs, the temperature of the wax rooms.

Also it allows for daily and weekly programming on and off.

The adjustment of the working temperature is carried out via electronic thermostat with microprocessor.




The operator can set the different programs, diversified by time, temperature; there are also special programs for the cleaning of paraffin rooms.

In the front part, behind a small flap retractable, there are the hose connections for filling and emptying of reagent tanks and / or paraffin.

The basket provided offers the possibility of having different load quantities: ~100, ~200, ~300 cassettes with use controlled amounts of reagent according to the load.

S2 Screen 14" a color touch screen, is resistant to solvents, with a graphical representation of the management process of the instrument, through an intuitive software.



The ergonomic design allows for easy accessibility.

All major functions for the user are easy to access. This includes the hose connections for filling and emptying of the remote reagents and / or paraffin.

The filling and emptying increase user safety.

The simple and safe filling of the system, thanks to the level sensors, ensures that the reagent tanks are always filled in the correct amounts.

S21 The result: maximum protection of the operator, quality of materials and minimization of operational errors.

1.3 Processor capacity

S6, S7 The instrument to process up to 20 fully settable by the operator programs and composed of a maximum of 10 reagent and 3 pools of paraffin.

Time for each program: from 0 to 99 hours and 59 minutes.

S9 Up to 300 cassettes can be processed simultaneously

Wax clean program

10 tanks for reagents

S11 3 baths for wax paraffin

2 tanks with cleaning solution

1 condensation tanks

S18 1 carbon filter bottle



2. Technical features

2.1 Technical Data

Certification: CE, IVD
Protection class: I
Fuses type Fst: 10 A
Pollution class: 2
Over-voltage Category II Installation
Power supply: 220V ~ 50Hz
110V ~ 60Hz
Relative humidity: 10 to 80%
Maximum power draw: 1500 V/A
UPS: (Optional)

S23

2.2 Paraffin stations

S15, S16

Number of paraffin baths: 3
Volume (in liters): 4.0 lt. / Each tank
Melting time: Approx. 3 hours
Temperature: 65 °C
Temperature accuracy: + 1 °C

2.3 Process chamber

Capacity: approx. 300 cassettes, contained in a stainless steel drum to 3 floors with two separators and closing top cover

S12

Reagent volume: 6.1 Lt
Temperature (paraffin): 50°C - 65°C

S17

Temperature (reagents): ambient or 35°C
Temperature (cleaning reagents): 50°C - 65°C

Temperature accuracy: + 1°C
Filling time: up to 5 min
Drain time: up to 5 min
Impregnation vacuum: -70 kPa (g)
Impregnation pressure: 35 kPa (g)
Fill vacuum: -70 kPa (g)
Drain pressure: 35 kPa (g)