

## Table Top Low Speed Centrifuge



### Introduction:

BKC-TL4C centrifuge is a desktop low-speed centrifuge, suitable for the separation of blood samples in hospital laboratories, laboratories, beauty salons, dental hospitals, etc.

### Features:

- \* Small size, safe and reliable, easy to use.
- \* Adjustable acceleration levels: 10, deceleration levels: 10.
- \* The fuselage is made of high-quality plastic mold material, with explosion-proof protection.
- \* Adopt DC brushless motor, stable operation, small vibration and low noise.
- \* The button-type programming design can display the running parameters in real time, and the operation is more intuitive.
- \* Centrifugal speed, time, and elevating speed can be set freely, and centrifugal force can be checked at any time.
- \* Ultra-low noise, microcomputer control, intelligent interface, fault display, door cover, overspeed and other automatic protection functions.

### Technical Parameters:

Model	BKC-TL4C
Max. Speed	4000rpm
Max. RCF	1880xg
Max. Capacity	8*20ml
Speed Precision	±10rpm
Time Range	1s~99min59s
Power Supply	AC 100~240V, 50/60Hz
Consumption	250W
Noise	≤55dB
External Size(L*W*H)mm	310*270*210
Package Size(L*W*H)mm	370*310*250
Net Weight/Gross Weight(kg)	7.5/8.5

### Rotor:

No.	Rotor	Capacity	Max. Speed(rpm)	Max. RCF(xg)
No.1	Angle Rotor	6*10/15ml	4000	1880
No.2		8*10/15ml		1880
No.3		8*20ml		1840
No.4		12*5ml		1540
No.5		12*7/10ml		1790

## Table Top Low Speed Centrifuge



### Introduction:

BKC-TL4X blood bank special automatic balancing centrifuge is a special centrifuge designed to meet the needs of rapid centrifugation in blood banks.

### Features:

- \* Microcomputer processor control, OLED real-time display of all operating parameters.
- \* Adjustable acceleration levels: 10, deceleration levels: 10.
- \* Brushless DC motor, no dust pollution, maintenance free.
- \* Unique ventilation and cooling design: when the rotation speed is less than 4000r/min for a long time, the sample is only raised by 5 degrees Celsius.
- \* 20 sets of centrifugation programs can be stored.
- \* Safety door lock, over temperature protection, unbalance detection function.
- \* Humanized operation interface, concise and clear, easy to operate.

### Technical Parameters:

Model	BKC-TL4X
Max. Speed	4000rpm
Max. RCF	2250xg
Max. Capacity	24*10ml
Speed Precision	±20rpm
Time Range	1s~999min
Power Supply	AC220V, 50/60Hz(Standard); 110V, 60Hz (Optional)
Consumption	200W
Noise	≤65dB
External Size(L*W*H) mm	350*400*270
Package Size(L*W*H) mm	410*510*310
Net Weight/Gross Weight(kg)	18/20

### Rotor:

No.	Rotor	Capacity	Max. Speed(rpm)	Max. RCF(xg)
No.1	Angle Rotor	12*15ml	4000	2200
No.2		24*10ml		2250