HIGH VACUUM, HIGH FLOW HOSPITAL SUCTION ASPIRATORS



Designed for professional aspiration of bodily fluids, tissues or bones of patients during or after surgery.

Oiless and maintenance free piston type pumps provide high performances. Excellent suction capacities and max vacuum built up within a few seconds. Available with vacuum gauge and autoclavable jars made in Makrolon® with 200 ml (2 l jar) or 500 ml (4 or 5 l jars) graduation and 2-3 litres Flovac jars with disposable liners.

Wide range of versions with different features

CLINIC PLUS

- 60 l/m (Clinic Plus) or 90 l/m (Hospi Plus) flow rate;
- 2, 4 or 5 l jars;
- MPR system for versatility;
- footswitch and flow direction diverter.



Clinic Plus Basic and Hospi Plus Basic



Clinic Plus Full and Hospi Plus Full with foot switch and electronic flow direction

HOSPI PLUS

Customized Hospi Plus MPR with 1x2 | jar, 1x5 | jar and safety trap Multipurpose stainless steel rail for maximum versatility allows to hang any accessory. Suitable for MPR models only 28154. 28155. 28156 and HOSPI PLUS MPR Rings for: 2 or 5 I autoclavable jars, 4 antistatic castors with brake High standards of safety in overflow protection system

MPR SYSTEM

Multi purpose rai

Double security valve integrated in the jar and hydrophobic filter (all models), safety trap bottle (only MPR models).

MPR (Multi Purpose Rail) models

This system enhances the versatility for easy and quick exchange of different accessories, with no need for tools. Equipped with five connections for rings of various diameters to fit jars of different sizes and types (2I, 3I, 5I), cannula holders and safety trap bottle.

EMERGENCY DEPT. **GENERAL SURGERY**

MAIN APPLICATIONS GYNAFCOLOGY NEUROSURGERY **OBSTETRICS**

OPERATING THEATRE DENTAL PRACTICE



Multipurpose rail with 5 locking slots offers versatility to operators in changing accessories

	Operating voltage: Maximum suction: Operating cycle: Flow: Power: Noise level: Norms:	230 V - 50/60 Hz or 110 V - 60 - 0,90 bar (675 mmHg) continuous 60 l/min 230 VA 51.7 dBA EN 60601-1-1, EN 60601-1-2 93/42 EEC		230 V - 1 - 0.90 ba continu 90 l/min 385 VA 46.4 dBA EN 6060 93/42 EE	ar (675 ous A)1-1-1, [mmHg)		HZ
121°C autoclavable jar with overflow valve system (2, 4 or 5 l) Rings to accommodate 5 l jars Safety Trap Bottle (220 ml) Antibacterial & Hydrophobic Filter (single-patient) Autoclavable silicone tubes Ø 8x14 mm length 150 cm Conical Connector Ø 10-11-12mm Air suction inlet Footswitch with intermittent or continuous operation Change-Over System from jar to jar by soft-touch keys Power Cord with Schuko plug Multilingual manual: GB, FR, IT, ES, DE, GR, PL, RO			Clinic,	S and H Clinic, Hospi full 2 - - 1 1 1 1 1 1 1	Clinic	Clinic	Hospi basic MPR 2 2 1 2 2 2 2 2 -	Hospi full MPR 2 2 2 2 2 2 2 1 1 1

TECHNICAL SPECIFICATIONS

Volt	tage	SUCTION ASPIRATORS	Autocla- vable	Foot	Flow direction
230 V	110 V	CLINIC and HOSPI PLUS	Jars	switch	diverter*
28194	28118	CLINIC Basic	2x2 l	-	-
28195	-	CLINIC Full	2x2 l	yes	yes
28196	-	CLINIC Basic	2x4 l	-	-
28198	28119**	CLINIC Full	2x4 l	yes	yes
28159	-	CLINIC Basic MPR	2x5 l	-	-
28160	-	CLINIC Full MPR	2x5 l	yes	yes
28200	-	HOSPI Basic	2x2 l	-	-
28203	-	HOSPI Full	2x2 l	yes	yes
28201	-	HOSPI Basic	2x4 l	-	-
28204	28120**	HOSPI Full	2x4 l	yes	yes
28161	-	HOSPI Basic MPR	2x5 l	-	-
28162	-	HOSPI Full MPR	2x5 l	yes	yes
*Allows to direct suctioned liquids to any of the 2 jars **with 2x5 Liars					x5 Liars

,	ions to uncersuctioned inquias to any or the 2 juis	
GIMA code	ACCESSORIES FOR CLINIC/HOSPI PLUS MPR	
28150	Safety trap bottle 220 ml - spare	
	Multipurpose stainless steel rail - optional	
28154	Ring for 2 I autoclavable jar - optional	
28155	Ring for 5 I autoclavable jar - spare	
28156	Ring for 2 or 3 Flovac jar - optional	