



M60 MINI LOADER TECHNICAL SPECIFICATIONS



GENERAL

BUCKET CAPACITY	0.35 M ³
RATED LOADING CAPACITY	950-1200* KG
OPERATING WEIGHT	2900-3200* KG
TIPPING LOAD	1900-2400* KG
BREAKOUT FORCE	2070 KG
DIESEL ENGINE	KUBOTA V2403-M-T (STAGE 3A)
RATED OUTPUT	60HP-44 kW @ 2700RPM
CYLINDER	4
COOLING SYSTEM	LIQUID
BREAKS	HYDRASTATIC BRAKE SYSTEM (SAHR)
TIRES STANDARD	10 × 16,5
BATTERY	12V - 105A
SPEED	0-12km/h
DRIVE & BOOM & BUCKET CONTROL	JOYSTICK (HYDRAULIC)

*: with counterweight option

HYDRAULIC SYSTEM (BOSCH REXTROTH)

HYDRAULIC PRESSURE	220 bar
HYDRAULIC OIL FLOW	78 lt/min

CAPACITIES

FUEL TANK	56 lt
HYDRAULIC OIL	56 lt

DIMENSIONS

WIDTH OVER BUCKET	1607 mm
WIDTH OVER CHASSIS	1230 mm
LENGTH WITH BUCKET	3330 mm
MAX. DUMP HEIGHT	2165 mm
HINGE PIN HEIGHT AT MAX. LIFT	3000 mm
MAX. HEIGHT	3900 mm
HEIGHT TO TOP OF CAB	1940 mm

