

BIOMAG®

Products

(3)

Biomag® Lumina 1,34 kg

Description: EASY, battery incl., outputs 3/1, 3D programs 1, 2, 31, 32, belt PL5, tester, power cord 1,5m, including user manual

Description: CLINIC, battery incl., outputs 3/1, 108 3D programs, belt PL5, tester, power cord 3m, including user manual



Biomag® Lumina 1,20 kg

Description: EASY, battery excl., outputs 3/1, 3D programs 1, 2, 31, 32, belt PL5, tester, power cord 1,5m, user manual

Description: CLINIC, battery excl., outputs 3/1, 108 3D programs, belt PL5, tester, power cord 3m, user manual



Biomag® Lumio 0,56 kg

Description: QUATRO, 4 programs, tester, user manual, cardboard case, power adapter



Biomag® LightFit 0,60 kg

Description: UNO, 3 programs, user manual, tester, power adapter

Description: DUO, 3 programs, user manual, tester, power adapter

J biomag[®] BIOMAG MEDICAL S.R.O. PRŮMYSLOVÁ 1 270 506 01 JIČÍN

L8319 AL79-2C-COMBI 1,40 kg



Two-piece applicator with alternating activation of its parts, with an opening for combined application and for fixation suitable for Biomag® Lumina, Lumio

Parameters: wide. 430 mm, length. 790 mm, high. 28 mm, MIMP 4 mT, weight 1,4 kg

L8314 AL80

1,55 kg



Three-piece applicator which allows fixation, suitable for Biomag® Lumina, Lumio, **LightFit DUO**

Parameters: wide. 380 mm, length. 800 mm, high. 34 mm, MIMP 3,5 mT, weight 1,55 kg

L8312 AL95-2C

1,80 kg



Two-piece applicator with alternating with alternating activation of its part, suitable for Biomag® Lumina, Lumio, LightFit DUO

Parameters: wide. 460 mm, length. 950 mm, high. 34 mm, MIMP 4 mT, weight 1,8 kg

L8315 AL96-2C

3,58 kg



Two-piece applicator with alternating with alternating activation of its part, suitable for Biomag® Lumio

Parameters: wide. 460 mm, length. 960 mm, high. 34 mm, MIMP 20 mT, weight 3,58 kg

L8326 AL115-3D

2,10 ka



Three-piece applicator with 3D pulses and openings for combined applications, suitable for Biomag® Lumina

Parameters: wide. 430 mm, length. 1 150 mm, high. 28 mm, MIMP 4 mT, weight 2,1 kg

L8320 AL115-3D-COMBI



Three-piece applicator with 3D pulses and openings for combined applications, allowing connection into a closed shape for rotary applications and following fixation, suitable for **Biomag® Lumina**

Parameters: wide. 430 mm, length. 1 150 mm, high. 28 mm, MIMP 4 mT, weight 2,1 kg

L8310 AL135



Three-piece applicator, suitable for Biomag® Lumina, Lumio, LightFit DUO

Parameters: wide. 460 mm, length. 1 350 mm, high. 25 mm, MIMP 1,2 mT, weight 1,9 kg

biomag°
BIOMAG MEDICAL S.R.O.
PRŮMYSLOVÁ 1 270
506 01 JIČÍN

<u> Applicator - solenoid</u>

L8401 SL19

1,25 kg



Flexible solenoid, suitable for Biomag® Lumina, Lumio, LightFit DUO

Parameters: Ø 190 mm, length. 310 mm, MIMP 3 mT, weight 1,25 kg

L8408 SL20-3D

2,00 kg



Solenoid with 3D field for rotary applications Ø 20cm, suitable for Biomag® Lumina

Parameters: Ø 200 mm, length. 140 mm, MIMP 16 mT, weight 2 kg

L8402 SL29

1,30 kg



Oval solenoid, suitable for Biomag® Lumina, Lumio, LightFit DUO

Parameters: Ø 290 mm, length. 80 mm, MIMP 4 mT, weight 1,3 kg

L8403 SL30-P

2,55 kg



Solenoid with flat bottom Biomag® Lumina, Lumio, LightFit DUO

Parameters: Ø 300 mm, length. 170 mm, MIMP 5 mT, weight 2,55 kg

L8409 SL30-3D

3,50 kg



Solenoid with 3D field for rotary applications, suitable for Biomag® Lumina

Parameters: Ø 300 mm, length. 340 mm, MIMP 4 mT, weight 3,5 kg

L8404 SL45-P

2 95 kg



Solenoid with flat bottom, suitable for Biomag® Lumina, Lumio, LightFit DUO

Parameters: Ø 450 mm, length. 120 mm, MIMP 2 mT, weight 2,95 kg

L8405 SL50-P

8,75 kg



Solenoid with flat bottom, suitable for Biomag® Lumina, Lumio, LightFit DUO

Parameters: Ø 500 mm, length. 340 mm, MIMP 1,5 mT, weight 8,75 kg

L8406 SL60-P

12,20 kg



Solenoid with flat bottom, suitable for Biomag® Lumina

Parameters: Ø 600 mm, length. 340 mm, MIMP 1,5 mT, weight 12,2 kg

L8407 SL70

13,35 kg



Solenoid designed for attachment to an adjustable table, suitable for Biomag® Lumina

Parameters: Ø 700 mm, length. 300 mm, MIMP 2 mT, weight 13,35 kg