

Technical specification

Brazed Plate Heat Exchanger



Project ref: TERMOELECTRICA SA -CHISINAU
 Line ref:
 Model: CB110-36M
 Item Id: n/a
 No of units: 1

Page: 1(2)
 Date: 2023-04-12

		Hot side S1 -> T1	Cold Side T4 -> S4
Process data			
Capacity:	kW	255.0	
Fluid:		Water	Water
Duty type:		Liquid cooling	Liquid heating
Volume flow rate:	m ³ /h	5,60	4,88
Inlet temperature:	°C	62,0	10,0
Outlet temperature:	°C	22,0	55,0
Total pressure drop calculated (allowed)	kPa	19,3 (20,00)	17,6 (20,00)
Velocity connections:	m/s	0,94	0,83

Heat exchanger specification			
Relative directions of fluids:		Countercurrent	
Number of plates:		36	
Channel volume:	dm ³	3,8	3,6
Number of circuits:		1	1
Design pressure at -196 °C	bar	30	30
Design pressure at 225 °C	bar	25	25
Design temperature (min/max):	°C	-196 / 225	
Pressure vessel code:		PED	
Material Channel plates / Sealing:		ALLOY 316 / Cu	
Additional connections:		S2, S3, T2	
Connection S1 (Hot-In):		Threaded (External) 2" ALLOY 316	
Connection T1 (Hot-Out):		Threaded (External) 2" ALLOY 316	
Connection T4 (Cold-In):		Threaded (External) NPT 2" ALLOY 316	
Connection S4 (Cold-Out):		Threaded (External) 2" ALLOY 316	
Additional connection S2:		Threaded (External) / 2"ISO 228/1-GB23	
Additional connection S3:		Threaded (External) / 2"ISO 228/1-GB23	
Additional connection T2:		Threaded (External) / 2"ISO 228/1-GB23	
Unit dimensions (length x width x height):	mm	193 x 191 x 616	
Net weight, empty / operating:	kg	20,0 / 27,33	
Packed length x width x height:	mm	0 x 0 x 0	
Packed weight:	kg	20	

The performance of the equipment is conditioned by the process media and process parameters being consistent with the provided customer data. Data, specifications, and other kind of information of technological nature set out in this document and submitted by Alfa Laval to you (Proprietary Information) are intellectual proprietary rights of Alfa Laval. The Proprietary Information shall remain the exclusive property of Alfa Laval and shall only be used for the purpose of evaluating Alfa Laval's quotation. The Proprietary Information may not, without the written consent of Alfa Laval, be used or copied, reproduced, transmitted or communicated or disclosed in any other way to a third party.

Technical specification

Brazed Plate Heat Exchanger



Project ref: TERMOELECTRICA SA -CHISINAU
Line ref:
Model: CB110-36M
Item Id: n/a
No of units: 1

Page: 2(2)
Date: 2023-04-12

Fluid properties		Hot side	Cold Side
Density (in/out):	kg/m ³	981,20/996,87	999,98/984,53
Specific heat capacity:	kJ/(kg·K)	4,18	4,19
Thermal conductivity:	W/(m·K)	0,630	0,617
Viscosity (in/out):	cP	0,4515/0,9601	1,3112/0,5031

The performance of the equipment is conditioned by the process media and process parameters being consistent with the provided customer data. Data, specifications, and other kind of information of technological nature set out in this document and submitted by Alfa Laval to you (Proprietary Information) are intellectual proprietary rights of Alfa Laval. The Proprietary Information shall remain the exclusive property of Alfa Laval and shall only be used for the purpose of evaluating Alfa Laval's quotation. The Proprietary Information may not, without the written consent of Alfa Laval, be used or copied, reproduced, transmitted or communicated or disclosed in any other way to a third party.