



Ducted Fume Hood



LED Display
Digital LED display:
Airflow Level



**Waterproof
Socket**



Universal Wheel



**Water Remote
Control**



Water Tap



**Water Tap &
Water Sink**

ADVANTAGE

1. Adjustable air speed: 9 levels.
2. Microprocessor control system, LED display.
3. Resistant to moderate acid and alkali.
4. With memory function in case of power-failure.
5. Manual front glass window, height adjustable.
6. Built-in PP centrifugal blower; low noise, easy installation.

TECHNICAL PARAMETERS

Model	FH1000(E)	FH1200(E)	FH1500(E)	FH1800(E)
External Size(W*D*H)	1000*800*2515mm	1200*800*2515mm	1500*800*2515mm	1800*800*2515mm
Internal Size(W*D*H)	790*600*870mm	990 *600*870mm	1290*600*870mm	1590*600*870mm
Work Surface Height	900mm			
Max Opening	750mm			
Air Velocity	0.3~0.8m/s			
System Exhaust Volume	570 m³/h	710 m³/h	930 m³/h	1140 m³/h
Noise	≤68dB			
Exhaust Duct	PVC,Standard length; 5 meters,Φ300mm			
Pipe Strap	2 pcs			
LED Lamp	20W *1		40W *1	
Blower	Built-in PP centrifugal blower			
Front Window	Manual, 5mm toughened glass, height adjustable			
Power Supply	220V±10%, 50/50Hz; 110V±10%, 60Hz			
Consumption	400W	400W	500W	500W
Material	Exterior	1.0mm cold-rolled steel with anti-bacterial powder coating		
	Interior	Compact laminate board with good acid and alkali resistance function		
	Work table	Chemical resistant phenolic resin		
Standard Accessory	PP Water sink, Total load of 2 waterproof sockets: 500w, Base cabinet, Water tap, 5 meters Exhaust duct(Φ300mm).			
Optional Accessory	Air supply flow control valve, gas faucet.			
Gross Weight	270kg	305kg	335kg	365kg
Package	Main Body	1140*940*1900mm	1340*940*1900mm	1640*940*1900mm
	Base Cabinet	1140*940*1050mm	1340*940*1050mm	1640*940*1050mm