

PRACTICO ELECTRO-MECHANICAL

Modular choice for general surgical procedures

Practico, the electro-mechanical, mobile operating table represents convenient design and maximum flexibility for general surgery.

Its modular construction with a wide range of posture possibilities offers comfort and operational efficiency for the whole surgical team. Therefore it is also a popular choice for day surgery clinics, where patient flow is crucial. With the comprehensive selection of accessories the table can be adjusted to meet most requirements for different surgical procedures.

Practico is available with standard table top/basic model, 300 mm sliding table top, Beach Chair back section or Kidney Bridge seat/back section. Safe working load (SWL) is 225 kg, max. lifting capacity 380 kg.

Not available for EU deliveries after 26th of May 2021.





Practico operating table features

- Electro-mechanical, mobile surgical table
- Removable table top sections and wide range of accessories enable fast and easy set up for different surgical procedures
- X-ray translucent table top panels
- Battery operated table with integrated charger/transformer, optional main power use
- Optional floor lock system to enhance the stability for demanding procedures
- Lightweight table top sections with quick release offer improved ergonomics for nurses
- The convenient design of the base together with the sliding function guarantees unlimited access for the surgeon to the patient
- Patented Beach Chair back section is extremely easy and lightweight in use and offers better comfort for the patient in semi-seated position
- Comfortable and soft, moulded IS-mattress, 65 mm or visco-elastic memory foam (VEF) 80 mm mattress
- Base cover either stainless steel or ABS

Title	Standard	Slide
Length	2090 mm	2090 mm
Width (table top)	540 mm	540 mm
Height adjustment	595 - 895 mm	665 - 965 mm
Safe working load (SWL)	225 kg	225 kg
Trendelenburg	-26 °	-26 °
Reverse Trendelenburg	+26 °	+26 °
Head rest adjustment	-45 - +45 °	-45 - +45 °
Back section adjustment	-15 - +70 °	-40 - +70 °
Leg section adjustment	-90 - +20 °	-90 - +20 °
Castors size	125	125
Secondary voltage	36 V	36 V
Frequency	50 - 60 Hz	50 - 60 Hz
Weight	195 kg	205 kg
Longitudinal shift of the table top		300 mm
Lateral tilt	-20 - +20 °	-20 - +20 °
Max. lifting capacity	380 kg	380 kg
Product Code	100030000	100030000