



DVB-T2 H.265 HD Receiver

HDT2-1254



General

Model Name	HDT2-1254
Marketing Area	Europe
Transponder	DVB-T2
Power Voltage	AC 100-240V~ 50/60Hz
Power adapter	DC 5V/1A
Power Consumption	<6W
Standby Power Consumption	<1W

System

Main Processor	Ali M3822P
DDR II	512Mbit
FLASH Size	32Mbit

Decode

	MPEG-2 MP@HL,HEVC/H.265
	AVC/H.264
Video decoder	MPEG-4 SP@L3 to ASP@L5,Xvid,VC1,VP8
Audio decoder	AAC/AC3/PCM
Video output ratio	4:3/16:9/Auto
Video resolution	1920*1080

Feature

DVB-T2 Standard	ETSI EN302755/ V1.3.1
OSD language	Multi language
Media playback	Yes
Record through USB HDD	Yes
Timeshift through USB HDD	Yes
7 days EPG (Electronic Program Guide)	Yes
DVB subtitle	Yes
Teletext	Yes
Easy first installation	Yes
Channel search with automatic / manual	Yes
TV and radio list handling	Yes
Favorite list editing for both radio and TV	Yes
Parental lock	Yes
Aspect ratio handling	Yes
Timer setting	Yes
LCN	Yes
Copy protection	HDMI 1.4a/HDCP 1.2
Software upgrade	USB/OTA

Tuner & Channel

Demod/Tuner Type	MXL608
RF Input Connector	IEC FEMALE
Receiving Channel Range	174~230MHz, 470~862MHz
Modulation	QPSK/16QAM/64QAM/256QAM
Code Rates	1/2,3/5,2/3,3/4,4/5,5/6,7/8
Band Width	6/7/8MHz
FFT Size	1k,2k,4k,8k,16k,32k
Guard Intervals	1/128,1/32,1/16,19/256,1/8,19/128,1/4

Terminal

HDMI	Yes
RF IN	Yes
RF OUT	Yes
DC IN	Yes
USB 2.0	Yes
SCART	Yes

Front panel

Display Type	Optional
Front panel keyboard	3
USB2.0	Yes
Infra-red receiver	Yes
Power indicator (LED)	Yes

Accessory

Remote control with battery	Yes
HDMI Cable	Optional
IB and Warranty Card	Yes

Dimensions

Body size	125*91*29mm
Packing size	mm
Net weight	Kg
QTY/CT	pcs
Container data	
20"(6000x2350x2380)	pcs
40"(12000x2350x2380)	pcs
40"HQ(12000*2350*2700)	pcs