

**Specificații tehnice**

[Acest tabel va fi completat de către **ofertant în coloanele 2, 3, 4, 6, 7**, iar de către autoritatea contractantă – în coloanele 1, 5]

<b>Numărul procedurii de achiziție:</b> Informația o găsiți în SIA RSAP.
<b>Obiectul achiziției:</b> Echipament de radioteleviziune (repetat)

Denumirea bunurilor/ serviciilor	Denumirea modelului bunului/ serviciului	Țara de origine	Producă torul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standar de de referință
1	2	3	4	5	6	7
<b>Bunuri/servicii</b>						
<b>Echipament de radioteleviziune (repetat)</b>						
<b>Lotul nr. 1</b>						
1.1. Camera PTZ	AW-UE160KEJ	China	Panasonic	Camera PTZ 4K 1” Type 9.6MP MOS Sensor Up to UHD 4K60 & 1080 Simultaneous Out 12G-SDI, HDMI, Fiber & IP Transmission Improved Phase-Detection Autofocus 20x Optical Zoom, 2x High-Speed Capture HDR Mode with HLG/BT.2020 Compatibility Wide 75.1° Horizontal Viewing Angle Up to 180°/Sec Pan/Tilt Speed Live Stream to Platforms via RTMP 2 x XLR Audio In, Front/Rear Tally Lamps Include 12v power supply 4-pin XLR connection	Camera PTZ 4K 1” Type 9.6MP MOS Sensor UHD 4K60 & 1080 Simultaneous Out 12G-SDI, HDMI, Fiber & IP Transmission Improved Phase-Detection Autofocus 20x Optical Zoom, 2x High-Speed Capture HDR Mode with HLG/BT.2020 Compatibility Wide 75.1° Horizontal Viewing Angle Up to 180°/Sec Pan/Tilt Speed Live Stream to Platforms via RTMP 2 x XLR Audio In, Front/Rear Tally Lamps Include 12v power supply 4-pin XLR connection	
1.2. Tripod	VX-18M	China	Viltrox	<b>Tripod + Fluid Head + Quick Release Plate + Pan Handle</b> Load Capacity: 5.99 kg	Tripod - Tripod + Fluid Head + Quick Release Plate + Pan Handle Load Capacity: 5.99 kg	

				<p>Maximum Working Height: 1.88 m  Minimum Working Height: 0.84 m  Folded Length: 89.92 cm  Materials: Aluminum  Versatile -75°to +90° tilt range and 360° pan range  Separate pan/tilt locks and built-in bubble level indicator for aligning the horizon line Sliding QR plate features 1/4"-20 top mounting screw and spare 3/8" screw  Interchangeable pan bar handle with angular adjustment that fits on either the left or right side of the head.  Three-section leg design with mid-level spreader and adjustable height</p>	<p>Maximum Working Height: 1.88 m  Minimum Working Height: 0.84 m  Folded Length: 89.92 cm  Materials: Aluminum  Versatile -75°to +90° tilt range and 360° pan range  Separate pan/tilt locks and built-in bubble level indicator for aligning the horizon line Sliding QR plate features 1/4"-20 top mounting screw and spare 3/8" screw  Interchangeable pan bar handle with angular adjustment that fits on either the left or right side of the head. Three-section leg design with mid-level spreader and adjustable height</p>	
<b>1.3. SDI Cable</b>	<b>VD083LP</b>	<b>Germany</b>	<b>Klotz</b>	<p>HD-SDI – high-flex video cable 0.8L/3.7  -inner conductor  – stranded bare copper, 19 x 0.16 mm  -insulation – gas injected foam PE, Ø 3.7 mm  -shielding - 2x tinned copper braid, &gt;95% coverage -outer jacket – PUR  -overall diameter – 6.1 mm  -min. bending radius – installation: 40 mm, operation: 60 mm  -characteristic impedance – 75 Ω ± 1%  -suitable for mobile HD-SDI use</p>	<p>HD-SDI – high-flex video cable 0.8L/3.7  -inner conductor – stranded bare copper, 19 x 0.16 mm  -insulation – gas injected foam PE, Ø 3.7 mm  -shielding - 2x tinned copper braid, &gt;95% coverage -outer jacket – PUR - overall diameter – 6.1 mm -min. bending radius – installation: 40 mm, operation: 60 mm - characteristic impedance – 75 Ω ± 1% -suitable for mobile HD-SDI use</p>	
<b>1.4. BNC connector</b>	<b>NBNC75BLP9</b>	<b>Liechtenstein</b>	<b>Neutrik</b>	<p>BNC Connector:  -Compatible for HD-SDI digital video cable at position nr. 1.3 (NBNC75BLP9)</p>	<p>BNC Connector: -Compatible for HD-SDI digital video cable at position nr. 1.3 (NBNC75BLP9)</p>	

1.5. Instalare				Materiale și elemente pasive/active necesare pentru interconectarea echipamentelor și punerea în funcțiune a acestora; Lucrările de montare, precum și operațiunile de instalare, ajustare; Sistemul va fi predat la cheie; Garanția hardware minim 3 ani.	Materiale și elemente pasive/active necesare pentru interconectarea echipamentelor și punerea în funcțiune a acestora; Lucrările de montare, precum și operațiunile de instalare, ajustare; Sistemul va fi predat la cheie; Garanția hardware minim 3 ani.	
----------------	--	--	--	--	--	--

Semnat: \_\_\_\_\_

Numele, Prenumele: Stînca Gheorghe

În calitate de: Administrator

Ofertantul: "ELECTROMECH ENGINEERING" SRL

Adresa: mun.Chișinău, str.Voluntarilor, 18/1, ap (of) 38