



## MICARE POWERLED

- Aluminum Lamp Housing
- High Color Rendering Index
- Uniform And Round Focus
- Life Time:  $\geq 50,000$ hrs
- Safety Explosion-Proof

## BRILLIANT BY DESIGN

The MICARE PowerLED Surgical Lighting System Provides Meaningful, Clinician-Inspired Advances To Keep Up With Life In Today's OR.

Through Thoughtful Innovation, This Future-Ready System Offers Superior Optical Performance, Laminar Airflow Design

## Full Intergration To The OR Environment From Conventional To Theatre Rooms

MICARE PowerLED ensures the clearest and brightest light for surgeons, without distractions from glare.

Allows equipment to be positioned within reach of the surgeon, concealing wires and cables to improve safety and hygiene. Equipment can be easily added, removed and upgraded to meet future requirements.

Thanks to MICARE Power LED High-quality illumination helps to relieve strain, Comfort Light feature, improves visual performance, reduces the sensation of glare and increases the feeling of wakefulness leading to a better working environment



# Micare PowerLED 700/500

## Evolving Design, Revolutionary Features

Near Perfect Colour Rendition with white and yellow LEDS mix  
For the best visualisation of tissue during surgery.

Widely Beam Technology From 15CM-35CM  
The largest light beams of any current product with high intensity across the full beam width.

Unique Comfort  
A soft illumination of light to reduce eye strain from high contrasts of light intensity.



Designed to Minimise Infections  
Easy to clean, sealed light head, remote controls and anti-microbial coatings.

HDI-SDI Camera Optional, Integrated cameras are fully enclosed inside the light head, records for risk, management, and optimize understanding and learning.

Maximum illumination up to 180,000 lux  
Stable and constant illumination  
Enhanced visibility, diagnosis and treatment



Endoscopy Mode In Deep Illumination For Various Operation Enviromental



Astro Space Design, Working seamlessly with laminar airflow solutions



Removable Sterilizaer Handle Can Be Easily For Internal Camera



5.1 INCHES LCD Touch Panel Optional (OEM With LOGO Print Available)





MICARE PowerLED Model	E700/700	E700/500	E500/500
Voltage	95~245V, 50/60HZ	95~245V, 50/60HZ	95~245V, 50/60HZ
Illuminance at distance of 1 m(LUX)	93,000-180,000/93,000-180,000	93,000-180,000/83,000-160,000	83,000-160,000/83,000-160,000
Brightness Adjustable	0-100%	0-100%	0-100%
Lamp Head Diameter	700MM/700MM	700MM/500MM	500MM/500MM
Quantity Of LEDS	80PCS/80PCS	80PCS/48PCS	48PCS/48PCS
Color Temperature Adjustable	3000-5500K	3000-5500K	3000-5500K
Color rendering index Ra	96	96	96
Color rendering index R9(Red)	98	98	98
Light Field Size Adjustable	150-350MM/150-350MM	150-350MM/90-260MM	90-260MM/90-260MM
Total radiant flux density	364W/m2	364W/m2	364W/m2
Endoscopy Mode	YES	YES	YES
Endoscopy Mode LEDS	8PCS/8PCS	8PCS/8PCS	8PCS/8PCS
Illumination For Endo-Mode	10%	15%	18%
LED service life	80,000hrs	80,000hrs	80,000hrs
Main Material	Aluminum	Aluminum	Aluminum
Rotating Angle Of Arm	>540&deg;	>540&deg;	>540&deg;
LED Bulb Power	1w Each Pc	1w Each Pc	1w Each Pc
Input Power	400w	400w	400w
Operating element	Touch Control	Touch Control	Touch Control
Light head protection rating	IP54+FireProof	IP54+FireProof	IP54+FireProof
Depth of illumination L1+12	1400MM	1200MM	1100MM
Lamp weight	700+700=52KGS	700+500=49KGS	500+500=46KGS
Packing	3 Wooden Cartons	3 Wooden Cartons	3 Wooden Cartons
LCD Touch Screen	Optional	Optional	Optional
Back Up Battery (4-6hrs)	Optional	Optional	Optional
Shadow Compensation Function	Optional	Optional	Optional
Internal/External Sony Camera(10X)	Optional	Optional	Optional
Monitor With Extra Arm(21 Inches)	Optional	Optional	Optional
Wall Mounted Control)	Optional	Optional	Optional

MICARE PowerLED Model	E700	E500
Voltage	95~245V, 50/60HZ	95~245V, 50/60HZ
Illuminance at distance of 1 m(LUX)	93,000-180,000	83,000-160,000
Brightness Adjustable	0-100%	0-100%
Lamp Head Diameter	700MM	500MM
Quantity Of LEDS	80PCS	48PCS
Color Temperature Adjustable	3000-5500K	3000-5500K
Color rendering index Ra	96	96
Color rendering index R9(Red)	98	98
Light Field Size Adjustable	150-350MM	90-260MM
Total radiant flux density	364W/m2	364W/m2
Endoscopy Mode	YES	YES
Endoscopy Mode LEDS	8PCS	8PCS
Illumination For Endo-Mode	10%	18%
LED service life	80,000hrs	80,000hrs
Main Material	Aluminum	Aluminum
Rotating Angle Of Arm	>540&deg;	>540&deg;
LED Bulb Power	1w Each Pc	1w Each Pc
Input Power	400w	400w
Operating element	Touch Control	Touch Control
Light head protection rating	IP54+FireProof	IP54+FireProof
Depth of illumination L1+12	1400MM	1100MM
Lamp weight	700+700=52KGS	500+500=46KGS
Packing	3 Wooden Cartons	3 Wooden Cartons
LCD Touch Screen	Optional	Optional
Back Up Battery (4-6hrs)	Optional	Optional
Shadow Compensation Function	Optional	Optional
Internal/External Sony Camera(10X)	Optional	Optional
Monitor With Extra Arm(21 Inches)	Optional	Optional
Wall Mounted Control)	Optional	Optional







MICARE PowerLED Model	E700L(Battery Optional)	E500L(Battery Optional)
Voltage	95~245V, 50/60HZ	95~245V, 50/60HZ
Illuminance at distance of 1 m(LUX)	93,000-180,000	83,000-160,000
Brightness Adjustable	0-100%	0-100%
Lamp Head Diameter	700MM	500MM
Quantity Of LEDS	80PCS	48PCS
Color Temperature Adjustable	3000-5500K	3000-5500K
Color rendering index Ra	96	96
Color rendering index R9(Red)	98	98
Light Field Size Adjustable	150-350MM	90-260MM
Total radiant flux density	364W/m <sup>2</sup>	364W/m <sup>2</sup>
Endoscopy Mode	YES	YES
Endoscopy Mode LEDS	8PCS	8PCS
Illumination For Endo-Mode	10%	18%
LED service life	80,000hrs	80,000hrs
Main Material	Aluminum	Aluminum
Rotating Angle Of Arm	>540&deg;	>540&deg;
LED Bulb Power	1w Each Pc	1w Each Pc
Input Power	400w	400w
Operating element	Touch Control	Touch Control
Light head protection rating	IP54+FireProof	IP54+FireProof
Depth of illumination L1+12	1400MM	1100MM
Lamp weight	700+700=52KGS	500+500=46KGS
Packing	3 Wooden Cartons	3 Wooden Cartons
LCD Touch Screen	Optional	Optional
Back Up Battery (4-6hrs)	Optional	Optional
Shadow Compensation Function	Optional	Optional
Internal/External Sony Camera(10X)	Optional	Optional
Monitor With Extra Arm(21 Inches)	Optional	Optional
Wall Mounted Control)	Optional	Optional



## Redefine optical performance Aerospace-based design

How can you deliver more clean airflow to your patient during a surgical procedure? The Osram Power LED allows unobstructed flow of clean air through the lighthead to dissipate accumulated heat and surgical smoke. Working seamlessly with laminar airflow solutions, it decreases air turbulence through its unique airfoil design. Aerospace-based design, We've learned from the best in the aerospace industry for a design that mitigates airflow turbulence while delivering clean air to the patient.

Lightweight aluminum construction  
The suspension weights approximately  
**30%** less than previous generations  
of steel arms.



# Micare Power LED E700/500 CAMERA AND VIDEO SYSTEM

THE NEW DIMENTSION IN VIDEO IMAGES

## CAMERA (INTERNAL & EXTERNAL) More Details, Better Visualization Fascinating Images-With Clear, Sharp Contrours



**E700/700  
Internal Camera**

**E700/500  
Internal Camera**

**E500/500  
Internal Camera**

### High Image Quality

- Camera With 10X Optical Zoom With 1950\*1080P HD Soluton
- Finely Textured Images With Clear, Sharp Cplors
- Remarkably Better Colors For Better Attention To Detail And A Brilliant Rendition

### Ultra High Definition

- Exmor R Sensor - Clearer Images In Every Condition
- Twice As Sensitive As Coneyventional Sensors
- Higher Image Quality In Low Light Conditions

### Easy Handling

- Easy Installation And Modification Or Retrofitting Of Existing OR Light Sustersms
- Mechanical And Electronical Image Rotation
- Fl;exible And Indepent Operation Via Remote Control
- Optional Operation Via Wall Control Unit



**E700  
Internal Camera**



**E500  
Internal Camera**



**E700  
Internal Camera**



**E500  
Internal Camera**

IMAGE SENSOR	SONY 1/2 8TYPE "EXMOR" CMOS, SUPPORT PROGRESSIVE MODE
IMAGE SOLUTION	1920*1080P, APPROX, 2,140,000 PIXELS
VIDEO OUTPUTS	20X OPTICAL ZOOM, 12X DIGITAL ZOOM
ASPECT VIDEO	SDI
FOCUS OPERATING	16:9
WHITE BALANCE	MANUAL & AUTO
REMOTE CONTROL	AUTO, ATW, INDOOR, OUTDOOR, ONE, PUSH WB, MANUAL WB
WIRELESS REMOTE CONTROL	STANDARD ACCESSORIES
HARD DISK FOR STORE	1T
POWER	6.8W
VOLTAGE	DC12-30W, 1.5A
INSTALLATION	INTERNAL & EXTERNAL OPTIONAL
MONITOR	21INCHES HANGING WITH ARM
SOUND COLLECTION	STANDARD



**E700/700  
External Camera**

**E700/500  
External Camera**

**E500/500  
External Camera**



**E700  
External Camera**



**E500  
External Camera**







## Future-ready to evolve with you

What if you had a lighting system that was modular, upgradeable, and expandable so that it could meet your ongoing needs with ease? You've found it. There are ways to customize this system today and in the future.

All of us here at MICARE are committed to you



## SIMPLY INGENUOUS

What if you had illumination in the OR that simply supported you throughout each surgical procedure? The MICARE PowerLED does this, delivering excellent color, contrast, clarity, and control.

A unique peninsula design provides optimal illumination at the surgical site, including deep cavity procedures. Advances in LED technology mean that the MICARE Powerled is able to optimize illumination through fewer LEDs than in the past.

You focus on patients. We focus on you. MICARE Lighting solutions bring together people and technology so that you have exactly what you need, when you need it, for the intelligent OR of today and tomorrow. From project design to implementation to service support, your success is our highest priority.

LIGHTING  
EXPERIENCE