

Technical Data Sheet

Favorit MULTI SF SAE 15W-40 API SF/CD



Packages:

1L, 4L, 5L, 20L, 60L, 208L

Meets the requirements and specifications:

SAE 15W-40 API SF/CD

[EN] Favorit MULTI SF SAE 15W-40 API SF/CD is a multipurpose multigrade engine oil with highly purified mineral basis for modern gasoline and diesel engines. Has good detergent-dispersing properties. Provides safe lubrication and cleanness of the engine components.

[RU] Favorit MULTI SF SAE 15W-40 API SF/CD всесезонное универсальное моторное масло на минеральной основе, разработанное для применения в бензиновых и дизельных двигателях автомобилей отечественного и зарубежного производства. Обладает высокими моющей-диспергирующими свойствами. Обеспечивает надежную смазку и чистоту деталей двигателя.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	101.07
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	14.29
Viscosity index	STB 1797	144.96
Flash poin, °C	GOST 4333	226
Pour point, °C	GOST 20287	-30
TBN, g KOH/kg	GOST 11362	5.8
Density at 20°C, kg/m ³	GOST 3900	875

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.