

Specificații tehnice F4.1

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1719407888063 din 26 iunie 2024

Obiectul achiziției: Echipamentului de radioteleviziune (repetat) . Cod CPV : 32200000-5 - Aparate de emisie pentru radiotelefonie, radiotelegrafie, radiodifuziune și televiziune . Licitație deschisă.

Denumirea bunurilor/ serviciilor	Denumirea modelului bunului/ serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Bunuri/ servicii						
Echipamentului de radioteleviziune (repetat)						
Lotul nr. 2						
2.1. Video lens	70-200mm f/4 Macro G OSS II Lens with 72mm Filter Kit	PRC	Sony	Maximum Aperture f/4 Minimum Aperture f/22 Lens Mount E Mount Lens Format Coverage Full-Frame Angle of View 34° to 12° 30' Minimum Focus Distance 26 cm Maximum Magnification 0.5x Optical Design 19 Elements in 13 Groups Diaphragm Blades 9, Rounded Focus Type Autofocus Image Stabilization Yes Tripod Collar Removable and Rotating Filter Size 72 mm (Front) (included transparent filter)	Maximum Aperture f/4 Minimum Aperture f/22 Lens Mount E Mount Lens Format Coverage Full-Frame Angle of View 34° to 12° 30' Minimum Focus Distance 26 cm Maximum Magnification 0.5x Optical Design 19 Elements in 13 Groups Diaphragm Blades 9, Rounded Focus Type Autofocus Image Stabilization Yes Tripod Collar Removable and Rotating Include -72 mm (Front) Filter : Tiffen 72 mmUV Protector filter Garanție : 24 luni	

2.2. Filter video lens	82mm Black Pro-Mist 1/8 Filter	USA/ PRC	Tiffen	Filter Type Mist (Grade 1/8) Filter Factor Not Specified by Manufacturer Circular Size 82 mm Filter Thread Front Accessory Thread / Bayonet 82 mm Filter Material Glass Ring Material Aluminum Knurling Top	Filter Type Mist (Grade 1/8) Filter Factor Not Specified by Manufacturer Circular Size 82 mm Filter Thread Front Accessory Thread / Bayonet 82 mm Filter Material Glass Ring Material Aluminum Knurling Top Garanție : 24 luni
Lotul nr. 3					
3.1. Light equipment	PL-E90 3 Kit 90W Portable Bi-color SMD Panel LED light kit	PRC	SWIT	Portable Bi-color SMD Panel LED light (3 light in kit) 480pcs edge mounted SMD-LEDs Unique 90° light guide technology 90W power, 2200Lux @ 1meter 0-100% flick-free dimming, 70° effective wide beam angle 2700K-6500K continuously adjustable Super high CRI Ra 98, TLCI 99 LCD display color, dimmer and battery info Power by V-mount / Gold mount battery Strong all-metal housing with U-stand Provide portable 3-light kit Include AC-DC adator	Portable Bi-color SMD Panel LED light (3 light in kit) 480pcs edge mounted SMD-LEDs Unique 90° light guide technology 90W power, 2200Lux @ 1meter 0-100% flick-free dimming, 70° effective wide beam angle 2700K-6500K continuously adjustable Super high CRI Ra 98, TLCI 99 LCD display color, dimmer and battery info Power by V-mount / Gold mount battery Strong all-metal housing with U-stand Provide portable 3-light kit Include AC-DC adator Garanție : 12 luni
3.2. Stand light	Light Stand 285 cm Steel & Aluminum (HD)	PRC	Cinelight	Maximum Working Height 285 cm Load Capacity min 10 kg Number of Sections 4 Leg Shape - Round Finish - Black Material - Metal	Stand type: Baby stand Mounting : Stud 16mm (5/8") Maximum height : 285 cm Minimum height : 109 cm Maximum payload : 10 kg Folded length : 109 cm Footprint diameter : 120 cm Column diameters : 25 / 30 / 35 mm Legs diameter : 22 mm Collapsing protection : Spring Material : Steel & Aluminum Color :Black .Weight : 4.8 kg Garanție : 24 luni
3.3. Flag	I780B 30X36" Solid Black Flag	Italia	Avenger	76X90 cm Black Flag, Weight 1.6 kg, Height 90 cm	76X90 cm flag Lighting control tool

					Made of steel spring tubes Useful in combination with grip heads Weight 1.6 kg, Height 90 cm Garanție : 12 luni
Lotul nr. 4					
4.1. V-mount Plate	Camera Battery Slide Pro for Sony FX6 (V-Mount)	PRC	Wooden	Power Output DC Jack: 19.5 VDC Camera Power Method Connector Inputs/Outputs 3 x D-Tap Plate Front / Battery Mount V-Mount Number of Battery Bays 1 Indicator LED	Power Output DC Jack: 19.5 VDC Camera Power Method Connector Inputs/Outputs 3 x D-Tap Plate Front / Battery Mount V-Mount Number of Battery Bays 1 Indicator LED Garanție : 12 luni
4.2. Charger V-Mount Kit	SWXCompact Quad MicroBattery Fast Charger (V-Mount)	PRC	Core	Mount / Series Type V-Mount Simultaneously Charge 4 Batteries Chemistry Lithium-Ion Included Battery Capacity 4 x 6600 mAh / 98 Wh Output Voltage 14.8 VDC; 10 A 1 x D-Tap Input/Output 1 x USB Type-A Output USB Output 5 V, 3 A	Chemistry : Lithium-Ion Charger Compatibility : V-Mount Number of Battery Bays : 4 Multi-Bay Charging Modes : Simultaneous Charger Power Source : AC Power (Cable Included) Charger Power I/O : 1x IEC Female Input 100 to 240 VAC, 50 / 60 Hz at 2.2 A Charger Included Adapter / Cable 1x USA Type-A/B Plug to IEC Male Cable Battery Output Voltage : 16.8 VDC at 2.6 A Recharge Time : 2.5 Hours (98 Wh Batteries) Included : SWX NANO Micro 98Wh Li-Ion 4 x Batteries 6600 mAh / 98 Wh Output Voltage 14.8 VDC; 10 A 1 x D-Tap Input/Output 1 x USB Type-A Output USB Output 5 V, 3 A Garanție : 12 luni
4.3. Battery V Mount	NERO-M Cine V-Lock	PRC	Hedbox	Mount Type V – Mount (V-lock holder) Power Meter Blue Color 4-LED Power Monitor (Display 100%, 75%, 50%, or 25% SOC capacity) Product Color Dark Grey Bat. Cell Model LG High Load Stand 18650 x 16 Bat. Cell Chemistry Lithium-Ion Output Voltage 14.8V DC	Mount Type :V – Mount Cameras Compatible (V-lock holder) Power Meter : Blue Color 4-LED Power Monitor (Display 100%, 75%, 50%, or 25% SOC capacity) Product Color : Dark Grey Bat. Cell Model : LG High Load Stand 18650 x 16 Bat. Cell Chemistry : Lithium-Ion

				<p>Minimum Out Voltage 10.0V DC (Auto Power Control) Capacity 10400 mAh / 150 Wh Maximum Load 13A / 190W USB Output 5V, 12W / 2.4A max D-Tap Output 14.8V, 100W / 6.8A max Internal Protection: Cells Framing Construction System Maximum Charge: 16.8V / 3.0A Include Dual-Channel Portable Charger for V-Mount Charger Power 1x IEC Female Input 100 to 240 VAC, 50 / 60 Hz 1x XLR 4-Pin Female Output 16.7 VDC at 4.5 A (75W)</p>	<p>Output Voltage :14.8V DC Minimum Out Voltage : 10.0V DC (Auto Power Control) Capacity : 10400 mAh / 150 Wh Maximum Load : 13A / 190W USB Output :5V, 12W / 2.4A max (Dust Protection Cover) D-Tap Output :14.8V, 100W / 6.8A max (Dust Protection Cover) Internal Protection :Cells Framing Construction System Maximum Charge :16.8V / 3.0A Include : Hedbox Dual Digital V-Mount Battery Charger with Power Bank Function Charger Compatibility : V-Mount Number of Battery Bays : 2 Multi-Bay Charging Modes : Simultaneous Charger Power Source : AC Power (Cable Included) Charger Power I/O : 1x IEC Male Input 100 to 240 VAC, 50 / 60 Hz at 1.5 A 1x XLR 4-Pin Female Output : 16.8 VDC at 4.5 A (75 W) Charger Included Adapter / Cable : 1x XLR 4-Pin Male to XLR 4-Pin Female Cable (10' / 3 m) .Indicator : LED Garanție : 12 luni</p>
4.4. Wireless Power Bank	10W Wireless Power Bank 10000 WPB15PDZM	PRC	Xiaomi	<p>Battery capacity 35.2Wh/36Wh, 9800mAh/10000mAh Input port Type-C Wired output (USB-A): 5V=3A, 9V=2.23A, 12V=1.67A, max. (Type-C): 5V=3A, 9V=2.23A, 12V=1.67A, 10V=2.25A max. (Dual port): 5V=3A .Output port USB-A/Type-C .Wireless output 10W MAX</p>	<p>Battery capacity 35.2Wh/36Wh, 9800mAh/10000mAh Input port Type-C Wired output (USB-A): 5V=3A, 9V=2.23A, 12V=1.67A, max. (Type-C): 5V=3A, 9V=2.23A, 12V=1.67A, 10V=2.25A max. (Dual port): 5V=3A .Output port USB-A/Type-C .Wireless output 10W MAX Garanție : 12 luni</p>

Semnat: _____ Numele, Prenumele: Cîrlig Ion , În calitate de : Director

Ofertantul: „WEST BUY” SRL Adresa: mun.Chisinau , bd.Mircea cel Batrin 39 ap 143

Data : 16.07.2024